
argo-models

Release 2.7.5

eterna2 <eterna2@hotmail.com>

May 11, 2020

CONTENTS:

1	API Reference	1
1.1	argo	1
1.1.1	Subpackages	1
1.1.1.1	argo.models	1
1.1.1.1.1	Submodules	1
1.1.1.1.1.1	argo.models.cronv1alpha1_create_cron_workflow_request	1
1.1.1.1.1.2	Module Contents	1
1.1.1.1.1.3	argo.models.cronv1alpha1_lint_cron_workflow_request	2
1.1.1.1.1.4	Module Contents	2
1.1.1.1.1.5	argo.models.cronv1alpha1_update_cron_workflow_request	3
1.1.1.1.1.6	Module Contents	3
1.1.1.1.1.7	argo.models.google_protobuf_any	4
1.1.1.1.1.8	Module Contents	4
1.1.1.1.1.9	argo.models.grpc_gateway_runtime_stream_error	4
1.1.1.1.1.10	Module Contents	5
1.1.1.1.1.11	argo.models.v1alpha1_archive_strategy	6
1.1.1.1.1.12	Module Contents	6
1.1.1.1.1.13	argo.models.v1alpha1_arguments	6
1.1.1.1.1.14	Module Contents	6
1.1.1.1.1.15	argo.models.v1alpha1_artifact	7
1.1.1.1.1.16	Module Contents	7
1.1.1.1.1.17	argo.models.v1alpha1_artifact_location	8
1.1.1.1.1.18	Module Contents	8
1.1.1.1.1.19	argo.models.v1alpha1_artifact_repository_ref	10
1.1.1.1.1.20	Module Contents	10
1.1.1.1.1.21	argo.models.v1alpha1_artifactory_artifact	11
1.1.1.1.1.22	Module Contents	11
1.1.1.1.1.23	argo.models.v1alpha1_artifactory_auth	11
1.1.1.1.1.24	Module Contents	12
1.1.1.1.1.25	argo.models.v1alpha1_backoff	12
1.1.1.1.1.26	Module Contents	12
1.1.1.1.1.27	argo.models.v1alpha1_continue_on	13
1.1.1.1.1.28	Module Contents	13
1.1.1.1.1.29	argo.models.v1alpha1_counter	14
1.1.1.1.1.30	Module Contents	14
1.1.1.1.1.31	argo.models.v1alpha1_cron_workflow	14
1.1.1.1.1.32	Module Contents	14
1.1.1.1.1.33	argo.models.v1alpha1_cron_workflow_list	15
1.1.1.1.1.34	Module Contents	15
1.1.1.1.1.35	argo.models.v1alpha1_cron_workflow_spec	16

1.1.1.1.1.36	Module Contents	16
1.1.1.1.1.37	argo.models.v1alpha1_cron_workflow_status	18
1.1.1.1.1.38	Module Contents	18
1.1.1.1.1.39	argo.models.v1alpha1_dag_task	18
1.1.1.1.1.40	Module Contents	19
1.1.1.1.1.41	argo.models.v1alpha1_dag_template	20
1.1.1.1.1.42	Module Contents	21
1.1.1.1.1.43	argo.models.v1alpha1_executor_config	21
1.1.1.1.1.44	Module Contents	21
1.1.1.1.1.45	argo.models.v1alpha1_gauge	22
1.1.1.1.1.46	Module Contents	22
1.1.1.1.1.47	argo.models.v1alpha1_gcs_artifact	23
1.1.1.1.1.48	Module Contents	23
1.1.1.1.1.49	argo.models.v1alpha1_gcs_bucket	23
1.1.1.1.1.50	Module Contents	24
1.1.1.1.1.51	argo.models.v1alpha1_git_artifact	24
1.1.1.1.1.52	Module Contents	24
1.1.1.1.1.53	argo.models.v1alpha1_hdfs_artifact	26
1.1.1.1.1.54	Module Contents	26
1.1.1.1.1.55	argo.models.v1alpha1_hdfs_config	26
1.1.1.1.1.56	Module Contents	27
1.1.1.1.1.57	argo.models.v1alpha1_hdfs_krb_config	27
1.1.1.1.1.58	Module Contents	28
1.1.1.1.1.59	argo.models.v1alpha1_histogram	29
1.1.1.1.1.60	Module Contents	29
1.1.1.1.1.61	argo.models.v1alpha1_http_artifact	30
1.1.1.1.1.62	Module Contents	30
1.1.1.1.1.63	argo.models.v1alpha1_info_response	30
1.1.1.1.1.64	Module Contents	30
1.1.1.1.1.65	argo.models.v1alpha1_inputs	31
1.1.1.1.1.66	Module Contents	31
1.1.1.1.1.67	argo.models.v1alpha1_item	32
1.1.1.1.1.68	Module Contents	32
1.1.1.1.1.69	argo.models.v1alpha1_item_value	33
1.1.1.1.1.70	Module Contents	33
1.1.1.1.1.71	argo.models.v1alpha1_link	34
1.1.1.1.1.72	Module Contents	34
1.1.1.1.1.73	argo.models.v1alpha1_log_entry	35
1.1.1.1.1.74	Module Contents	35
1.1.1.1.1.75	argo.models.v1alpha1_metadata	35
1.1.1.1.1.76	Module Contents	36
1.1.1.1.1.77	argo.models.v1alpha1_metric_label	36
1.1.1.1.1.78	Module Contents	36
1.1.1.1.1.79	argo.models.v1alpha1_metrics	37
1.1.1.1.1.80	Module Contents	37
1.1.1.1.1.81	argo.models.v1alpha1_node_status	37
1.1.1.1.1.82	Module Contents	38
1.1.1.1.1.83	argo.models.v1alpha1_oss_artifact	41
1.1.1.1.1.84	Module Contents	41
1.1.1.1.1.85	argo.models.v1alpha1_oss_bucket	42
1.1.1.1.1.86	Module Contents	42
1.1.1.1.1.87	argo.models.v1alpha1_outputs	43
1.1.1.1.1.88	Module Contents	43
1.1.1.1.1.89	argo.models.v1alpha1_parameter	43

1.1.1.1.1.90	Module Contents	44
1.1.1.1.1.91	argo.models.v1alpha1_pod_gc	45
1.1.1.1.1.92	Module Contents	45
1.1.1.1.1.93	argo.models.v1alpha1_prometheus	45
1.1.1.1.1.94	Module Contents	45
1.1.1.1.1.95	argo.models.v1alpha1_raw_artifact	47
1.1.1.1.1.96	Module Contents	47
1.1.1.1.1.97	argo.models.v1alpha1_resource_template	47
1.1.1.1.1.98	Module Contents	47
1.1.1.1.1.99	argo.models.v1alpha1_retry_strategy	49
1.1.1.1.1.100	Module Contents	49
1.1.1.1.1.101	argo.models.v1alpha1_s3_artifact	49
1.1.1.1.1.102	Module Contents	50
1.1.1.1.1.103	argo.models.v1alpha1_s3_bucket	50
1.1.1.1.1.104	Module Contents	50
1.1.1.1.1.105	argo.models.v1alpha1_script_template	52
1.1.1.1.1.106	Module Contents	52
1.1.1.1.1.107	argo.models.v1alpha1_sequence	52
1.1.1.1.1.108	Module Contents	53
1.1.1.1.1.109	argo.models.v1alpha1_suspend_template	53
1.1.1.1.1.110	Module Contents	54
1.1.1.1.1.111	argo.models.v1alpha1_template	54
1.1.1.1.1.112	Module Contents	55
1.1.1.1.1.113	argo.models.v1alpha1_template_ref	59
1.1.1.1.1.114	Module Contents	60
1.1.1.1.1.115	argo.models.v1alpha1_ttl_strategy	60
1.1.1.1.1.116	Module Contents	61
1.1.1.1.1.117	argo.models.v1alpha1_user_container	61
1.1.1.1.1.118	Module Contents	62
1.1.1.1.1.119	argo.models.v1alpha1_value_from	62
1.1.1.1.1.120	Module Contents	62
1.1.1.1.1.121	argo.models.v1alpha1_workflow	63
1.1.1.1.1.122	Module Contents	63
1.1.1.1.1.123	argo.models.v1alpha1_workflow_condition	64
1.1.1.1.1.124	Module Contents	64
1.1.1.1.1.125	argo.models.v1alpha1_workflow_create_request	65
1.1.1.1.1.126	Module Contents	65
1.1.1.1.1.127	argo.models.v1alpha1_workflow_lint_request	66
1.1.1.1.1.128	Module Contents	66
1.1.1.1.1.129	argo.models.v1alpha1_workflow_list	67
1.1.1.1.1.130	Module Contents	67
1.1.1.1.1.131	argo.models.v1alpha1_workflow_resubmit_request	67
1.1.1.1.1.132	Module Contents	68
1.1.1.1.1.133	argo.models.v1alpha1_workflow_resume_request	68
1.1.1.1.1.134	Module Contents	69
1.1.1.1.1.135	argo.models.v1alpha1_workflow_retry_request	69
1.1.1.1.1.136	Module Contents	70
1.1.1.1.1.137	argo.models.v1alpha1_workflow_spec	70
1.1.1.1.1.138	Module Contents	71
1.1.1.1.1.139	argo.models.v1alpha1_workflow_status	76
1.1.1.1.1.140	Module Contents	76
1.1.1.1.1.141	argo.models.v1alpha1_workflow_step	78
1.1.1.1.1.142	Module Contents	78
1.1.1.1.1.143	argo.models.v1alpha1_workflow_stop_request	80

1.1.1.1.1.144	Module Contents	80
1.1.1.1.1.145	argo.models.v1alpha1_workflow_suspend_request	81
1.1.1.1.1.146	Module Contents	81
1.1.1.1.1.147	argo.models.v1alpha1_workflow_template	81
1.1.1.1.1.148	Module Contents	82
1.1.1.1.1.149	argo.models.v1alpha1_workflow_template_create_request	82
1.1.1.1.1.150	Module Contents	82
1.1.1.1.1.151	argo.models.v1alpha1_workflow_template_lint_request	83
1.1.1.1.1.152	Module Contents	83
1.1.1.1.1.153	argo.models.v1alpha1_workflow_template_list	84
1.1.1.1.1.154	Module Contents	84
1.1.1.1.1.155	argo.models.v1alpha1_workflow_template_spec	85
1.1.1.1.1.156	Module Contents	85
1.1.1.1.1.157	argo.models.v1alpha1_workflow_template_update_request	85
1.1.1.1.1.158	Module Contents	85
1.1.1.1.1.159	argo.models.v1alpha1_workflow_terminate_request	86
1.1.1.1.1.160	Module Contents	86
1.1.1.1.1.161	argo.models.v1alpha1_workflow_watch_event	87
1.1.1.1.1.162	Module Contents	87
1.1.1.1.2	Package Contents	87
1.1.2	Submodules	148
1.1.2.1	argo.configuration	148
1.1.2.1.1	Module Contents	148
2	argo-models	151
2.1	Developer notes	151
2.2	License	152
3	Indices and tables	153
	Python Module Index	155
	Index	157

API REFERENCE

This page contains auto-generated API reference documentation¹.

1.1 argo

argo namespaced package

1.1.1 Subpackages

1.1.1.1 `argo.models`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1 Submodules

1.1.1.1.1.1 `argo.models.cronv1alpha1_create_cron_workflow_request`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.2 Module Contents

class `argo.models.cronv1alpha1_create_cron_workflow_request.Cronv1alpha1CreateCronWorkflowRequest`

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Cronv1alpha1CreateCronWorkflowRequest - a model defined in OpenAPI

¹ Created with `sphinx-autoapi`

```
openapi_types
attribute_map
property create_options (self)
    Gets the create_options of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Returns The create_options of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Return type kubernetes.client.models.V1CreateOptions
property cron_workflow (self)
    Gets the cron_workflow of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Returns The cron_workflow of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Return type V1alpha1CronWorkflow
property namespace (self)
    Gets the namespace of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Returns The namespace of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501
    Return type str
to_dict (self)
    Returns the model properties as a dict
to_str (self)
    Returns the string representation of the model
```

1.1.1.1.3 argo.models.cronv1alpha1_lint_cron_workflow_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.4 Module Contents

```
class argo.models.cronv1alpha1_lint_cron_workflow_request.Cronv1alpha1LintCronWorkflowRequest
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Cronv1alpha1LintCronWorkflowRequest - a model defined in OpenAPI

```
openapi_types
attribute_map
property cron_workflow (self)
    Gets the cron_workflow of this Cronv1alpha1LintCronWorkflowRequest. # noqa: E501
    Returns The cron_workflow of this Cronv1alpha1LintCronWorkflowRequest. # noqa: E501
    Return type V1alpha1CronWorkflow
property namespace (self)
    Gets the namespace of this Cronv1alpha1LintCronWorkflowRequest. # noqa: E501
```


Returns The namespace of this Cronv1alpha1LintCronWorkflowRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.5 argo.models.cronv1alpha1_update_cron_workflow_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.6 Module Contents

class argo.models.cronv1alpha1_update_cron_workflow_request.Cronv1alpha1UpdateCronWorkflowRequest

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Cronv1alpha1UpdateCronWorkflowRequest - a model defined in OpenAPI

openapi_types

attribute_map

property cron_workflow (*self*)

Gets the cron_workflow of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The cron_workflow of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type *V1alpha1CronWorkflow*

property name (*self*)

Gets the name of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The name of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The namespace of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.7 argo.models.google_protobuf_any

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.8 Module Contents

class argo.models.google_protobuf_any.**GoogleProtobufAny** (*type_url=None,*
value=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

GoogleProtobufAny - a model defined in OpenAPI

openapi_types

attribute_map

property type_url (*self*)

Gets the type_url of this GoogleProtobufAny. # noqa: E501

Returns The type_url of this GoogleProtobufAny. # noqa: E501

Return type str

property value (*self*)

Gets the value of this GoogleProtobufAny. # noqa: E501

Returns The value of this GoogleProtobufAny. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.9 argo.models.grpc_gateway_runtime_stream_error

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.10 Module Contents

```
class argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError (details=None,
                                                                                   grpc_code=None,
                                                                                   http_code=None,
                                                                                   http_status=None,
                                                                                   message=None,
                                                                                   sage=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

GrpcGatewayRuntimeStreamError - a model defined in OpenAPI

openapi_types

attribute_map

property details (*self*)

Gets the details of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The details of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type list[*GoogleProtobufAny*]

property grpc_code (*self*)

Gets the grpc_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The grpc_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type int

property http_code (*self*)

Gets the http_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The http_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type int

property http_status (*self*)

Gets the http_status of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The http_status of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type str

property message (*self*)

Gets the message of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The message of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.11 argo.models.v1alpha1_archive_strategy

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.12 Module Contents

```
class argo.models.v1alpha1_archive_strategy.V1alpha1ArchiveStrategy(_none=None,  
                                                                    tar=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArchiveStrategy - a model defined in OpenAPI

openapi_types

attribute_map

property tar(self)

Gets the tar of this V1alpha1ArchiveStrategy. # noqa: E501

Returns The tar of this V1alpha1ArchiveStrategy. # noqa: E501

Return type object

to_dict(self)

Returns the model properties as a dict

to_str(self)

Returns the string representation of the model

1.1.1.1.13 argo.models.v1alpha1_arguments

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.14 Module Contents

```
class argo.models.v1alpha1_arguments.V1alpha1Arguments(artifacts=None,  paramete-  
                                                         ters=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Arguments - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts(self)

Gets the artifacts of this V1alpha1Arguments. # noqa: E501

Returns The artifacts of this V1alpha1Arguments. # noqa: E501

Return type list[*V1alpha1Artifact*]

property parameters (*self*)

Gets the parameters of this V1alpha1Arguments. # noqa: E501

Returns The parameters of this V1alpha1Arguments. # noqa: E501

Return type list[*V1alpha1Parameter*]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.15 argo.models.v1alpha1_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.16 Module Contents

```
class argo.models.v1alpha1_artifact.V1alpha1Artifact (archive=None,          arti-
                                                    fact_location=None,
                                                    _from=None,
                                                    global_name=None,
                                                    mode=None,      name=None,
                                                    optional=None, path=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Artifact - a model defined in OpenAPI

openapi_types

attribute_map

property archive (*self*)

Gets the archive of this V1alpha1Artifact. # noqa: E501

Returns The archive of this V1alpha1Artifact. # noqa: E501

Return type *V1alpha1ArchiveStrategy*

property artifact_location (*self*)

Gets the artifact_location of this V1alpha1Artifact. # noqa: E501

Returns The artifact_location of this V1alpha1Artifact. # noqa: E501

Return type *V1alpha1ArtifactLocation*

property global_name (*self*)

Gets the global_name of this V1alpha1Artifact. # noqa: E501

Returns The global_name of this V1alpha1Artifact. # noqa: E501

Return type str

property mode (*self*)

Gets the mode of this V1alpha1Artifact. # noqa: E501

mode bits to use on this file, must be a value between 0 and 0777 set when loading input artifacts. # noqa: E501

Returns The mode of this V1alpha1Artifact. # noqa: E501

Return type int

property name (*self*)

Gets the name of this V1alpha1Artifact. # noqa: E501

name of the artifact. must be unique within a template's inputs/outputs. # noqa: E501

Returns The name of this V1alpha1Artifact. # noqa: E501

Return type str

property optional (*self*)

Gets the optional of this V1alpha1Artifact. # noqa: E501

Returns The optional of this V1alpha1Artifact. # noqa: E501

Return type bool

property path (*self*)

Gets the path of this V1alpha1Artifact. # noqa: E501

Returns The path of this V1alpha1Artifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.17 argo.models.v1alpha1_artifact_location

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.18 Module Contents

```
class argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation (archive_logs=None,
                                                                    arti-
                                                                    fac-
                                                                    tory=None,
                                                                    gcs=None,
                                                                    git=None,
                                                                    hdfs=None,
                                                                    http=None,
                                                                    oss=None,
                                                                    raw=None,
                                                                    s3=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactLocation - a model defined in OpenAPI

openapi_types

attribute_map

property archive_logs (*self*)

Gets the archive_logs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The archive_logs of this V1alpha1ArtifactLocation. # noqa: E501

Return type bool

property artifactory (*self*)

Gets the artifactory of this V1alpha1ArtifactLocation. # noqa: E501

Returns The artifactory of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1ArtifactoryArtifact*

property gcs (*self*)

Gets the gcs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The gcs of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1GCSArtifact*

property git (*self*)

Gets the git of this V1alpha1ArtifactLocation. # noqa: E501

Returns The git of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1GitArtifact*

property hdfs (*self*)

Gets the hdfs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The hdfs of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1HDFSArtifact*

property http (*self*)

Gets the http of this V1alpha1ArtifactLocation. # noqa: E501

Returns The http of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1HTTPArtifact*

property oss (*self*)

Gets the oss of this V1alpha1ArtifactLocation. # noqa: E501

Returns The oss of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1OSSArtifact*

property raw (*self*)

Gets the raw of this V1alpha1ArtifactLocation. # noqa: E501

Returns The raw of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1RawArtifact*

property s3 (*self*)

Gets the s3 of this V1alpha1ArtifactLocation. # noqa: E501

Returns The s3 of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1S3Artifact*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.19 argo.models.v1alpha1_artifact_repository_ref

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.20 Module Contents

class argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef (*config_map=None*, *key=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactRepositoryRef - a model defined in OpenAPI

openapi_types

attribute_map

property config_map (*self*)

Gets the config_map of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Returns The config_map of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Return type str

property key (*self*)

Gets the key of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Returns The key of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.21 argo.models.v1alpha1_artifactifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.22 Module Contents

class argo.models.v1alpha1_artifactifact.V1alpha1Artifactifact (*artifact_auth=None, url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Artifactifact - a model defined in OpenAPI

openapi_types

attribute_map

property artifact_auth (*self*)

Gets the artifact_auth of this V1alpha1Artifactifact. # noqa: E501

Returns The artifact_auth of this V1alpha1Artifactifact. # noqa: E501

Return type *V1alpha1ArtifactAuth*

property url (*self*)

Gets the url of this V1alpha1Artifactifact. # noqa: E501

Returns The url of this V1alpha1Artifactifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.23 argo.models.v1alpha1_artifact_auth

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.24 Module Contents

```
class argo.models.v1alpha1_artifactory_auth.V1alpha1ArtifactoryAuth (password_secret=None,
                                                                    user-
                                                                    name_secret=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactoryAuth - a model defined in OpenAPI

openapi_types

attribute_map

property password_secret (*self*)

Gets the password_secret of this V1alpha1ArtifactoryAuth. # noqa: E501

Returns The password_secret of this V1alpha1ArtifactoryAuth. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property username_secret (*self*)

Gets the username_secret of this V1alpha1ArtifactoryAuth. # noqa: E501

Returns The username_secret of this V1alpha1ArtifactoryAuth. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.25 argo.models.v1alpha1_backoff

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.26 Module Contents

```
class argo.models.v1alpha1_backoff.V1alpha1Backoff (duration=None,    factor=None,
                                                    max_duration=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Backoff - a model defined in OpenAPI

openapi_types

attribute_map

property duration (*self*)

Gets the duration of this V1alpha1Backoff. # noqa: E501

Returns The duration of this V1alpha1Backoff. # noqa: E501

Return type str

property factor (*self*)

Gets the factor of this V1alpha1Backoff. # noqa: E501

Returns The factor of this V1alpha1Backoff. # noqa: E501

Return type int

property max_duration (*self*)

Gets the max_duration of this V1alpha1Backoff. # noqa: E501

Returns The max_duration of this V1alpha1Backoff. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.27 argo.models.v1alpha1_continue_on

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.28 Module Contents

class argo.models.v1alpha1_continue_on.V1alpha1ContinueOn (*error=None*,
failed=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ContinueOn - a model defined in OpenAPI

openapi_types

attribute_map

property error (*self*)

Gets the error of this V1alpha1ContinueOn. # noqa: E501

Returns The error of this V1alpha1ContinueOn. # noqa: E501

Return type bool

property failed (*self*)

Gets the failed of this V1alpha1ContinueOn. # noqa: E501

Returns The failed of this V1alpha1ContinueOn. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.29 argo.models.v1alpha1_counter

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.30 Module Contents

class argo.models.v1alpha1_counter.V1alpha1Counter (*value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Counter - a model defined in OpenAPI

openapi_types

attribute_map

property value (*self*)

Gets the value of this V1alpha1Counter. # noqa: E501

Returns The value of this V1alpha1Counter. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.31 argo.models.v1alpha1_cron_workflow

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.32 Module Contents

class argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow (*metadata=None,*
spec=None,
status=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflow - a model defined in OpenAPI

openapi_types

attribute_map

property metadata (*self*)

Gets the metadata of this V1alpha1CronWorkflow. # noqa: E501

Returns The metadata of this V1alpha1CronWorkflow. # noqa: E501

Return type `kubernetes.client.models.V1ObjectMeta`

property spec (*self*)

Gets the spec of this V1alpha1CronWorkflow. # noqa: E501

Returns The spec of this V1alpha1CronWorkflow. # noqa: E501

Return type *V1alpha1CronWorkflowSpec*

property status (*self*)

Gets the status of this V1alpha1CronWorkflow. # noqa: E501

Returns The status of this V1alpha1CronWorkflow. # noqa: E501

Return type *V1alpha1CronWorkflowStatus*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.33 `argo.models.v1alpha1_cron_workflow_list`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.34 Module Contents

class `argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList` (*items=None, meta-data=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowList - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)

Gets the items of this V1alpha1CronWorkflowList. # noqa: E501

Returns The items of this V1alpha1CronWorkflowList. # noqa: E501

Return type `list[V1alpha1CronWorkflow]`

property metadata (*self*)

Gets the metadata of this V1alpha1CronWorkflowList. # noqa: E501

Returns The metadata of this V1alpha1CronWorkflowList. # noqa: E501

Return type `kubernetes.client.models.V1ListMeta`

to_dict (*self*)

Returns the model properties as a dict

```
to_str(self)
    Returns the string representation of the model
```

1.1.1.1.1.35 argo.models.v1alpha1_cron_workflow_spec

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.36 Module Contents

```
class argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec (concurrency_policy=None,
                                                                    failed_jobs_history_limit=None,
                                                                    schedule=None,
                                                                    starting_deadline_seconds=None,
                                                                    success_jobs_history_limit=None,
                                                                    suspend=None,
                                                                    time_zone=None,
                                                                    workflow_meta=None,
                                                                    workflow_spec=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowSpec - a model defined in OpenAPI

openapi_types

attribute_map

property concurrency_policy(self)

Gets the concurrency_policy of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The concurrency_policy of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property failed_jobs_history_limit(self)

Gets the failed_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The failed_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type int

property schedule(self)

Gets the schedule of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The schedule of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property starting_deadline_seconds (*self*)

Gets the starting_deadline_seconds of this V1alpha1CronWorkflowSpec. # noqa: E501

StartingDeadlineSeconds is the K8s-style deadline that will limit the time a CronWorkflow will be run after its original scheduled time if it is missed. # noqa: E501

Returns The starting_deadline_seconds of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property successful_jobs_history_limit (*self*)

Gets the successful_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The successful_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type int

property suspend (*self*)

Gets the suspend of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The suspend of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type bool

property timezone (*self*)

Gets the timezone of this V1alpha1CronWorkflowSpec. # noqa: E501

Timezone is the timezone against which the cron schedule will be calculated, e.g. "Asia/Tokyo". Default is machine's local time. # noqa: E501

Returns The timezone of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property workflow_meta (*self*)

Gets the workflow_meta of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The workflow_meta of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1ObjectMeta

property workflow_spec (*self*)

Gets the workflow_spec of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The workflow_spec of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type *V1alpha1WorkflowSpec*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.37 argo.models.v1alpha1_cron_workflow_status

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.38 Module Contents

class argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus (*active=None, last_scheduled_time=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowStatus - a model defined in OpenAPI

openapi_types

attribute_map

property active (*self*)

Gets the active of this V1alpha1CronWorkflowStatus. # noqa: E501

Returns The active of this V1alpha1CronWorkflowStatus. # noqa: E501

Return type list[kubernetes.client.models.V1ObjectReference]

property last_scheduled_time (*self*)

Gets the last_scheduled_time of this V1alpha1CronWorkflowStatus. # noqa: E501

Returns The last_scheduled_time of this V1alpha1CronWorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.39 argo.models.v1alpha1_dag_task

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.40 Module Contents

```
class argo.models.v1alpha1_dag_task.V1alpha1DAGTask (arguments=None,      con-
                                                    tinue_on=None,      dependen-
                                                    cies=None,      name=None,
                                                    on_exit=None,  template=None,
                                                    template_ref=None,
                                                    when=None,  with_items=None,
                                                    with_param=None,
                                                    with_sequence=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1DAGTask - a model defined in OpenAPI

openapi_types

attribute_map

property arguments (*self*)

Gets the arguments of this V1alpha1DAGTask. # noqa: E501

Returns The arguments of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1Arguments*

property continue_on (*self*)

Gets the continue_on of this V1alpha1DAGTask. # noqa: E501

Returns The continue_on of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1ContinueOn*

property dependencies (*self*)

Gets the dependencies of this V1alpha1DAGTask. # noqa: E501

Returns The dependencies of this V1alpha1DAGTask. # noqa: E501

Return type list[str]

property name (*self*)

Gets the name of this V1alpha1DAGTask. # noqa: E501

Returns The name of this V1alpha1DAGTask. # noqa: E501

Return type str

property on_exit (*self*)

Gets the on_exit of this V1alpha1DAGTask. # noqa: E501

OnExit is a template reference which is invoked at the end of the template, irrespective of the success, failure, or error of the primary template. # noqa: E501

Returns The on_exit of this V1alpha1DAGTask. # noqa: E501

Return type str

property template (*self*)

Gets the template of this V1alpha1DAGTask. # noqa: E501

Returns The template of this V1alpha1DAGTask. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1DAGTask. # noqa: E501

Returns The template_ref of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1TemplateRef*

property when (*self*)

Gets the when of this V1alpha1DAGTask. # noqa: E501

Returns The when of this V1alpha1DAGTask. # noqa: E501

Return type str

property with_items (*self*)

Gets the with_items of this V1alpha1DAGTask. # noqa: E501

Returns The with_items of this V1alpha1DAGTask. # noqa: E501

Return type list[*V1alpha1Item*]

property with_param (*self*)

Gets the with_param of this V1alpha1DAGTask. # noqa: E501

WithParam expands a task into multiple parallel tasks from the value in the parameter, which is expected to be a JSON list. # noqa: E501

Returns The with_param of this V1alpha1DAGTask. # noqa: E501

Return type str

property with_sequence (*self*)

Gets the with_sequence of this V1alpha1DAGTask. # noqa: E501

Returns The with_sequence of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1Sequence*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.41 argo.models.v1alpha1_dag_template

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.42 Module Contents

```
class argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate (fail_fast=None,  
target=None,  
tasks=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1DAGTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property fail_fast (*self*)

Gets the fail_fast of this V1alpha1DAGTemplate. # noqa: E501

Returns The fail_fast of this V1alpha1DAGTemplate. # noqa: E501

Return type bool

property target (*self*)

Gets the target of this V1alpha1DAGTemplate. # noqa: E501

Returns The target of this V1alpha1DAGTemplate. # noqa: E501

Return type str

property tasks (*self*)

Gets the tasks of this V1alpha1DAGTemplate. # noqa: E501

Returns The tasks of this V1alpha1DAGTemplate. # noqa: E501

Return type list[V1alpha1DAGTask]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.43 argo.models.v1alpha1_executor_config

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.44 Module Contents

```
class argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig (service_account_name=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ExecutorConfig - a model defined in OpenAPI

openapi_types

attribute_map

property `service_account_name` (*self*)

Gets the `service_account_name` of this `V1alpha1ExecutorConfig`. # noqa: E501

`ServiceAccountName` specifies the service account name of the executor container. # noqa: E501

Returns The `service_account_name` of this `V1alpha1ExecutorConfig`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.45 `argo.models.v1alpha1_gauge`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.46 Module Contents

class `argo.models.v1alpha1_gauge.V1alpha1Gauge` (*realtime=None, value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1Gauge` - a model defined in OpenAPI

openapi_types

attribute_map

property `realtime` (*self*)

Gets the `realtime` of this `V1alpha1Gauge`. # noqa: E501

Returns The `realtime` of this `V1alpha1Gauge`. # noqa: E501

Return type `bool`

property `value` (*self*)

Gets the `value` of this `V1alpha1Gauge`. # noqa: E501

Returns The `value` of this `V1alpha1Gauge`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.47 argo.models.v1alpha1_gcs_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.48 Module Contents

class argo.models.v1alpha1_gcs_artifact.V1alpha1GCSArtifact (*g_cs_bucket=None, key=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GCSArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property g_cs_bucket (*self*)

Gets the g_cs_bucket of this V1alpha1GCSArtifact. # noqa: E501

Returns The g_cs_bucket of this V1alpha1GCSArtifact. # noqa: E501

Return type *V1alpha1GCSBucket*

property key (*self*)

Gets the key of this V1alpha1GCSArtifact. # noqa: E501

Returns The key of this V1alpha1GCSArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.49 argo.models.v1alpha1_gcs_bucket

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.50 Module Contents

```
class argo.models.v1alpha1_gcs_bucket.V1alpha1GCSBucket (bucket=None, service_account_key_secret=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GCSBucket - a model defined in OpenAPI

openapi_types

attribute_map

property bucket (*self*)

Gets the bucket of this V1alpha1GCSBucket. # noqa: E501

Returns The bucket of this V1alpha1GCSBucket. # noqa: E501

Return type str

property service_account_key_secret (*self*)

Gets the service_account_key_secret of this V1alpha1GCSBucket. # noqa: E501

Returns The service_account_key_secret of this V1alpha1GCSBucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.51 argo.models.v1alpha1_git_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.52 Module Contents

```
class argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact (depth=None, fetch=None, insecure_ignore_host_key=None, password_secret=None, repo=None, revision=None, ssh_private_key_secret=None, username_secret=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GitArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property depth (*self*)

Gets the depth of this V1alpha1GitArtifact. # noqa: E501

Returns The depth of this V1alpha1GitArtifact. # noqa: E501

Return type str

property fetch (*self*)

Gets the fetch of this V1alpha1GitArtifact. # noqa: E501

Returns The fetch of this V1alpha1GitArtifact. # noqa: E501

Return type list[str]

property insecure_ignore_host_key (*self*)

Gets the insecure_ignore_host_key of this V1alpha1GitArtifact. # noqa: E501

Returns The insecure_ignore_host_key of this V1alpha1GitArtifact. # noqa: E501

Return type bool

property password_secret (*self*)

Gets the password_secret of this V1alpha1GitArtifact. # noqa: E501

Returns The password_secret of this V1alpha1GitArtifact. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property repo (*self*)

Gets the repo of this V1alpha1GitArtifact. # noqa: E501

Returns The repo of this V1alpha1GitArtifact. # noqa: E501

Return type str

property revision (*self*)

Gets the revision of this V1alpha1GitArtifact. # noqa: E501

Returns The revision of this V1alpha1GitArtifact. # noqa: E501

Return type str

property ssh_private_key_secret (*self*)

Gets the ssh_private_key_secret of this V1alpha1GitArtifact. # noqa: E501

Returns The ssh_private_key_secret of this V1alpha1GitArtifact. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property username_secret (*self*)

Gets the username_secret of this V1alpha1GitArtifact. # noqa: E501

Returns The username_secret of this V1alpha1GitArtifact. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.53 argo.models.v1alpha1_hdfs_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.54 Module Contents

```
class argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact (force=None,  
                                                             hDFS_config=None,  
                                                             path=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HDFSArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property force (*self*)

Gets the force of this V1alpha1HDFSArtifact. # noqa: E501

Returns The force of this V1alpha1HDFSArtifact. # noqa: E501

Return type bool

property hDFS_config (*self*)

Gets the hDFS_config of this V1alpha1HDFSArtifact. # noqa: E501

Returns The hDFS_config of this V1alpha1HDFSArtifact. # noqa: E501

Return type *V1alpha1HDFSConfig*

property path (*self*)

Gets the path of this V1alpha1HDFSArtifact. # noqa: E501

Returns The path of this V1alpha1HDFSArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.55 argo.models.v1alpha1_hdfs_config

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.56 Module Contents

```
class argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig(addresses=None,  
                                                         hdfs_krb_config=None,  
                                                         hdfs_user=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HDFSConfig - a model defined in OpenAPI

openapi_types

attribute_map

property addresses (*self*)

Gets the addresses of this V1alpha1HDFSConfig. # noqa: E501

Returns The addresses of this V1alpha1HDFSConfig. # noqa: E501

Return type list[str]

property hdfs_krb_config (*self*)

Gets the hdfs_krb_config of this V1alpha1HDFSConfig. # noqa: E501

Returns The hdfs_krb_config of this V1alpha1HDFSConfig. # noqa: E501

Return type *V1alpha1HDFSConfig*

property hdfs_user (*self*)

Gets the hdfs_user of this V1alpha1HDFSConfig. # noqa: E501

HDFSUser is the user to access HDFS file system. It is ignored if either ccache or keytab is used. # noqa: E501

Returns The hdfs_user of this V1alpha1HDFSConfig. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.57 argo.models.v1alpha1_hdfs_krb_config

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.58 Module Contents

```
class argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSKrbConfig(krb_c_cache_secret=None,  
                                                                krb_config_config_map=None,  
                                                                krb_keytab_secret=None,  
                                                                krb_realm=None,  
                                                                krb_service_principal_name=None,  
                                                                krb_username=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HDFSKrbConfig - a model defined in OpenAPI

openapi_types

attribute_map

property **krb_c_cache_secret** (*self*)

Gets the krb_c_cache_secret of this V1alpha1HDFSKrbConfig. # noqa: E501

Returns The krb_c_cache_secret of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

property **krb_config_config_map** (*self*)

Gets the krb_config_config_map of this V1alpha1HDFSKrbConfig. # noqa: E501

Returns The krb_config_config_map of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type `kubernetes.client.models.V1ConfigMapKeySelector`

property **krb_keytab_secret** (*self*)

Gets the krb_keytab_secret of this V1alpha1HDFSKrbConfig. # noqa: E501

Returns The krb_keytab_secret of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

property **krb_realm** (*self*)

Gets the krb_realm of this V1alpha1HDFSKrbConfig. # noqa: E501

KrbRealm is the Kerberos realm used with Kerberos keytab It must be set if keytab is used. # noqa: E501

Returns The krb_realm of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type `str`

property **krb_service_principal_name** (*self*)

Gets the krb_service_principal_name of this V1alpha1HDFSKrbConfig. # noqa: E501

KrbServicePrincipalName is the principal name of Kerberos service It must be set if either ccache or keytab is used. # noqa: E501

Returns The krb_service_principal_name of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type `str`

property **krb_username** (*self*)

Gets the krb_username of this V1alpha1HDFSKrbConfig. # noqa: E501

KrbUsername is the Kerberos username used with Kerberos keytab It must be set if keytab is used. # noqa: E501

Returns The krb_username of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.59 argo.models.v1alpha1_histogram

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.60 Module Contents

class argo.models.v1alpha1_histogram.V1alpha1Histogram (*buckets=None*,
value=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Histogram - a model defined in OpenAPI

openapi_types

attribute_map

property buckets (*self*)

Gets the buckets of this V1alpha1Histogram. # noqa: E501

Returns The buckets of this V1alpha1Histogram. # noqa: E501

Return type list[float]

property value (*self*)

Gets the value of this V1alpha1Histogram. # noqa: E501

Returns The value of this V1alpha1Histogram. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.61 `argo.models.v1alpha1_http_artifact`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.62 Module Contents

class `argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact` (*url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HTTPArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property url (*self*)

Gets the url of this V1alpha1HTTPArtifact. # noqa: E501

Returns The url of this V1alpha1HTTPArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.63 `argo.models.v1alpha1_info_response`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.64 Module Contents

class `argo.models.v1alpha1_info_response.V1alpha1InfoResponse` (*links=None, managed_namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1InfoResponse - a model defined in OpenAPI

openapi_types

attribute_map

property links (*self*)

Gets the links of this V1alpha1InfoResponse. # noqa: E501

Returns The links of this V1alpha1InfoResponse. # noqa: E501

Return type list[*V1alpha1Link*]

property managed_namespace (*self*)

Gets the managed_namespace of this V1alpha1InfoResponse. # noqa: E501

Returns The managed_namespace of this V1alpha1InfoResponse. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.65 argo.models.v1alpha1_inputs

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.66 Module Contents

class argo.models.v1alpha1_inputs.V1alpha1Inputs (*artifacts=None, parameters=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Inputs - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts (*self*)

Gets the artifacts of this V1alpha1Inputs. # noqa: E501

Returns The artifacts of this V1alpha1Inputs. # noqa: E501

Return type list[*V1alpha1Artifact*]

property parameters (*self*)

Gets the parameters of this V1alpha1Inputs. # noqa: E501

Returns The parameters of this V1alpha1Inputs. # noqa: E501

Return type list[*V1alpha1Parameter*]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.67 argo.models.v1alpha1_item

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.68 Module Contents

```
class argo.models.v1alpha1_item.V1alpha1Item(bool_val=None, list_val=None,  
                                              map_val=None, num_val=None,  
                                              str_val=None, type=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Item - a model defined in OpenAPI

openapi_types

attribute_map

property bool_val (*self*)

Gets the bool_val of this V1alpha1Item. # noqa: E501

Returns The bool_val of this V1alpha1Item. # noqa: E501

Return type bool

property list_val (*self*)

Gets the list_val of this V1alpha1Item. # noqa: E501

Returns The list_val of this V1alpha1Item. # noqa: E501

Return type list[V1alpha1ItemValue]

property map_val (*self*)

Gets the map_val of this V1alpha1Item. # noqa: E501

Returns The map_val of this V1alpha1Item. # noqa: E501

Return type dict(str, V1alpha1ItemValue)

property num_val (*self*)

Gets the num_val of this V1alpha1Item. # noqa: E501

Returns The num_val of this V1alpha1Item. # noqa: E501

Return type str

property str_val (*self*)

Gets the str_val of this V1alpha1Item. # noqa: E501

Returns The str_val of this V1alpha1Item. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1Item. # noqa: E501

Returns The type of this V1alpha1Item. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.69 argo.models.v1alpha1_item_value

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.70 Module Contents

```
class argo.models.v1alpha1_item_value.V1alpha1ItemValue (bool_val=None,
                                                         list_val=None,
                                                         map_val=None,
                                                         num_val=None,
                                                         str_val=None,
                                                         type=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ItemValue - a model defined in OpenAPI

openapi_types

attribute_map

property bool_val (*self*)

Gets the bool_val of this V1alpha1ItemValue. # noqa: E501

Returns The bool_val of this V1alpha1ItemValue. # noqa: E501

Return type bool

property list_val (*self*)

Gets the list_val of this V1alpha1ItemValue. # noqa: E501

Returns The list_val of this V1alpha1ItemValue. # noqa: E501

Return type list[str]

property map_val (*self*)

Gets the map_val of this V1alpha1ItemValue. # noqa: E501

Returns The map_val of this V1alpha1ItemValue. # noqa: E501

Return type dict(str, str)

property num_val (*self*)

Gets the num_val of this V1alpha1ItemValue. # noqa: E501

Returns The num_val of this V1alpha1ItemValue. # noqa: E501

Return type str

property str_val (*self*)

Gets the str_val of this V1alpha1ItemValue. # noqa: E501

Returns The str_val of this V1alpha1ItemValue. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1ItemValue. # noqa: E501

Returns The type of this V1alpha1ItemValue. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.71 argo.models.v1alpha1_link

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.72 Module Contents

class argo.models.v1alpha1_link.V1alpha1Link (*name=None, scope=None, url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Link - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1Link. # noqa: E501

Returns The name of this V1alpha1Link. # noqa: E501

Return type str

property scope (*self*)

Gets the scope of this V1alpha1Link. # noqa: E501

Returns The scope of this V1alpha1Link. # noqa: E501

Return type str

property url (*self*)

Gets the url of this V1alpha1Link. # noqa: E501

The URL. May contain “\${metadata.namespace}” and “\${metadata.name}”. # noqa: E501

Returns The url of this V1alpha1Link. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

1.1.1.1.1.73 argo.models.v1alpha1_log_entry

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.74 Module Contents

class argo.models.v1alpha1_log_entry.V1alpha1LogEntry (*content=None*,
pod_name=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>
Do not edit the class manually.
V1alpha1LogEntry - a model defined in OpenAPI

openapi_types

attribute_map

property content (*self*)
Gets the content of this V1alpha1LogEntry. # noqa: E501
Returns The content of this V1alpha1LogEntry. # noqa: E501
Return type str

property pod_name (*self*)
Gets the pod_name of this V1alpha1LogEntry. # noqa: E501
Returns The pod_name of this V1alpha1LogEntry. # noqa: E501
Return type str

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

1.1.1.1.1.75 argo.models.v1alpha1_metadata

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.76 Module Contents

class argo.models.v1alpha1_metadata.V1alpha1Metadata (*annotations=None, labels=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Metadata - a model defined in OpenAPI

openapi_types

attribute_map

property annotations (*self*)

Gets the annotations of this V1alpha1Metadata. # noqa: E501

Returns The annotations of this V1alpha1Metadata. # noqa: E501

Return type dict(str, str)

property labels (*self*)

Gets the labels of this V1alpha1Metadata. # noqa: E501

Returns The labels of this V1alpha1Metadata. # noqa: E501

Return type dict(str, str)

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.77 argo.models.v1alpha1_metric_label

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.78 Module Contents

class argo.models.v1alpha1_metric_label.V1alpha1MetricLabel (*key=None, value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1MetricLabel - a model defined in OpenAPI

openapi_types

attribute_map

property key (*self*)

Gets the key of this V1alpha1MetricLabel. # noqa: E501

Returns The key of this V1alpha1MetricLabel. # noqa: E501

Return type str

property value (*self*)

Gets the value of this V1alpha1MetricLabel. # noqa: E501

Returns The value of this V1alpha1MetricLabel. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.179 `argo.models.v1alpha1_metrics`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.180 Module Contents

class `argo.models.v1alpha1_metrics.V1alpha1Metrics` (*prometheus=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Metrics - a model defined in OpenAPI

openapi_types

attribute_map

property prometheus (*self*)

Gets the prometheus of this V1alpha1Metrics. # noqa: E501

Returns The prometheus of this V1alpha1Metrics. # noqa: E501

Return type list[V1alpha1Prometheus]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.181 `argo.models.v1alpha1_node_status`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.82 Module Contents

```
class argo.models.v1alpha1_node_status.V1alpha1NodeStatus (boundary_id=None,
                                                           children=None,   dae-
                                                           moned=None,    dis-
                                                           play_name=None,
                                                           finished_at=None,
                                                           id=None, inputs=None,
                                                           message=None,
                                                           name=None,      out-
                                                           bound_nodes=None,
                                                           outputs=None,
                                                           phase=None,
                                                           pod_ip=None,    re-
                                                           sources_duration=None,
                                                           started_at=None,
                                                           stored_template_id=None,
                                                           template_name=None,
                                                           template_ref=None,
                                                           template_scope=None,
                                                           type=None,      work-
                                                           flow_template_name=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1NodeStatus - a model defined in OpenAPI

openapi_types

attribute_map

property boundary_id (*self*)

Gets the boundary_id of this V1alpha1NodeStatus. # noqa: E501

Returns The boundary_id of this V1alpha1NodeStatus. # noqa: E501

Return type str

property children (*self*)

Gets the children of this V1alpha1NodeStatus. # noqa: E501

Returns The children of this V1alpha1NodeStatus. # noqa: E501

Return type list[str]

property daemoned (*self*)

Gets the daemoned of this V1alpha1NodeStatus. # noqa: E501

Returns The daemoned of this V1alpha1NodeStatus. # noqa: E501

Return type bool

property display_name (*self*)

Gets the display_name of this V1alpha1NodeStatus. # noqa: E501

Returns The display_name of this V1alpha1NodeStatus. # noqa: E501

Return type str

property finished_at (*self*)

Gets the finished_at of this V1alpha1NodeStatus. # noqa: E501

Returns The finished_at of this V1alpha1NodeStatus. # noqa: E501

Return type `kubernetes.client.models.V1Time`

property id (*self*)

Gets the id of this V1alpha1NodeStatus. # noqa: E501

Returns The id of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property inputs (*self*)

Gets the inputs of this V1alpha1NodeStatus. # noqa: E501

Returns The inputs of this V1alpha1NodeStatus. # noqa: E501

Return type `V1alpha1Inputs`

property message (*self*)

Gets the message of this V1alpha1NodeStatus. # noqa: E501

A human readable message indicating details about why the node is in this condition. # noqa: E501

Returns The message of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property name (*self*)

Gets the name of this V1alpha1NodeStatus. # noqa: E501

Returns The name of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property outbound_nodes (*self*)

Gets the outbound_nodes of this V1alpha1NodeStatus. # noqa: E501

OutboundNodes tracks the node IDs which are considered “outbound” nodes to a template invocation. For every invocation of a template, there are nodes which we considered as “outbound”. Essentially, these are last nodes in the execution sequence to run, before the template is considered completed. These nodes are then connected as parents to a following step. In the case of single pod steps (i.e. container, script, resource templates), this list will be nil since the pod itself is already considered the “outbound” node. In the case of DAGs, outbound nodes are the “target” tasks (tasks with no children). In the case of steps, outbound nodes are all the containers involved in the last step group. NOTE: since templates are composable, the list of outbound nodes are carried upwards when a DAG/steps template invokes another DAG/steps template. In other words, the outbound nodes of a template, will be a superset of the outbound nodes of its last children. # noqa: E501

Returns The outbound_nodes of this V1alpha1NodeStatus. # noqa: E501

Return type `list[str]`

property outputs (*self*)

Gets the outputs of this V1alpha1NodeStatus. # noqa: E501

Returns The outputs of this V1alpha1NodeStatus. # noqa: E501

Return type `V1alpha1Outputs`

property phase (*self*)

Gets the phase of this V1alpha1NodeStatus. # noqa: E501

Phase a simple, high-level summary of where the node is in its lifecycle. Can be used as a state machine. # noqa: E501

Returns The phase of this V1alpha1NodeStatus. # noqa: E501

Return type str

property pod_ip (*self*)

Gets the pod_ip of this V1alpha1NodeStatus. # noqa: E501

Returns The pod_ip of this V1alpha1NodeStatus. # noqa: E501

Return type str

property resources_duration (*self*)

Gets the resources_duration of this V1alpha1NodeStatus. # noqa: E501

ResourcesDuration is indicative, but not accurate, resource duration. This is populated when the nodes completes. # noqa: E501

Returns The resources_duration of this V1alpha1NodeStatus. # noqa: E501

Return type dict(str, str)

property started_at (*self*)

Gets the started_at of this V1alpha1NodeStatus. # noqa: E501

Returns The started_at of this V1alpha1NodeStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property stored_template_id (*self*)

Gets the stored_template_id of this V1alpha1NodeStatus. # noqa: E501

StoredTemplateID is the ID of stored template. DEPRECATED: This value is not used anymore. # noqa: E501

Returns The stored_template_id of this V1alpha1NodeStatus. # noqa: E501

Return type str

property template_name (*self*)

Gets the template_name of this V1alpha1NodeStatus. # noqa: E501

Returns The template_name of this V1alpha1NodeStatus. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1NodeStatus. # noqa: E501

Returns The template_ref of this V1alpha1NodeStatus. # noqa: E501

Return type *V1alpha1TemplateRef*

property template_scope (*self*)

Gets the template_scope of this V1alpha1NodeStatus. # noqa: E501

TemplateScope is the template scope in which the template of this node was retrieved. # noqa: E501

Returns The template_scope of this V1alpha1NodeStatus. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1NodeStatus. # noqa: E501

Returns The type of this V1alpha1NodeStatus. # noqa: E501

Return type str

property workflow_template_name (*self*)

Gets the workflow_template_name of this V1alpha1NodeStatus. # noqa: E501

WorkflowTemplateName is the WorkflowTemplate resource name on which the resolved template of this node is retrieved. DEPRECATED: This value is not used anymore. # noqa: E501

Returns The workflow_template_name of this V1alpha1NodeStatus. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.83 argo.models.v1alpha1_oss_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.84 Module Contents

class argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact (*key=None*,
o_ss_bucket=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1OSSArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property key (*self*)

Gets the key of this V1alpha1OSSArtifact. # noqa: E501

Returns The key of this V1alpha1OSSArtifact. # noqa: E501

Return type str

property o_ss_bucket (*self*)

Gets the o_ss_bucket of this V1alpha1OSSArtifact. # noqa: E501

Returns The o_ss_bucket of this V1alpha1OSSArtifact. # noqa: E501

Return type *V1alpha1OSSBucket*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.85 argo.models.v1alpha1_oss_bucket

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.86 Module Contents

```
class argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket (access_key_secret=None,
                                                         bucket=None,          end-
                                                         point=None,          se-
                                                         cret_key_secret=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1OSSBucket - a model defined in OpenAPI

openapi_types

attribute_map

property access_key_secret (*self*)

Gets the access_key_secret of this V1alpha1OSSBucket. # noqa: E501

Returns The access_key_secret of this V1alpha1OSSBucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property bucket (*self*)

Gets the bucket of this V1alpha1OSSBucket. # noqa: E501

Returns The bucket of this V1alpha1OSSBucket. # noqa: E501

Return type str

property endpoint (*self*)

Gets the endpoint of this V1alpha1OSSBucket. # noqa: E501

Returns The endpoint of this V1alpha1OSSBucket. # noqa: E501

Return type str

property secret_key_secret (*self*)

Gets the secret_key_secret of this V1alpha1OSSBucket. # noqa: E501

Returns The secret_key_secret of this V1alpha1OSSBucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.187 argo.models.v1alpha1_outputs

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.188 Module Contents

class argo.models.v1alpha1_outputs.V1alpha1Outputs (*artifacts=None, parameters=None, result=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Outputs - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts (*self*)

Gets the artifacts of this V1alpha1Outputs. # noqa: E501

Returns The artifacts of this V1alpha1Outputs. # noqa: E501

Return type list[V1alpha1Artifact]

property parameters (*self*)

Gets the parameters of this V1alpha1Outputs. # noqa: E501

Returns The parameters of this V1alpha1Outputs. # noqa: E501

Return type list[V1alpha1Parameter]

property result (*self*)

Gets the result of this V1alpha1Outputs. # noqa: E501

Returns The result of this V1alpha1Outputs. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.189 argo.models.v1alpha1_parameter

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.90 Module Contents

```
class argo.models.v1alpha1_parameter.V1alpha1Parameter (default=None,  
                                                         global_name=None,  
                                                         name=None, value=None,  
                                                         value_from=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Parameter - a model defined in OpenAPI

openapi_types

attribute_map

property default (*self*)

Gets the default of this V1alpha1Parameter. # noqa: E501

Returns The default of this V1alpha1Parameter. # noqa: E501

Return type str

property global_name (*self*)

Gets the global_name of this V1alpha1Parameter. # noqa: E501

Returns The global_name of this V1alpha1Parameter. # noqa: E501

Return type str

property name (*self*)

Gets the name of this V1alpha1Parameter. # noqa: E501

Returns The name of this V1alpha1Parameter. # noqa: E501

Return type str

property value (*self*)

Gets the value of this V1alpha1Parameter. # noqa: E501

Returns The value of this V1alpha1Parameter. # noqa: E501

Return type str

property value_from (*self*)

Gets the value_from of this V1alpha1Parameter. # noqa: E501

Returns The value_from of this V1alpha1Parameter. # noqa: E501

Return type *V1alpha1ValueFrom*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.91 argo.models.v1alpha1_pod_gc

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.92 Module Contents

class argo.models.v1alpha1_pod_gc.V1alpha1PodGC (*strategy=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1PodGC - a model defined in OpenAPI

openapi_types

attribute_map

property strategy (*self*)

Gets the strategy of this V1alpha1PodGC. # noqa: E501

Returns The strategy of this V1alpha1PodGC. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.93 argo.models.v1alpha1_prometheus

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.94 Module Contents

class argo.models.v1alpha1_prometheus.V1alpha1Prometheus (*counter=None,*
gauge=None,
help=None, *his-*
togram=None, *la-*
bels=None, name=None,
when=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Prometheus - a model defined in OpenAPI

openapi_types

attribute_map

property counter (*self*)

Gets the counter of this V1alpha1Prometheus. # noqa: E501

Returns The counter of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Counter*

property gauge (*self*)

Gets the gauge of this V1alpha1Prometheus. # noqa: E501

Returns The gauge of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Gauge*

property help (*self*)

Gets the help of this V1alpha1Prometheus. # noqa: E501

Returns The help of this V1alpha1Prometheus. # noqa: E501

Return type str

property histogram (*self*)

Gets the histogram of this V1alpha1Prometheus. # noqa: E501

Returns The histogram of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Histogram*

property labels (*self*)

Gets the labels of this V1alpha1Prometheus. # noqa: E501

Returns The labels of this V1alpha1Prometheus. # noqa: E501

Return type list[*V1alpha1MetricLabel*]

property name (*self*)

Gets the name of this V1alpha1Prometheus. # noqa: E501

Returns The name of this V1alpha1Prometheus. # noqa: E501

Return type str

property when (*self*)

Gets the when of this V1alpha1Prometheus. # noqa: E501

Returns The when of this V1alpha1Prometheus. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.95 argo.models.v1alpha1_raw_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.96 Module Contents

class argo.models.v1alpha1_raw_artifact.V1alpha1RawArtifact (data=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1RawArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property data (self)

Gets the data of this V1alpha1RawArtifact. # noqa: E501

Returns The data of this V1alpha1RawArtifact. # noqa: E501

Return type str

to_dict (self)

Returns the model properties as a dict

to_str (self)

Returns the string representation of the model

1.1.1.1.1.97 argo.models.v1alpha1_resource_template

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.98 Module Contents

class argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate (action=None, fail-
ure_condition=None, mani-
fest=None, merge_strategy=None, set_owner_reference=None, suc-
cess_condition=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ResourceTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property action (*self*)

Gets the action of this V1alpha1ResourceTemplate. # noqa: E501

Returns The action of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property failure_condition (*self*)

Gets the failure_condition of this V1alpha1ResourceTemplate. # noqa: E501

Returns The failure_condition of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property manifest (*self*)

Gets the manifest of this V1alpha1ResourceTemplate. # noqa: E501

Returns The manifest of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property merge_strategy (*self*)

Gets the merge_strategy of this V1alpha1ResourceTemplate. # noqa: E501

Returns The merge_strategy of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property set_owner_reference (*self*)

Gets the set_owner_reference of this V1alpha1ResourceTemplate. # noqa: E501

SetOwnerReference sets the reference to the workflow on the OwnerReference of generated resource. # noqa: E501

Returns The set_owner_reference of this V1alpha1ResourceTemplate. # noqa: E501

Return type bool

property success_condition (*self*)

Gets the success_condition of this V1alpha1ResourceTemplate. # noqa: E501

Returns The success_condition of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.99 argo.models.v1alpha1_retry_strategy

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.100 Module Contents

```
class argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy (backoff=None,
                                                                limit=None,
                                                                retry_policy=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1RetryStrategy - a model defined in OpenAPI

openapi_types

attribute_map

property backoff (*self*)

Gets the backoff of this V1alpha1RetryStrategy. # noqa: E501

Returns The backoff of this V1alpha1RetryStrategy. # noqa: E501

Return type *V1alpha1Backoff*

property limit (*self*)

Gets the limit of this V1alpha1RetryStrategy. # noqa: E501

Returns The limit of this V1alpha1RetryStrategy. # noqa: E501

Return type int

property retry_policy (*self*)

Gets the retry_policy of this V1alpha1RetryStrategy. # noqa: E501

Returns The retry_policy of this V1alpha1RetryStrategy. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.101 argo.models.v1alpha1_s3_artifact

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.102 Module Contents

```
class argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact (key=None,  
                                                         s3_bucket=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1S3Artifact - a model defined in OpenAPI

openapi_types

attribute_map

property key (*self*)

Gets the key of this V1alpha1S3Artifact. # noqa: E501

Returns The key of this V1alpha1S3Artifact. # noqa: E501

Return type str

property s3_bucket (*self*)

Gets the s3_bucket of this V1alpha1S3Artifact. # noqa: E501

Returns The s3_bucket of this V1alpha1S3Artifact. # noqa: E501

Return type *V1alpha1S3Bucket*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.103 argo.models.v1alpha1_s3_bucket

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.104 Module Contents

```
class argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket (access_key_secret=None,  
                                                         bucket=None,          end-  
                                                         point=None,          inse-  
                                                         cure=None,    region=None,  
                                                         role_arn=None,      se-  
                                                         cret_key_secret=None,  
                                                         use_sdk_creds=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1S3Bucket - a model defined in OpenAPI

openapi_types

attribute_map

property access_key_secret (*self*)

Gets the access_key_secret of this V1alpha1S3Bucket. # noqa: E501

Returns The access_key_secret of this V1alpha1S3Bucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property bucket (*self*)

Gets the bucket of this V1alpha1S3Bucket. # noqa: E501

Returns The bucket of this V1alpha1S3Bucket. # noqa: E501

Return type str

property endpoint (*self*)

Gets the endpoint of this V1alpha1S3Bucket. # noqa: E501

Returns The endpoint of this V1alpha1S3Bucket. # noqa: E501

Return type str

property insecure (*self*)

Gets the insecure of this V1alpha1S3Bucket. # noqa: E501

Returns The insecure of this V1alpha1S3Bucket. # noqa: E501

Return type bool

property region (*self*)

Gets the region of this V1alpha1S3Bucket. # noqa: E501

Returns The region of this V1alpha1S3Bucket. # noqa: E501

Return type str

property role_arn (*self*)

Gets the role_arn of this V1alpha1S3Bucket. # noqa: E501

RoleARN is the Amazon Resource Name (ARN) of the role to assume. # noqa: E501

Returns The role_arn of this V1alpha1S3Bucket. # noqa: E501

Return type str

property secret_key_secret (*self*)

Gets the secret_key_secret of this V1alpha1S3Bucket. # noqa: E501

Returns The secret_key_secret of this V1alpha1S3Bucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property use_sdk_creds (*self*)

Gets the use_sdk_creds of this V1alpha1S3Bucket. # noqa: E501

UseSDKCreds tells the driver to figure out credentials based on sdk defaults. # noqa: E501

Returns The use_sdk_creds of this V1alpha1S3Bucket. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.105 `argo.models.v1alpha1_script_template`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.106 Module Contents

class `argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate` (*container=None*,
source=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ScriptTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property container (*self*)

Gets the container of this V1alpha1ScriptTemplate. # noqa: E501

Returns The container of this V1alpha1ScriptTemplate. # noqa: E501

Return type `kubernetes.client.models.V1Container`

property source (*self*)

Gets the source of this V1alpha1ScriptTemplate. # noqa: E501

Returns The source of this V1alpha1ScriptTemplate. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.107 `argo.models.v1alpha1_sequence`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.108 Module Contents

class argo.models.v1alpha1_sequence.V1alpha1Sequence (*count=None, end=None, format=None, start=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Sequence - a model defined in OpenAPI

openapi_types

attribute_map

property count (*self*)

Gets the count of this V1alpha1Sequence. # noqa: E501

Returns The count of this V1alpha1Sequence. # noqa: E501

Return type str

property end (*self*)

Gets the end of this V1alpha1Sequence. # noqa: E501

Returns The end of this V1alpha1Sequence. # noqa: E501

Return type str

property format (*self*)

Gets the format of this V1alpha1Sequence. # noqa: E501

Returns The format of this V1alpha1Sequence. # noqa: E501

Return type str

property start (*self*)

Gets the start of this V1alpha1Sequence. # noqa: E501

Returns The start of this V1alpha1Sequence. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.109 argo.models.v1alpha1_suspend_template

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.110 Module Contents

class `argo.models.v1alpha1_suspend_template.V1alpha1SuspendTemplate` (*duration=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1SuspendTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property duration (*self*)

Gets the duration of this V1alpha1SuspendTemplate. # noqa: E501

Returns The duration of this V1alpha1SuspendTemplate. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.111 `argo.models.v1alpha1_template`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.112 Module Contents

```
class argo.models.v1alpha1_template.V1alpha1Template (active_deadline_seconds=None,
                                                    affinity=None,
                                                    archive_location=None,
                                                    arguments=None,          auto-
                                                    mount_service_account_token=None,
                                                    container=None,          dae-
                                                    mon=None, dag=None, execu-
                                                    tor=None, host_aliases=None,
                                                    init_containers=None,    in-
                                                    puts=None, metadata=None,
                                                    metrics=None, name=None,
                                                    node_selector=None,    out-
                                                    puts=None, parallelism=None,
                                                    pod_spec_patch=None,
                                                    priority=None,          prior-
                                                    ity_class_name=None,
                                                    resource=None,          resub-
                                                    mit_pending_pods=None,
                                                    retry_strategy=None,
                                                    scheduler_name=None,
                                                    script=None,            secu-
                                                    rity_context=None,      ser-
                                                    vice_account_name=None,
                                                    sidecars=None, steps=None,
                                                    suspend=None,           tem-
                                                    plate=None,             tem-
                                                    plate_ref=None,         tolera-
                                                    tions=None, volumes=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Template - a model defined in OpenAPI

openapi_types

attribute_map

property active_deadline_seconds (self)

Gets the active_deadline_seconds of this V1alpha1Template. # noqa: E501

Optional duration in seconds relative to the StartTime that the pod may be active on a node before the system actively tries to terminate the pod; value must be positive integer This field is only applicable to container and script templates. # noqa: E501

Returns The active_deadline_seconds of this V1alpha1Template. # noqa: E501

Return type str

property affinity (self)

Gets the affinity of this V1alpha1Template. # noqa: E501

Returns The affinity of this V1alpha1Template. # noqa: E501

Return type kubernetes.client.models.V1Affinity

property archive_location (self)

Gets the archive_location of this V1alpha1Template. # noqa: E501

Returns The archive_location of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ArtifactLocation*

property arguments (*self*)

Gets the arguments of this V1alpha1Template. # noqa: E501

Returns The arguments of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Arguments*

property automount_service_account_token (*self*)

Gets the automount_service_account_token of this V1alpha1Template. # noqa: E501

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted in pods. ServiceAccountName of ExecutorConfig must be specified if this value is false. # noqa: E501

Returns The automount_service_account_token of this V1alpha1Template. # noqa: E501

Return type bool

property container (*self*)

Gets the container of this V1alpha1Template. # noqa: E501

Returns The container of this V1alpha1Template. # noqa: E501

Return type kubernetes.client.models.V1Container

property daemon (*self*)

Gets the daemon of this V1alpha1Template. # noqa: E501

Returns The daemon of this V1alpha1Template. # noqa: E501

Return type bool

property dag (*self*)

Gets the dag of this V1alpha1Template. # noqa: E501

Returns The dag of this V1alpha1Template. # noqa: E501

Return type *V1alpha1DAGTemplate*

property executor (*self*)

Gets the executor of this V1alpha1Template. # noqa: E501

Returns The executor of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ExecutorConfig*

property host_aliases (*self*)

Gets the host_aliases of this V1alpha1Template. # noqa: E501

Returns The host_aliases of this V1alpha1Template. # noqa: E501

Return type list[kubernetes.client.models.V1HostAlias]

property init_containers (*self*)

Gets the init_containers of this V1alpha1Template. # noqa: E501

Returns The init_containers of this V1alpha1Template. # noqa: E501

Return type list[*V1alpha1UserContainer*]

property inputs (*self*)

Gets the inputs of this V1alpha1Template. # noqa: E501

Returns The inputs of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Inputs*

property metadata (*self*)

Gets the metadata of this V1alpha1Template. # noqa: E501

Returns The metadata of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Metadata*

property metrics (*self*)

Gets the metrics of this V1alpha1Template. # noqa: E501

Returns The metrics of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Metrics*

property name (*self*)

Gets the name of this V1alpha1Template. # noqa: E501

Returns The name of this V1alpha1Template. # noqa: E501

Return type str

property node_selector (*self*)

Gets the node_selector of this V1alpha1Template. # noqa: E501

NodeSelector is a selector to schedule this step of the workflow to be run on the selected node(s). Overrides the selector set at the workflow level. # noqa: E501

Returns The node_selector of this V1alpha1Template. # noqa: E501

Return type dict(str, str)

property outputs (*self*)

Gets the outputs of this V1alpha1Template. # noqa: E501

Returns The outputs of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Outputs*

property parallelism (*self*)

Gets the parallelism of this V1alpha1Template. # noqa: E501

Parallelism limits the max total parallel pods that can execute at the same time within the boundaries of this template invocation. If additional steps/dag templates are invoked, the pods created by those templates will not be counted towards this total. # noqa: E501

Returns The parallelism of this V1alpha1Template. # noqa: E501

Return type str

property pod_spec_patch (*self*)

Gets the pod_spec_patch of this V1alpha1Template. # noqa: E501

PodSpecPatch holds strategic merge patch to apply against the pod spec. Allows parameterization of container fields which are not strings (e.g. resource limits). # noqa: E501

Returns The pod_spec_patch of this V1alpha1Template. # noqa: E501

Return type str

property priority (*self*)

Gets the priority of this V1alpha1Template. # noqa: E501

Priority to apply to workflow pods. # noqa: E501

Returns The priority of this V1alpha1Template. # noqa: E501

Return type int

property priority_class_name (*self*)

Gets the priority_class_name of this V1alpha1Template. # noqa: E501

PriorityClassName to apply to workflow pods. # noqa: E501

Returns The priority_class_name of this V1alpha1Template. # noqa: E501

Return type str

property resource (*self*)

Gets the resource of this V1alpha1Template. # noqa: E501

Returns The resource of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ResourceTemplate*

property resubmit_pending_pods (*self*)

Gets the resubmit_pending_pods of this V1alpha1Template. # noqa: E501

Returns The resubmit_pending_pods of this V1alpha1Template. # noqa: E501

Return type bool

property retry_strategy (*self*)

Gets the retry_strategy of this V1alpha1Template. # noqa: E501

Returns The retry_strategy of this V1alpha1Template. # noqa: E501

Return type *V1alpha1RetryStrategy*

property scheduler_name (*self*)

Gets the scheduler_name of this V1alpha1Template. # noqa: E501

Returns The scheduler_name of this V1alpha1Template. # noqa: E501

Return type str

property script (*self*)

Gets the script of this V1alpha1Template. # noqa: E501

Returns The script of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ScriptTemplate*

property security_context (*self*)

Gets the security_context of this V1alpha1Template. # noqa: E501

Returns The security_context of this V1alpha1Template. # noqa: E501

Return type `kubernetes.client.models.V1PodSecurityContext`

property service_account_name (*self*)

Gets the service_account_name of this V1alpha1Template. # noqa: E501

Returns The service_account_name of this V1alpha1Template. # noqa: E501

Return type str

property sidecars (*self*)

Gets the sidecars of this V1alpha1Template. # noqa: E501

Returns The sidecars of this V1alpha1Template. # noqa: E501

Return type list[*V1alpha1UserContainer*]

property steps (*self*)

Gets the steps of this V1alpha1Template. # noqa: E501

Returns The steps of this V1alpha1Template. # noqa: E501

Return type list[list]

property suspend (*self*)

Gets the suspend of this V1alpha1Template. # noqa: E501

Returns The suspend of this V1alpha1Template. # noqa: E501

Return type *V1alpha1SuspendTemplate*

property template (*self*)

Gets the template of this V1alpha1Template. # noqa: E501

Template is the name of the template which is used as the base of this template. DEPRECATED: This field is not used. # noqa: E501

Returns The template of this V1alpha1Template. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1Template. # noqa: E501

Returns The template_ref of this V1alpha1Template. # noqa: E501

Return type *V1alpha1TemplateRef*

property tolerations (*self*)

Gets the tolerations of this V1alpha1Template. # noqa: E501

Returns The tolerations of this V1alpha1Template. # noqa: E501

Return type list[kubernetes.client.models.V1Toleration]

property volumes (*self*)

Gets the volumes of this V1alpha1Template. # noqa: E501

Returns The volumes of this V1alpha1Template. # noqa: E501

Return type list[kubernetes.client.models.V1Volume]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.113 argo.models.v1alpha1_template_ref

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.114 Module Contents

```
class argo.models.v1alpha1_template_ref.V1alpha1TemplateRef (name=None, run-  
time_resolution=None,  
template=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1TemplateRef - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1TemplateRef. # noqa: E501

Name is the resource name of the template. # noqa: E501

Returns The name of this V1alpha1TemplateRef. # noqa: E501

Return type str

property runtime_resolution (*self*)

Gets the runtime_resolution of this V1alpha1TemplateRef. # noqa: E501

RuntimeResolution skips validation at creation time. By enabling this option, you can create the referred workflow template before the actual runtime. # noqa: E501

Returns The runtime_resolution of this V1alpha1TemplateRef. # noqa: E501

Return type bool

property template (*self*)

Gets the template of this V1alpha1TemplateRef. # noqa: E501

Template is the name of referred template in the resource. # noqa: E501

Returns The template of this V1alpha1TemplateRef. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.115 argo.models.v1alpha1_ttl_strategy

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.116 Module Contents

```
class argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy (seconds_after_completion=None,
                                                            sec-
                                                            onds_after_failure=None,
                                                            sec-
                                                            onds_after_success=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1TTLStrategy - a model defined in OpenAPI

openapi_types

attribute_map

property seconds_after_completion (*self*)

Gets the seconds_after_completion of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_completion of this V1alpha1TTLStrategy. # noqa: E501

Return type int

property seconds_after_failure (*self*)

Gets the seconds_after_failure of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_failure of this V1alpha1TTLStrategy. # noqa: E501

Return type int

property seconds_after_success (*self*)

Gets the seconds_after_success of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_success of this V1alpha1TTLStrategy. # noqa: E501

Return type int

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.117 argo.models.v1alpha1_user_container

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.118 Module Contents

```
class argo.models.v1alpha1_user_container.V1alpha1UserContainer (container=None,  
                                                                mir-  
                                                                ror_volume_mounts=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1UserContainer - a model defined in OpenAPI

openapi_types

attribute_map

property container (*self*)

Gets the container of this V1alpha1UserContainer. # noqa: E501

Returns The container of this V1alpha1UserContainer. # noqa: E501

Return type kubernetes.client.models.V1Container

property mirror_volume_mounts (*self*)

Gets the mirror_volume_mounts of this V1alpha1UserContainer. # noqa: E501

Returns The mirror_volume_mounts of this V1alpha1UserContainer. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.119 argo.models.v1alpha1_value_from

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.120 Module Contents

```
class argo.models.v1alpha1_value_from.V1alpha1ValueFrom (default=None,  
                                                         jq_filter=None,  
                                                         json_path=None, parame-  
                                                         ter=None, path=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ValueFrom - a model defined in OpenAPI

openapi_types

attribute_map

property default (*self*)

Gets the default of this V1alpha1ValueFrom. # noqa: E501

Returns The default of this V1alpha1ValueFrom. # noqa: E501

Return type str

property jq_filter (*self*)

Gets the jq_filter of this V1alpha1ValueFrom. # noqa: E501

Returns The jq_filter of this V1alpha1ValueFrom. # noqa: E501

Return type str

property json_path (*self*)

Gets the json_path of this V1alpha1ValueFrom. # noqa: E501

Returns The json_path of this V1alpha1ValueFrom. # noqa: E501

Return type str

property parameter (*self*)

Gets the parameter of this V1alpha1ValueFrom. # noqa: E501

Returns The parameter of this V1alpha1ValueFrom. # noqa: E501

Return type str

property path (*self*)

Gets the path of this V1alpha1ValueFrom. # noqa: E501

Returns The path of this V1alpha1ValueFrom. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.121 argo.models.v1alpha1_workflow

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.122 Module Contents

class argo.models.v1alpha1_workflow.V1alpha1Workflow (*metadata=None, spec=None, status=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Workflow - a model defined in OpenAPI

openapi_types

attribute_map

property metadata (*self*)

Gets the metadata of this V1alpha1Workflow. # noqa: E501

Returns The metadata of this V1alpha1Workflow. # noqa: E501

Return type `kubernetes.client.models.V1ObjectMeta`

property spec (*self*)

Gets the spec of this V1alpha1Workflow. # noqa: E501

Returns The spec of this V1alpha1Workflow. # noqa: E501

Return type `V1alpha1WorkflowSpec`

property status (*self*)

Gets the status of this V1alpha1Workflow. # noqa: E501

Returns The status of this V1alpha1Workflow. # noqa: E501

Return type `V1alpha1WorkflowStatus`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.123 `argo.models.v1alpha1_workflow_condition`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.124 Module Contents

```
class argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition (message=None,  
                                                                           sta-  
                                                                           tus=None,  
                                                                           type=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowCondition - a model defined in OpenAPI

openapi_types

attribute_map

property message (*self*)

Gets the message of this V1alpha1WorkflowCondition. # noqa: E501

Returns The message of this V1alpha1WorkflowCondition. # noqa: E501

Return type `str`

property status (*self*)

Gets the status of this V1alpha1WorkflowCondition. # noqa: E501

Returns The status of this V1alpha1WorkflowCondition. # noqa: E501

Return type `str`

property type (*self*)

Gets the type of this V1alpha1WorkflowCondition. # noqa: E501

Returns The type of this V1alpha1WorkflowCondition. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.125 `argo.models.v1alpha1_workflow_create_request`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.126 Module Contents

```
class argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest (create_options,
                                         in-
                                         stance_id=None,
                                         names-
                                         pace=None,
                                         server_dry_ru
                                         work-
                                         flow=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowCreateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The create_options of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property instance_id (*self*)

Gets the instance_id of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The instance_id of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type str

property server_dry_run (*self*)

Gets the server_dry_run of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The server_dry_run of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type bool

property workflow (*self*)

Gets the workflow of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The workflow of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type *V1alpha1Workflow*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.127 argo.models.v1alpha1_workflow_lint_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.128 Module Contents

class argo.models.v1alpha1_workflow_lint_request.V1alpha1WorkflowLintRequest (*namespace=None, workflow=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowLintRequest - a model defined in OpenAPI

openapi_types

attribute_map

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowLintRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowLintRequest. # noqa: E501

Return type str

property workflow (*self*)

Gets the workflow of this V1alpha1WorkflowLintRequest. # noqa: E501

Returns The workflow of this V1alpha1WorkflowLintRequest. # noqa: E501

Return type *V1alpha1Workflow*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.129 argo.models.v1alpha1_workflow_list

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.130 Module Contents

class argo.models.v1alpha1_workflow_list.V1alpha1WorkflowList (*items=None, metadata=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowList - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)

Gets the items of this V1alpha1WorkflowList. # noqa: E501

Returns The items of this V1alpha1WorkflowList. # noqa: E501

Return type list[V1alpha1Workflow]

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowList. # noqa: E501

Returns The metadata of this V1alpha1WorkflowList. # noqa: E501

Return type kubernetes.client.models.V1ListMeta

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.131 argo.models.v1alpha1_workflow_resubmit_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.132 Module Contents

class argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest (memoize

name=N

names-

pace=N

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowResubmitRequest - a model defined in OpenAPI

openapi_types

attribute_map

property memoized (*self*)

Gets the memoized of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The memoized of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type bool

property name (*self*)

Gets the name of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.133 argo.models.v1alpha1_workflow_resume_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.134 Module Contents

class argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest (*name=None, names-pace=None, node_field_se*

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowResumeRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

property node_field_selector (*self*)

Gets the node_field_selector of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The node_field_selector of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.135 argo.models.v1alpha1_workflow_retry_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.136 Module Contents

class argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest (*name=None, names-pace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowRetryRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowRetryRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowRetryRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowRetryRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowRetryRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.137 argo.models.v1alpha1_workflow_spec

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.138 Module Contents

```

class argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec (active_deadline_seconds=None,
                                                                affinity=None,
                                                                arguments=None,
                                                                arti-
                                                                fact_repository_ref=None,
                                                                auto-
                                                                mount_service_account_token=None,
                                                                dns_config=None,
                                                                dns_policy=None,
                                                                entrypoint=None,
                                                                executor=None,
                                                                host_aliases=None,
                                                                host_network=None,
                                                                im-
                                                                age_pull_secrets=None,
                                                                metrics=None,
                                                                node_selector=None,
                                                                on_exit=None,
                                                                paral-
                                                                lelism=None,
                                                                pod_disruption_budget=None,
                                                                pod_gc=None,
                                                                pod_priority=None,
                                                                pod_priority_class_name=None,
                                                                pod_spec_patch=None,
                                                                priority=None,
                                                                sched-
                                                                uler_name=None,
                                                                secu-
                                                                rity_context=None,
                                                                ser-
                                                                vice_account_name=None,
                                                                shutdown=None,
                                                                suspend=None,
                                                                templates=None,
                                                                tolera-
                                                                tions=None,
                                                                ttl_seconds_after_finished=None,
                                                                ttl_strategy=None,
                                                                vol-
                                                                ume_claim_templates=None,
                                                                volumes=None)

```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowSpec - a model defined in OpenAPI

openapi_types

attribute_map

property active_deadline_seconds (*self*)

Gets the active_deadline_seconds of this V1alpha1WorkflowSpec. # noqa: E501

Returns The active_deadline_seconds of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property affinity (*self*)

Gets the affinity of this V1alpha1WorkflowSpec. # noqa: E501

Returns The affinity of this V1alpha1WorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1Affinity

property arguments (*self*)

Gets the arguments of this V1alpha1WorkflowSpec. # noqa: E501

Returns The arguments of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1Arguments*

property artifact_repository_ref (*self*)

Gets the artifact_repository_ref of this V1alpha1WorkflowSpec. # noqa: E501

Returns The artifact_repository_ref of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1ArtifactRepositoryRef*

property automount_service_account_token (*self*)

Gets the automount_service_account_token of this V1alpha1WorkflowSpec. # noqa: E501

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted in pods. ServiceAccountName of ExecutorConfig must be specified if this value is false. # noqa: E501

Returns The automount_service_account_token of this V1alpha1WorkflowSpec. # noqa: E501

Return type bool

property dns_config (*self*)

Gets the dns_config of this V1alpha1WorkflowSpec. # noqa: E501

Returns The dns_config of this V1alpha1WorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1PodDNSConfig

property dns_policy (*self*)

Gets the dns_policy of this V1alpha1WorkflowSpec. # noqa: E501

Set DNS policy for the pod. Defaults to "ClusterFirst". Valid values are 'ClusterFirstWithHostNet', 'ClusterFirst', 'Default' or 'None'. DNS parameters given in DNSConfig will be merged with the policy selected with DNSPolicy. To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'. # noqa: E501

Returns The dns_policy of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property entrypoint (*self*)

Gets the entrypoint of this V1alpha1WorkflowSpec. # noqa: E501

Entrypoint is a template reference to the starting point of the v1alpha1. # noqa: E501

Returns The entrypoint of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property executor (*self*)

Gets the executor of this V1alpha1WorkflowSpec. # noqa: E501

Returns The executor of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1ExecutorConfig*

property host_aliases (*self*)

Gets the host_aliases of this V1alpha1WorkflowSpec. # noqa: E501

Returns The host_aliases of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1HostAlias]

property host_network (*self*)

Gets the host_network of this V1alpha1WorkflowSpec. # noqa: E501

Host networking requested for this workflow pod. Default to false. # noqa: E501

Returns The host_network of this V1alpha1WorkflowSpec. # noqa: E501

Return type bool

property image_pull_secrets (*self*)

Gets the image_pull_secrets of this V1alpha1WorkflowSpec. # noqa: E501

Returns The image_pull_secrets of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1LocalObjectReference]

property metrics (*self*)

Gets the metrics of this V1alpha1WorkflowSpec. # noqa: E501

Returns The metrics of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1Metrics*

property node_selector (*self*)

Gets the node_selector of this V1alpha1WorkflowSpec. # noqa: E501

NodeSelector is a selector which will result in all pods of the workflow to be scheduled on the selected node(s). This is able to be overridden by a nodeSelector specified in the template. # noqa: E501

Returns The node_selector of this V1alpha1WorkflowSpec. # noqa: E501

Return type dict(str, str)

property on_exit (*self*)

Gets the on_exit of this V1alpha1WorkflowSpec. # noqa: E501

OnExit is a template reference which is invoked at the end of the workflow, irrespective of the success, failure, or error of the primary v1alpha1. # noqa: E501

Returns The on_exit of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property parallelism (*self*)

Gets the parallelism of this V1alpha1WorkflowSpec. # noqa: E501

Returns The parallelism of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property pod_disruption_budget (*self*)

Gets the pod_disruption_budget of this V1alpha1WorkflowSpec. # noqa: E501

Returns The pod_disruption_budget of this V1alpha1WorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1PodDisruptionBudgetSpec

property pod_gc (*self*)

Gets the pod_gc of this V1alpha1WorkflowSpec. # noqa: E501

Returns The pod_gc of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1PodGC*

property pod_priority (*self*)

Gets the pod_priority of this V1alpha1WorkflowSpec. # noqa: E501

Priority to apply to workflow pods. # noqa: E501

Returns The pod_priority of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property pod_priority_class_name (*self*)

Gets the pod_priority_class_name of this V1alpha1WorkflowSpec. # noqa: E501

PriorityClassName to apply to workflow pods. # noqa: E501

Returns The pod_priority_class_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property pod_spec_patch (*self*)

Gets the pod_spec_patch of this V1alpha1WorkflowSpec. # noqa: E501

PodSpecPatch holds strategic merge patch to apply against the pod spec. Allows parameterization of container fields which are not strings (e.g. resource limits). # noqa: E501

Returns The pod_spec_patch of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property priority (*self*)

Gets the priority of this V1alpha1WorkflowSpec. # noqa: E501

Priority is used if controller is configured to process limited number of workflows in parallel. Workflows with higher priority are processed first. # noqa: E501

Returns The priority of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property scheduler_name (*self*)

Gets the scheduler_name of this V1alpha1WorkflowSpec. # noqa: E501

Returns The scheduler_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property security_context (*self*)

Gets the security_context of this V1alpha1WorkflowSpec. # noqa: E501

Returns The security_context of this V1alpha1WorkflowSpec. # noqa: E501

Return type *kubernetes.client.models.V1PodSecurityContext*

property service_account_name (*self*)

Gets the service_account_name of this V1alpha1WorkflowSpec. # noqa: E501

ServiceAccountName is the name of the ServiceAccount to run all pods of the workflow as. # noqa: E501

Returns The service_account_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property shutdown (*self*)

Gets the shutdown of this V1alpha1WorkflowSpec. # noqa: E501

Returns The shutdown of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property suspend (*self*)

Gets the suspend of this V1alpha1WorkflowSpec. # noqa: E501

Returns The suspend of this V1alpha1WorkflowSpec. # noqa: E501

Return type bool

property templates (*self*)

Gets the templates of this V1alpha1WorkflowSpec. # noqa: E501

Returns The templates of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[V1alpha1Template]

property tolerations (*self*)

Gets the tolerations of this V1alpha1WorkflowSpec. # noqa: E501

Returns The tolerations of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1Toleration]

property ttl_seconds_after_finished (*self*)

Gets the ttl_seconds_after_finished of this V1alpha1WorkflowSpec. # noqa: E501

TTLSecondsAfterFinished limits the lifetime of a Workflow that has finished execution (Succeeded, Failed, Error). If this field is set, once the Workflow finishes, it will be deleted after ttlSecondsAfterFinished expires. If this field is unset, ttlSecondsAfterFinished will not expire. If this field is set to zero, ttlSecondsAfterFinished expires immediately after the Workflow finishes. DEPRECATED: Use TTLStrategy.SecondsAfterCompletion instead. # noqa: E501

Returns The ttl_seconds_after_finished of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property ttl_strategy (*self*)

Gets the ttl_strategy of this V1alpha1WorkflowSpec. # noqa: E501

Returns The ttl_strategy of this V1alpha1WorkflowSpec. # noqa: E501

Return type V1alpha1TTLStrategy

property volume_claim_templates (*self*)

Gets the volume_claim_templates of this V1alpha1WorkflowSpec. # noqa: E501

Returns The volume_claim_templates of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1PersistentVolumeClaim]

property volumes (*self*)

Gets the volumes of this V1alpha1WorkflowSpec. # noqa: E501

Returns The volumes of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1Volume]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.139 `argo.models.v1alpha1_workflow_status`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.140 Module Contents

```
class argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus (compressed_nodes=None,
                                                                    condi-
                                                                    tions=None,
                                                                    fin-
                                                                    ished_at=None,
                                                                    mes-
                                                                    sage=None,
                                                                    nodes=None,
                                                                    of-
                                                                    fload_node_status_version=None,
                                                                    out-
                                                                    puts=None,
                                                                    persis-
                                                                    tent_volume_claims=None,
                                                                    phase=None,
                                                                    re-
                                                                    sources_duration=None,
                                                                    started_at=None,
                                                                    stored_templates=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStatus - a model defined in OpenAPI

openapi_types

attribute_map

property compressed_nodes (*self*)

Gets the compressed_nodes of this V1alpha1WorkflowStatus. # noqa: E501

Returns The compressed_nodes of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property conditions (*self*)

Gets the conditions of this V1alpha1WorkflowStatus. # noqa: E501

Returns The conditions of this V1alpha1WorkflowStatus. # noqa: E501

Return type list[V1alpha1WorkflowCondition]

property finished_at (*self*)

Gets the finished_at of this V1alpha1WorkflowStatus. # noqa: E501

Returns The finished_at of this V1alpha1WorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property message (*self*)

Gets the message of this V1alpha1WorkflowStatus. # noqa: E501

A human readable message indicating details about why the workflow is in this condition. # noqa: E501

Returns The message of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property nodes (*self*)

Gets the nodes of this V1alpha1WorkflowStatus. # noqa: E501

Nodes is a mapping between a node ID and the node's status. # noqa: E501

Returns The nodes of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, *V1alpha1NodeStatus*)

property offload_node_status_version (*self*)

Gets the offload_node_status_version of this V1alpha1WorkflowStatus. # noqa: E501

Whether on not node status has been offloaded to a database. If exists, then Nodes and CompressedNodes will be empty. This will actually be populated with a hash of the offloaded data. # noqa: E501

Returns The offload_node_status_version of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property outputs (*self*)

Gets the outputs of this V1alpha1WorkflowStatus. # noqa: E501

Returns The outputs of this V1alpha1WorkflowStatus. # noqa: E501

Return type *V1alpha1Outputs*

property persistent_volume_claims (*self*)

Gets the persistent_volume_claims of this V1alpha1WorkflowStatus. # noqa: E501

PersistentVolumeClaims tracks all PVCs that were created as part of the v1alpha1. The contents of this list are drained at the end of the workflow. # noqa: E501

Returns The persistent_volume_claims of this V1alpha1WorkflowStatus. # noqa: E501

Return type list[kubernetes.client.models.V1Volume]

property phase (*self*)

Gets the phase of this V1alpha1WorkflowStatus. # noqa: E501

Phase a simple, high-level summary of where the workflow is in its lifecycle. # noqa: E501

Returns The phase of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property resources_duration (*self*)

Gets the resources_duration of this V1alpha1WorkflowStatus. # noqa: E501

Returns The resources_duration of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, str)

property started_at (*self*)

Gets the started_at of this V1alpha1WorkflowStatus. # noqa: E501

Returns The started_at of this V1alpha1WorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property `stored_templates` (*self*)

Gets the stored_templates of this V1alpha1WorkflowStatus. # noqa: E501

StoredTemplates is a mapping between a template ref and the node's status. # noqa: E501

Returns The stored_templates of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, *V1alpha1Template*)

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.141 `argo.models.v1alpha1_workflow_step`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.142 Module Contents

```
class argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep (arguments=None,
                                                                con-
                                                                tinue_on=None,
                                                                name=None,
                                                                on_exit=None,
                                                                template=None,
                                                                tem-
                                                                plate_ref=None,
                                                                when=None,
                                                                with_items=None,
                                                                with_param=None,
                                                                with_sequence=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStep - a model defined in OpenAPI

openapi_types

attribute_map

property `arguments` (*self*)

Gets the arguments of this V1alpha1WorkflowStep. # noqa: E501

Returns The arguments of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1Arguments*

property `continue_on` (*self*)

Gets the continue_on of this V1alpha1WorkflowStep. # noqa: E501

Returns The continue_on of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1ContinueOn*

property name (*self*)

Gets the name of this V1alpha1WorkflowStep. # noqa: E501

Returns The name of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property on_exit (*self*)

Gets the on_exit of this V1alpha1WorkflowStep. # noqa: E501

OnExit is a template reference which is invoked at the end of the template, irrespective of the success, failure, or error of the primary template. # noqa: E501

Returns The on_exit of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property template (*self*)

Gets the template of this V1alpha1WorkflowStep. # noqa: E501

Returns The template of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1WorkflowStep. # noqa: E501

Returns The template_ref of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1TemplateRef*

property when (*self*)

Gets the when of this V1alpha1WorkflowStep. # noqa: E501

Returns The when of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property with_items (*self*)

Gets the with_items of this V1alpha1WorkflowStep. # noqa: E501

Returns The with_items of this V1alpha1WorkflowStep. # noqa: E501

Return type list[*V1alpha1Item*]

property with_param (*self*)

Gets the with_param of this V1alpha1WorkflowStep. # noqa: E501

WithParam expands a step into multiple parallel steps from the value in the parameter, which is expected to be a JSON list. # noqa: E501

Returns The with_param of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property with_sequence (*self*)

Gets the with_sequence of this V1alpha1WorkflowStep. # noqa: E501

Returns The with_sequence of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1Sequence*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.143 argo.models.v1alpha1_workflow_stop_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.144 Module Contents

```
class argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest (message=None,  
name=None,  
names-  
pace=None,  
node_field_selector=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStopRequest - a model defined in OpenAPI

openapi_types

attribute_map

property message (*self*)

Gets the message of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The message of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property name (*self*)

Gets the name of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property node_field_selector (*self*)

Gets the node_field_selector of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The node_field_selector of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.145 argo.models.v1alpha1_workflow_suspend_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.146 Module Contents

class argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest *(name=None, namespace=None)*

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowSuspendRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.147 argo.models.v1alpha1_workflow_template

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.148 Module Contents

```
class argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate (metadata=None,  
                                                                    spec=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowTemplate. # noqa: E501

Returns The metadata of this V1alpha1WorkflowTemplate. # noqa: E501

Return type kubernetes.client.models.V1ObjectMeta

property spec (*self*)

Gets the spec of this V1alpha1WorkflowTemplate. # noqa: E501

Returns The spec of this V1alpha1WorkflowTemplate. # noqa: E501

Return type *V1alpha1WorkflowTemplateSpec*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.1.149 argo.models.v1alpha1_workflow_template_create_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.1.150 Module Contents

```
class argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateCreateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Returns The create_options of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Return type `str`

property template (*self*)

Gets the template of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Returns The template of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Return type `V1alpha1WorkflowTemplate`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.151 `argo.models.v1alpha1_workflow_template_lint_request`

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.152 Module Contents

class `argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest`

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateLintRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Returns The create_options of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Return type `str`

property template (*self*)

Gets the template of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Returns The template of this V1alpha1WorkflowTemplateLintRequest. # noqa: E501

Return type *V1alpha1WorkflowTemplate*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.153 argo.models.v1alpha1_workflow_template_list

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.154 Module Contents

class argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList (*items=None, meta-data=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateList - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)

Gets the items of this V1alpha1WorkflowTemplateList. # noqa: E501

Returns The items of this V1alpha1WorkflowTemplateList. # noqa: E501

Return type list[*V1alpha1WorkflowTemplate*]

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowTemplateList. # noqa: E501

Returns The metadata of this V1alpha1WorkflowTemplateList. # noqa: E501

Return type *kubernetes.client.models.V1ListMeta*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.155 argo.models.v1alpha1_workflow_template_spec

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.156 Module Contents

class argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec (*workflow_spec=*

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateSpec - a model defined in OpenAPI

openapi_types

attribute_map

property workflow_spec (*self*)

Gets the workflow_spec of this V1alpha1WorkflowTemplateSpec. # noqa: E501

Returns The workflow_spec of this V1alpha1WorkflowTemplateSpec. # noqa: E501

Return type *V1alpha1WorkflowSpec*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.157 argo.models.v1alpha1_workflow_template_update_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.158 Module Contents

class argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateUpdateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Return type str

property template (*self*)

Gets the template of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Returns The template of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Return type *V1alpha1WorkflowTemplate*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

1.1.1.1.159 argo.models.v1alpha1_workflow_terminate_request

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.160 Module Contents

class argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest (*name*
name
pace

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTerminateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowTerminateRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowTerminateRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowTerminateRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowTerminateRequest. # noqa: E501

Return type str

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

1.1.1.1.161 argo.models.v1alpha1_workflow_watch_event

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.1.1.162 Module Contents

class argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent (*object=None, type=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowWatchEvent - a model defined in OpenAPI

openapi_types

attribute_map

property type (*self*)
Gets the type of this V1alpha1WorkflowWatchEvent. # noqa: E501

Returns The type of this V1alpha1WorkflowWatchEvent. # noqa: E501

Return type str

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

1.1.1.1.2 Package Contents

class argo.models.Cronv1alpha1CreateCronWorkflowRequest (*create_options=None, cron_workflow=None, namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Cronv1alpha1CreateCronWorkflowRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)
Gets the create_options of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501

Returns The create_options of this Cronv1alpha1CreateCronWorkflowRequest. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property `cron_workflow` (*self*)

Gets the `cron_workflow` of this `Cronv1alpha1CreateCronWorkflowRequest`. # noqa: E501

Returns The `cron_workflow` of this `Cronv1alpha1CreateCronWorkflowRequest`. # noqa: E501

Return type `V1alpha1CronWorkflow`

property `namespace` (*self*)

Gets the `namespace` of this `Cronv1alpha1CreateCronWorkflowRequest`. # noqa: E501

Returns The `namespace` of this `Cronv1alpha1CreateCronWorkflowRequest`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.Cronv1alpha1LintCronWorkflowRequest` (*cron_workflow=None*,
namespace=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`Cronv1alpha1LintCronWorkflowRequest` - a model defined in OpenAPI

openapi_types

attribute_map

property `cron_workflow` (*self*)

Gets the `cron_workflow` of this `Cronv1alpha1LintCronWorkflowRequest`. # noqa: E501

Returns The `cron_workflow` of this `Cronv1alpha1LintCronWorkflowRequest`. # noqa: E501

Return type `V1alpha1CronWorkflow`

property `namespace` (*self*)

Gets the `namespace` of this `Cronv1alpha1LintCronWorkflowRequest`. # noqa: E501

Returns The `namespace` of this `Cronv1alpha1LintCronWorkflowRequest`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.Cronv1alpha1UpdateCronWorkflowRequest` (*cron_workflow=None*,
name=None, *namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`Cronv1alpha1UpdateCronWorkflowRequest` - a model defined in OpenAPI

openapi_types

attribute_map

property `cron_workflow` (*self*)

Gets the cron_workflow of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The cron_workflow of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type *V1alpha1CronWorkflow*

property `name` (*self*)

Gets the name of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The name of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type str

property `namespace` (*self*)

Gets the namespace of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Returns The namespace of this Cronv1alpha1UpdateCronWorkflowRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.GoogleProtobufAny` (*type_url=None, value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

GoogleProtobufAny - a model defined in OpenAPI

openapi_types

attribute_map

property `type_url` (*self*)

Gets the type_url of this GoogleProtobufAny. # noqa: E501

Returns The type_url of this GoogleProtobufAny. # noqa: E501

Return type str

property `value` (*self*)

Gets the value of this GoogleProtobufAny. # noqa: E501

Returns The value of this GoogleProtobufAny. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.GrpcGatewayRuntimeStreamError` (*details=None, grpc_code=None, http_code=None, http_status=None, message=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

GrpcGatewayRuntimeStreamError - a model defined in OpenAPI

openapi_types

attribute_map

property details (*self*)

Gets the details of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The details of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type list[*GoogleProtobufAny*]

property grpc_code (*self*)

Gets the grpc_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The grpc_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type int

property http_code (*self*)

Gets the http_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The http_code of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type int

property http_status (*self*)

Gets the http_status of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The http_status of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type str

property message (*self*)

Gets the message of this GrpcGatewayRuntimeStreamError. # noqa: E501

Returns The message of this GrpcGatewayRuntimeStreamError. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ArchiveStrategy (*_none=None, tar=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArchiveStrategy - a model defined in OpenAPI

openapi_types

attribute_map

property tar (*self*)

Gets the tar of this V1alpha1ArchiveStrategy. # noqa: E501

Returns The tar of this V1alpha1ArchiveStrategy. # noqa: E501

Return type object

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1Arguments (artifacts=None, parameters=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Arguments - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts (*self*)

Gets the artifacts of this V1alpha1Arguments. # noqa: E501

Returns The artifacts of this V1alpha1Arguments. # noqa: E501

Return type list[V1alpha1Artifact]

property parameters (*self*)

Gets the parameters of this V1alpha1Arguments. # noqa: E501

Returns The parameters of this V1alpha1Arguments. # noqa: E501

Return type list[V1alpha1Parameter]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1Artifact (archive=None, artifact_location=None, _from=None,
                                     global_name=None, mode=None, name=None, optional=None, path=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Artifact - a model defined in OpenAPI

openapi_types

attribute_map

property archive (*self*)

Gets the archive of this V1alpha1Artifact. # noqa: E501

Returns The archive of this V1alpha1Artifact. # noqa: E501

Return type V1alpha1ArchiveStrategy

property artifact_location (*self*)

Gets the artifact_location of this V1alpha1Artifact. # noqa: E501

Returns The artifact_location of this V1alpha1Artifact. # noqa: E501

Return type V1alpha1ArtifactLocation

property global_name (*self*)

Gets the global_name of this V1alpha1Artifact. # noqa: E501

Returns The global_name of this V1alpha1Artifact. # noqa: E501

Return type str

property mode (*self*)

Gets the mode of this V1alpha1Artifact. # noqa: E501

mode bits to use on this file, must be a value between 0 and 0777 set when loading input artifacts. # noqa: E501

Returns The mode of this V1alpha1Artifact. # noqa: E501

Return type int

property name (*self*)

Gets the name of this V1alpha1Artifact. # noqa: E501

name of the artifact. must be unique within a template's inputs/outputs. # noqa: E501

Returns The name of this V1alpha1Artifact. # noqa: E501

Return type str

property optional (*self*)

Gets the optional of this V1alpha1Artifact. # noqa: E501

Returns The optional of this V1alpha1Artifact. # noqa: E501

Return type bool

property path (*self*)

Gets the path of this V1alpha1Artifact. # noqa: E501

Returns The path of this V1alpha1Artifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1ArtifactLocation (archive_logs=None,          artifactory=None,
                                           gcs=None, git=None, hdfs=None, http=None,
                                           oss=None, raw=None, s3=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactLocation - a model defined in OpenAPI

openapi_types**attribute_map****property archive_logs** (*self*)

Gets the archive_logs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The archive_logs of this V1alpha1ArtifactLocation. # noqa: E501

Return type bool

property artifactory (*self*)

Gets the artifactory of this V1alpha1ArtifactLocation. # noqa: E501

Returns The artifactory of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1ArtifactoryArtifact*

property gcs (*self*)

Gets the gcs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The gcs of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1GCSArtifact*

property `git` (*self*)

Gets the git of this V1alpha1ArtifactLocation. # noqa: E501

Returns The git of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1GitArtifact*

property `hdfs` (*self*)

Gets the hdfs of this V1alpha1ArtifactLocation. # noqa: E501

Returns The hdfs of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1HDFSArtifact*

property `http` (*self*)

Gets the http of this V1alpha1ArtifactLocation. # noqa: E501

Returns The http of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1HTTPArtifact*

property `oss` (*self*)

Gets the oss of this V1alpha1ArtifactLocation. # noqa: E501

Returns The oss of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1OSSArtifact*

property `raw` (*self*)

Gets the raw of this V1alpha1ArtifactLocation. # noqa: E501

Returns The raw of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1RawArtifact*

property `s3` (*self*)

Gets the s3 of this V1alpha1ArtifactLocation. # noqa: E501

Returns The s3 of this V1alpha1ArtifactLocation. # noqa: E501

Return type *V1alpha1S3Artifact*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1ArtifactRepositoryRef` (*config_map=None, key=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactRepositoryRef - a model defined in OpenAPI

openapi_types

attribute_map

property `config_map` (*self*)

Gets the config_map of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Returns The config_map of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Return type str

property `key` (*self*)

Gets the key of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Returns The key of this V1alpha1ArtifactRepositoryRef. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1ArtifactFactoryArtifact` (*artifactory_auth=None, url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactFactoryArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property `artifactory_auth` (*self*)

Gets the artifactory_auth of this V1alpha1ArtifactFactoryArtifact. # noqa: E501

Returns The artifactory_auth of this V1alpha1ArtifactFactoryArtifact. # noqa: E501

Return type *V1alpha1ArtifactAuth*

property `url` (*self*)

Gets the url of this V1alpha1ArtifactFactoryArtifact. # noqa: E501

Returns The url of this V1alpha1ArtifactFactoryArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1ArtifactFactoryAuth` (*password_secret=None, user-
name_secret=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ArtifactFactoryAuth - a model defined in OpenAPI

openapi_types

attribute_map

property `password_secret` (*self*)

Gets the password_secret of this V1alpha1ArtifactFactoryAuth. # noqa: E501

Returns The password_secret of this V1alpha1ArtifactFactoryAuth. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

property `username_secret` (*self*)

Gets the username_secret of this V1alpha1ArtifactFactoryAuth. # noqa: E501

Returns The username_secret of this V1alpha1ArtifactoryAuth. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Backoff (*duration=None, factor=None, max_duration=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Backoff - a model defined in OpenAPI

openapi_types

attribute_map

property duration (*self*)

Gets the duration of this V1alpha1Backoff. # noqa: E501

Returns The duration of this V1alpha1Backoff. # noqa: E501

Return type str

property factor (*self*)

Gets the factor of this V1alpha1Backoff. # noqa: E501

Returns The factor of this V1alpha1Backoff. # noqa: E501

Return type int

property max_duration (*self*)

Gets the max_duration of this V1alpha1Backoff. # noqa: E501

Returns The max_duration of this V1alpha1Backoff. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ContinueOn (*error=None, failed=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ContinueOn - a model defined in OpenAPI

openapi_types

attribute_map

property error (*self*)

Gets the error of this V1alpha1ContinueOn. # noqa: E501

Returns The error of this V1alpha1ContinueOn. # noqa: E501

Return type bool

property failed (*self*)

Gets the failed of this V1alpha1ContinueOn. # noqa: E501

Returns The failed of this V1alpha1ContinueOn. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Counter (*value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Counter - a model defined in OpenAPI

openapi_types

attribute_map

property value (*self*)

Gets the value of this V1alpha1Counter. # noqa: E501

Returns The value of this V1alpha1Counter. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1CronWorkflow (*metadata=None, spec=None, status=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflow - a model defined in OpenAPI

openapi_types

attribute_map

property metadata (*self*)

Gets the metadata of this V1alpha1CronWorkflow. # noqa: E501

Returns The metadata of this V1alpha1CronWorkflow. # noqa: E501

Return type kubernetes.client.models.V1ObjectMeta

property spec (*self*)

Gets the spec of this V1alpha1CronWorkflow. # noqa: E501

Returns The spec of this V1alpha1CronWorkflow. # noqa: E501

Return type *V1alpha1CronWorkflowSpec*

property status (*self*)

Gets the status of this V1alpha1CronWorkflow. # noqa: E501

Returns The status of this V1alpha1CronWorkflow. # noqa: E501

Return type *V1alpha1CronWorkflowStatus*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

class argo.models.V1alpha1CronWorkflowList (*items=None, metadata=None*)
NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowList - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)
Gets the items of this V1alpha1CronWorkflowList. # noqa: E501
Returns The items of this V1alpha1CronWorkflowList. # noqa: E501
Return type list[V1alpha1CronWorkflow]

property metadata (*self*)
Gets the metadata of this V1alpha1CronWorkflowList. # noqa: E501
Returns The metadata of this V1alpha1CronWorkflowList. # noqa: E501
Return type kubernetes.client.models.V1ListMeta

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

class argo.models.V1alpha1CronWorkflowSpec (*concurrency_policy=None, failed_jobs_history_limit=None, schedule=None, starting_deadline_seconds=None, successful_jobs_history_limit=None, suspend=None, timezone=None, workflow_meta=None, workflow_spec=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowSpec - a model defined in OpenAPI

openapi_types

attribute_map

property concurrency_policy (*self*)
Gets the concurrency_policy of this V1alpha1CronWorkflowSpec. # noqa: E501
Returns The concurrency_policy of this V1alpha1CronWorkflowSpec. # noqa: E501
Return type str

property failed_jobs_history_limit (*self*)
Gets the failed_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501
Returns The failed_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501
Return type int

property schedule (*self*)
Gets the schedule of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The schedule of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property starting_deadline_seconds (*self*)

Gets the starting_deadline_seconds of this V1alpha1CronWorkflowSpec. # noqa: E501

StartingDeadlineSeconds is the K8s-style deadline that will limit the time a CronWorkflow will be run after its original scheduled time if it is missed. # noqa: E501

Returns The starting_deadline_seconds of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property successful_jobs_history_limit (*self*)

Gets the successful_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The successful_jobs_history_limit of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type int

property suspend (*self*)

Gets the suspend of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The suspend of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type bool

property timezone (*self*)

Gets the timezone of this V1alpha1CronWorkflowSpec. # noqa: E501

Timezone is the timezone against which the cron schedule will be calculated, e.g. "Asia/Tokyo". Default is machine's local time. # noqa: E501

Returns The timezone of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type str

property workflow_meta (*self*)

Gets the workflow_meta of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The workflow_meta of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1ObjectMeta

property workflow_spec (*self*)

Gets the workflow_spec of this V1alpha1CronWorkflowSpec. # noqa: E501

Returns The workflow_spec of this V1alpha1CronWorkflowSpec. # noqa: E501

Return type *V1alpha1WorkflowSpec*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1CronWorkflowStatus (*active=None, last_scheduled_time=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1CronWorkflowStatus - a model defined in OpenAPI

openapi_types

attribute_map

property active (*self*)

Gets the active of this V1alpha1CronWorkflowStatus. # noqa: E501

Returns The active of this V1alpha1CronWorkflowStatus. # noqa: E501

Return type list[kubernetes.client.models.V1ObjectReference]

property last_scheduled_time (*self*)

Gets the last_scheduled_time of this V1alpha1CronWorkflowStatus. # noqa: E501

Returns The last_scheduled_time of this V1alpha1CronWorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1DAGTask (arguments=None, continue_on=None, dependencies=None, name=None, on_exit=None, template=None, template_ref=None, when=None, with_items=None, with_param=None, with_sequence=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1DAGTask - a model defined in OpenAPI

openapi_types**attribute_map****property arguments** (*self*)

Gets the arguments of this V1alpha1DAGTask. # noqa: E501

Returns The arguments of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1Arguments*

property continue_on (*self*)

Gets the continue_on of this V1alpha1DAGTask. # noqa: E501

Returns The continue_on of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1ContinueOn*

property dependencies (*self*)

Gets the dependencies of this V1alpha1DAGTask. # noqa: E501

Returns The dependencies of this V1alpha1DAGTask. # noqa: E501

Return type list[str]

property name (*self*)

Gets the name of this V1alpha1DAGTask. # noqa: E501

Returns The name of this V1alpha1DAGTask. # noqa: E501

Return type str

property on_exit (*self*)

Gets the on_exit of this V1alpha1DAGTask. # noqa: E501

OnExit is a template reference which is invoked at the end of the template, irrespective of the success, failure, or error of the primary template. # noqa: E501

Returns The on_exit of this V1alpha1DAGTask. # noqa: E501

Return type str

property template (*self*)

Gets the template of this V1alpha1DAGTask. # noqa: E501

Returns The template of this V1alpha1DAGTask. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1DAGTask. # noqa: E501

Returns The template_ref of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1TemplateRef*

property when (*self*)

Gets the when of this V1alpha1DAGTask. # noqa: E501

Returns The when of this V1alpha1DAGTask. # noqa: E501

Return type str

property with_items (*self*)

Gets the with_items of this V1alpha1DAGTask. # noqa: E501

Returns The with_items of this V1alpha1DAGTask. # noqa: E501

Return type list[*V1alpha1Item*]

property with_param (*self*)

Gets the with_param of this V1alpha1DAGTask. # noqa: E501

WithParam expands a task into multiple parallel tasks from the value in the parameter, which is expected to be a JSON list. # noqa: E501

Returns The with_param of this V1alpha1DAGTask. # noqa: E501

Return type str

property with_sequence (*self*)

Gets the with_sequence of this V1alpha1DAGTask. # noqa: E501

Returns The with_sequence of this V1alpha1DAGTask. # noqa: E501

Return type *V1alpha1Sequence*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1DAGTemplate (*fail_fast=None, target=None, tasks=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1DAGTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property fail_fast (*self*)

Gets the fail_fast of this V1alpha1DAGTemplate. # noqa: E501

Returns The fail_fast of this V1alpha1DAGTemplate. # noqa: E501

Return type bool

property target (*self*)

Gets the target of this V1alpha1DAGTemplate. # noqa: E501

Returns The target of this V1alpha1DAGTemplate. # noqa: E501

Return type str

property tasks (*self*)

Gets the tasks of this V1alpha1DAGTemplate. # noqa: E501

Returns The tasks of this V1alpha1DAGTemplate. # noqa: E501

Return type list[V1alpha1DAGTask]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ExecutorConfig (*service_account_name=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ExecutorConfig - a model defined in OpenAPI

openapi_types

attribute_map

property service_account_name (*self*)

Gets the service_account_name of this V1alpha1ExecutorConfig. # noqa: E501

ServiceAccountName specifies the service account name of the executor container. # noqa: E501

Returns The service_account_name of this V1alpha1ExecutorConfig. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1GCSArtifact (*g_cs_bucket=None, key=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GCSArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property g_cs_bucket (*self*)

Gets the g_cs_bucket of this V1alpha1GCSArtifact. # noqa: E501

Returns The g_cs_bucket of this V1alpha1GCSArtifact. # noqa: E501

Return type V1alpha1GCSBucket

property key (*self*)

Gets the key of this V1alpha1GCSArtifact. # noqa: E501

Returns The key of this V1alpha1GCSArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1GCSBucket (*bucket=None, service_account_key_secret=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GCSBucket - a model defined in OpenAPI

openapi_types

attribute_map

property bucket (*self*)

Gets the bucket of this V1alpha1GCSBucket. # noqa: E501

Returns The bucket of this V1alpha1GCSBucket. # noqa: E501

Return type str

property service_account_key_secret (*self*)

Gets the service_account_key_secret of this V1alpha1GCSBucket. # noqa: E501

Returns The service_account_key_secret of this V1alpha1GCSBucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Gauge (*realtime=None, value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Gauge - a model defined in OpenAPI

openapi_types

attribute_map

property realtime (*self*)

Gets the realtime of this V1alpha1Gauge. # noqa: E501

Returns The realtime of this V1alpha1Gauge. # noqa: E501

Return type bool

property value (*self*)

Gets the value of this V1alpha1Gauge. # noqa: E501

Returns The value of this V1alpha1Gauge. # noqa: E501

Return type str

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

```
class argo.models.V1alpha1GitArtifact (depth=None,          fetch=None,          inse-
                                     cure_ignore_host_key=None,      pass-
                                     word_secret=None,          repo=None,          revi-
                                     sion=None,    ssh_private_key_secret=None, user-
                                     name_secret=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1GitArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property depth (*self*)
Gets the depth of this V1alpha1GitArtifact. # noqa: E501
Returns The depth of this V1alpha1GitArtifact. # noqa: E501
Return type str

property fetch (*self*)
Gets the fetch of this V1alpha1GitArtifact. # noqa: E501
Returns The fetch of this V1alpha1GitArtifact. # noqa: E501
Return type list[str]

property insecure_ignore_host_key (*self*)
Gets the insecure_ignore_host_key of this V1alpha1GitArtifact. # noqa: E501
Returns The insecure_ignore_host_key of this V1alpha1GitArtifact. # noqa: E501
Return type bool

property password_secret (*self*)
Gets the password_secret of this V1alpha1GitArtifact. # noqa: E501
Returns The password_secret of this V1alpha1GitArtifact. # noqa: E501
Return type kubernetes.client.models.V1SecretKeySelector

property repo (*self*)
Gets the repo of this V1alpha1GitArtifact. # noqa: E501
Returns The repo of this V1alpha1GitArtifact. # noqa: E501
Return type str

property revision (*self*)
Gets the revision of this V1alpha1GitArtifact. # noqa: E501
Returns The revision of this V1alpha1GitArtifact. # noqa: E501
Return type str

property ssh_private_key_secret (*self*)
Gets the ssh_private_key_secret of this V1alpha1GitArtifact. # noqa: E501
Returns The ssh_private_key_secret of this V1alpha1GitArtifact. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

property `username_secret` (*self*)

Gets the `username_secret` of this `V1alpha1GitArtifact`. # noqa: E501

Returns The `username_secret` of this `V1alpha1GitArtifact`. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1HDFSArtifact` (*force=None, h_dfs_config=None, path=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1HDFSArtifact` - a model defined in OpenAPI

openapi_types

attribute_map

property `force` (*self*)

Gets the `force` of this `V1alpha1HDFSArtifact`. # noqa: E501

Returns The `force` of this `V1alpha1HDFSArtifact`. # noqa: E501

Return type `bool`

property `h_dfs_config` (*self*)

Gets the `h_dfs_config` of this `V1alpha1HDFSArtifact`. # noqa: E501

Returns The `h_dfs_config` of this `V1alpha1HDFSArtifact`. # noqa: E501

Return type `V1alpha1HDFSConfig`

property `path` (*self*)

Gets the `path` of this `V1alpha1HDFSArtifact`. # noqa: E501

Returns The `path` of this `V1alpha1HDFSArtifact`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1HDFSConfig` (*addresses=None, h_dfs_krb_config=None, hdfs_user=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1HDFSConfig` - a model defined in OpenAPI

openapi_types

attribute_map

property `addresses` (*self*)

Gets the `addresses` of this `V1alpha1HDFSConfig`. # noqa: E501

Returns The addresses of this V1alpha1HDFSConfig. # noqa: E501

Return type list[str]

property h_dfs_krb_config (*self*)

Gets the h_dfs_krb_config of this V1alpha1HDFSConfig. # noqa: E501

Returns The h_dfs_krb_config of this V1alpha1HDFSConfig. # noqa: E501

Return type *V1alpha1HDFSkrbConfig*

property hdfs_user (*self*)

Gets the hdfs_user of this V1alpha1HDFSConfig. # noqa: E501

HDFSUser is the user to access HDFS file system. It is ignored if either ccache or keytab is used. # noqa: E501

Returns The hdfs_user of this V1alpha1HDFSConfig. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1HDFSkrbConfig (krb_c_cache_secret=None,
                                         krb_config_config_map=None,
                                         krb_keytab_secret=None,      krb_realm=None,
                                         krb_service_principal_name=None,
                                         krb_username=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HDFSkrbConfig - a model defined in OpenAPI

openapi_types

attribute_map

property krb_c_cache_secret (*self*)

Gets the krb_c_cache_secret of this V1alpha1HDFSkrbConfig. # noqa: E501

Returns The krb_c_cache_secret of this V1alpha1HDFSkrbConfig. # noqa: E501

Return type *kubernetes.client.models.V1SecretKeySelector*

property krb_config_config_map (*self*)

Gets the krb_config_config_map of this V1alpha1HDFSkrbConfig. # noqa: E501

Returns The krb_config_config_map of this V1alpha1HDFSkrbConfig. # noqa: E501

Return type *kubernetes.client.models.V1ConfigMapKeySelector*

property krb_keytab_secret (*self*)

Gets the krb_keytab_secret of this V1alpha1HDFSkrbConfig. # noqa: E501

Returns The krb_keytab_secret of this V1alpha1HDFSkrbConfig. # noqa: E501

Return type *kubernetes.client.models.V1SecretKeySelector*

property krb_realm (*self*)

Gets the krb_realm of this V1alpha1HDFSkrbConfig. # noqa: E501

KrbRealm is the Kerberos realm used with Kerberos keytab It must be set if keytab is used. # noqa: E501

Returns The krb_realm of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type str

property `krb_service_principal_name` (*self*)

Gets the krb_service_principal_name of this V1alpha1HDFSKrbConfig. # noqa: E501

KrbServicePrincipalName is the principal name of Kerberos service It must be set if either ccache or keytab is used. # noqa: E501

Returns The krb_service_principal_name of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type str

property `krb_username` (*self*)

Gets the krb_username of this V1alpha1HDFSKrbConfig. # noqa: E501

KrbUsername is the Kerberos username used with Kerberos keytab It must be set if keytab is used. # noqa: E501

Returns The krb_username of this V1alpha1HDFSKrbConfig. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1HTTPArtifact` (*url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1HTTPArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property `url` (*self*)

Gets the url of this V1alpha1HTTPArtifact. # noqa: E501

Returns The url of this V1alpha1HTTPArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1Histogram` (*buckets=None, value=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Histogram - a model defined in OpenAPI

openapi_types

attribute_map

property `buckets` (*self*)

Gets the buckets of this V1alpha1Histogram. # noqa: E501

Returns The buckets of this V1alpha1Histogram. # noqa: E501

Return type list[float]

property value (*self*)

Gets the value of this V1alpha1Histogram. # noqa: E501

Returns The value of this V1alpha1Histogram. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1InfoResponse (*links=None, managed_namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1InfoResponse - a model defined in OpenAPI

openapi_types

attribute_map

property links (*self*)

Gets the links of this V1alpha1InfoResponse. # noqa: E501

Returns The links of this V1alpha1InfoResponse. # noqa: E501

Return type list[V1alpha1Link]

property managed_namespace (*self*)

Gets the managed_namespace of this V1alpha1InfoResponse. # noqa: E501

Returns The managed_namespace of this V1alpha1InfoResponse. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Inputs (*artifacts=None, parameters=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Inputs - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts (*self*)

Gets the artifacts of this V1alpha1Inputs. # noqa: E501

Returns The artifacts of this V1alpha1Inputs. # noqa: E501

Return type list[V1alpha1Artifact]

property parameters (*self*)

Gets the parameters of this V1alpha1Inputs. # noqa: E501

Returns The parameters of this V1alpha1Inputs. # noqa: E501

Return type list[V1alpha1Parameter]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Item (*bool_val=None*, *list_val=None*, *map_val=None*,
num_val=None, *str_val=None*, *type=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Item - a model defined in OpenAPI

openapi_types

attribute_map

property bool_val (*self*)

Gets the bool_val of this V1alpha1Item. # noqa: E501

Returns The bool_val of this V1alpha1Item. # noqa: E501

Return type bool

property list_val (*self*)

Gets the list_val of this V1alpha1Item. # noqa: E501

Returns The list_val of this V1alpha1Item. # noqa: E501

Return type list[V1alpha1ItemValue]

property map_val (*self*)

Gets the map_val of this V1alpha1Item. # noqa: E501

Returns The map_val of this V1alpha1Item. # noqa: E501

Return type dict(str, V1alpha1ItemValue)

property num_val (*self*)

Gets the num_val of this V1alpha1Item. # noqa: E501

Returns The num_val of this V1alpha1Item. # noqa: E501

Return type str

property str_val (*self*)

Gets the str_val of this V1alpha1Item. # noqa: E501

Returns The str_val of this V1alpha1Item. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1Item. # noqa: E501

Returns The type of this V1alpha1Item. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ItemValue (*bool_val=None, list_val=None, map_val=None, num_val=None, str_val=None, type=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ItemValue - a model defined in OpenAPI

openapi_types

attribute_map

property bool_val (*self*)

Gets the bool_val of this V1alpha1ItemValue. # noqa: E501

Returns The bool_val of this V1alpha1ItemValue. # noqa: E501

Return type bool

property list_val (*self*)

Gets the list_val of this V1alpha1ItemValue. # noqa: E501

Returns The list_val of this V1alpha1ItemValue. # noqa: E501

Return type list[str]

property map_val (*self*)

Gets the map_val of this V1alpha1ItemValue. # noqa: E501

Returns The map_val of this V1alpha1ItemValue. # noqa: E501

Return type dict(str, str)

property num_val (*self*)

Gets the num_val of this V1alpha1ItemValue. # noqa: E501

Returns The num_val of this V1alpha1ItemValue. # noqa: E501

Return type str

property str_val (*self*)

Gets the str_val of this V1alpha1ItemValue. # noqa: E501

Returns The str_val of this V1alpha1ItemValue. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1ItemValue. # noqa: E501

Returns The type of this V1alpha1ItemValue. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Link (*name=None, scope=None, url=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Link - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1Link. # noqa: E501

Returns The name of this V1alpha1Link. # noqa: E501

Return type str

property scope (*self*)

Gets the scope of this V1alpha1Link. # noqa: E501

Returns The scope of this V1alpha1Link. # noqa: E501

Return type str

property url (*self*)

Gets the url of this V1alpha1Link. # noqa: E501

The URL. May contain “\${metadata.namespace}” and “\${metadata.name}”. # noqa: E501

Returns The url of this V1alpha1Link. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1LogEntry (*content=None, pod_name=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1LogEntry - a model defined in OpenAPI

openapi_types

attribute_map

property content (*self*)

Gets the content of this V1alpha1LogEntry. # noqa: E501

Returns The content of this V1alpha1LogEntry. # noqa: E501

Return type str

property pod_name (*self*)

Gets the pod_name of this V1alpha1LogEntry. # noqa: E501

Returns The pod_name of this V1alpha1LogEntry. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```

class argo.models.V1alpha1Metadata (annotations=None, labels=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1Metadata - a model defined in OpenAPI

    openapi_types
    attribute_map

    property annotations (self)
        Gets the annotations of this V1alpha1Metadata. # noqa: E501

        Returns The annotations of this V1alpha1Metadata. # noqa: E501

        Return type dict(str, str)

    property labels (self)
        Gets the labels of this V1alpha1Metadata. # noqa: E501

        Returns The labels of this V1alpha1Metadata. # noqa: E501

        Return type dict(str, str)

    to_dict (self)
        Returns the model properties as a dict

    to_str (self)
        Returns the string representation of the model

class argo.models.V1alpha1MetricLabel (key=None, value=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1MetricLabel - a model defined in OpenAPI

    openapi_types
    attribute_map

    property key (self)
        Gets the key of this V1alpha1MetricLabel. # noqa: E501

        Returns The key of this V1alpha1MetricLabel. # noqa: E501

        Return type str

    property value (self)
        Gets the value of this V1alpha1MetricLabel. # noqa: E501

        Returns The value of this V1alpha1MetricLabel. # noqa: E501

        Return type str

    to_dict (self)
        Returns the model properties as a dict

    to_str (self)
        Returns the string representation of the model

class argo.models.V1alpha1Metrics (prometheus=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1Metrics - a model defined in OpenAPI

```

openapi_types

attribute_map

property prometheus (*self*)

Gets the prometheus of this V1alpha1Metrics. # noqa: E501

Returns The prometheus of this V1alpha1Metrics. # noqa: E501

Return type list[V1alpha1Prometheus]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1NodeStatus (boundary_id=None, children=None, daemoned=None,  
                                         display_name=None, finished_at=None, id=None,  
                                         inputs=None, message=None, name=None, out-  
                                         bound_nodes=None, outputs=None, phase=None,  
                                         pod_ip=None, resources_duration=None,  
                                         started_at=None, stored_template_id=None,  
                                         template_name=None, template_ref=None,  
                                         template_scope=None, type=None, work-  
                                         flow_template_name=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1NodeStatus - a model defined in OpenAPI

openapi_types

attribute_map

property boundary_id (*self*)

Gets the boundary_id of this V1alpha1NodeStatus. # noqa: E501

Returns The boundary_id of this V1alpha1NodeStatus. # noqa: E501

Return type str

property children (*self*)

Gets the children of this V1alpha1NodeStatus. # noqa: E501

Returns The children of this V1alpha1NodeStatus. # noqa: E501

Return type list[str]

property daemoned (*self*)

Gets the daemoned of this V1alpha1NodeStatus. # noqa: E501

Returns The daemoned of this V1alpha1NodeStatus. # noqa: E501

Return type bool

property display_name (*self*)

Gets the display_name of this V1alpha1NodeStatus. # noqa: E501

Returns The display_name of this V1alpha1NodeStatus. # noqa: E501

Return type str

property finished_at (*self*)

Gets the finished_at of this V1alpha1NodeStatus. # noqa: E501

Returns The finished_at of this V1alpha1NodeStatus. # noqa: E501

Return type `kubernetes.client.models.V1Time`

property id (*self*)

Gets the id of this V1alpha1NodeStatus. # noqa: E501

Returns The id of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property inputs (*self*)

Gets the inputs of this V1alpha1NodeStatus. # noqa: E501

Returns The inputs of this V1alpha1NodeStatus. # noqa: E501

Return type `V1alpha1Inputs`

property message (*self*)

Gets the message of this V1alpha1NodeStatus. # noqa: E501

A human readable message indicating details about why the node is in this condition. # noqa: E501

Returns The message of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property name (*self*)

Gets the name of this V1alpha1NodeStatus. # noqa: E501

Returns The name of this V1alpha1NodeStatus. # noqa: E501

Return type `str`

property outbound_nodes (*self*)

Gets the outbound_nodes of this V1alpha1NodeStatus. # noqa: E501

OutboundNodes tracks the node IDs which are considered “outbound” nodes to a template invocation. For every invocation of a template, there are nodes which we considered as “outbound”. Essentially, these are last nodes in the execution sequence to run, before the template is considered completed. These nodes are then connected as parents to a following step. In the case of single pod steps (i.e. container, script, resource templates), this list will be nil since the pod itself is already considered the “outbound” node. In the case of DAGs, outbound nodes are the “target” tasks (tasks with no children). In the case of steps, outbound nodes are all the containers involved in the last step group. NOTE: since templates are composable, the list of outbound nodes are carried upwards when a DAG/steps template invokes another DAG/steps template. In other words, the outbound nodes of a template, will be a superset of the outbound nodes of its last children. # noqa: E501

Returns The outbound_nodes of this V1alpha1NodeStatus. # noqa: E501

Return type `list[str]`

property outputs (*self*)

Gets the outputs of this V1alpha1NodeStatus. # noqa: E501

Returns The outputs of this V1alpha1NodeStatus. # noqa: E501

Return type `V1alpha1Outputs`

property phase (*self*)

Gets the phase of this V1alpha1NodeStatus. # noqa: E501

Phase a simple, high-level summary of where the node is in its lifecycle. Can be used as a state machine. # noqa: E501

Returns The phase of this V1alpha1NodeStatus. # noqa: E501

Return type str

property pod_ip (*self*)

Gets the pod_ip of this V1alpha1NodeStatus. # noqa: E501

Returns The pod_ip of this V1alpha1NodeStatus. # noqa: E501

Return type str

property resources_duration (*self*)

Gets the resources_duration of this V1alpha1NodeStatus. # noqa: E501

ResourcesDuration is indicative, but not accurate, resource duration. This is populated when the nodes completes. # noqa: E501

Returns The resources_duration of this V1alpha1NodeStatus. # noqa: E501

Return type dict(str, str)

property started_at (*self*)

Gets the started_at of this V1alpha1NodeStatus. # noqa: E501

Returns The started_at of this V1alpha1NodeStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property stored_template_id (*self*)

Gets the stored_template_id of this V1alpha1NodeStatus. # noqa: E501

StoredTemplateID is the ID of stored template. DEPRECATED: This value is not used anymore. # noqa: E501

Returns The stored_template_id of this V1alpha1NodeStatus. # noqa: E501

Return type str

property template_name (*self*)

Gets the template_name of this V1alpha1NodeStatus. # noqa: E501

Returns The template_name of this V1alpha1NodeStatus. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1NodeStatus. # noqa: E501

Returns The template_ref of this V1alpha1NodeStatus. # noqa: E501

Return type *V1alpha1TemplateRef*

property template_scope (*self*)

Gets the template_scope of this V1alpha1NodeStatus. # noqa: E501

TemplateScope is the template scope in which the template of this node was retrieved. # noqa: E501

Returns The template_scope of this V1alpha1NodeStatus. # noqa: E501

Return type str

property type (*self*)

Gets the type of this V1alpha1NodeStatus. # noqa: E501

Returns The type of this V1alpha1NodeStatus. # noqa: E501

Return type str


```

property workflow_template_name (self)
    Gets the workflow_template_name of this V1alpha1NodeStatus. # noqa: E501

    WorkflowTemplateName is the WorkflowTemplate resource name on which the resolved template of this
    node is retrieved. DEPRECATED: This value is not used anymore. # noqa: E501

    Returns The workflow_template_name of this V1alpha1NodeStatus. # noqa: E501

    Return type str

to_dict (self)
    Returns the model properties as a dict

to_str (self)
    Returns the string representation of the model

class argo.models.V1alpha1OSSArtifact (key=None, o_ss_bucket=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1OSSArtifact - a model defined in OpenAPI

    openapi_types
    attribute_map

    property key (self)
        Gets the key of this V1alpha1OSSArtifact. # noqa: E501

        Returns The key of this V1alpha1OSSArtifact. # noqa: E501

        Return type str

    property o_ss_bucket (self)
        Gets the o_ss_bucket of this V1alpha1OSSArtifact. # noqa: E501

        Returns The o_ss_bucket of this V1alpha1OSSArtifact. # noqa: E501

        Return type V1alpha1OSSBucket

    to_dict (self)
        Returns the model properties as a dict

    to_str (self)
        Returns the string representation of the model

class argo.models.V1alpha1OSSBucket (access_key_secret=None, bucket=None, endpoint=None,
                                     secret_key_secret=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1OSSBucket - a model defined in OpenAPI

    openapi_types
    attribute_map

    property access_key_secret (self)
        Gets the access_key_secret of this V1alpha1OSSBucket. # noqa: E501

        Returns The access_key_secret of this V1alpha1OSSBucket. # noqa: E501

        Return type kubernetes.client.models.V1SecretKeySelector

    property bucket (self)
        Gets the bucket of this V1alpha1OSSBucket. # noqa: E501

```

Returns The bucket of this V1alpha1OSSBucket. # noqa: E501

Return type str

property endpoint (*self*)

Gets the endpoint of this V1alpha1OSSBucket. # noqa: E501

Returns The endpoint of this V1alpha1OSSBucket. # noqa: E501

Return type str

property secret_key_secret (*self*)

Gets the secret_key_secret of this V1alpha1OSSBucket. # noqa: E501

Returns The secret_key_secret of this V1alpha1OSSBucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Outputs (*artifacts=None, parameters=None, result=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Outputs - a model defined in OpenAPI

openapi_types

attribute_map

property artifacts (*self*)

Gets the artifacts of this V1alpha1Outputs. # noqa: E501

Returns The artifacts of this V1alpha1Outputs. # noqa: E501

Return type list[V1alpha1Artifact]

property parameters (*self*)

Gets the parameters of this V1alpha1Outputs. # noqa: E501

Returns The parameters of this V1alpha1Outputs. # noqa: E501

Return type list[V1alpha1Parameter]

property result (*self*)

Gets the result of this V1alpha1Outputs. # noqa: E501

Returns The result of this V1alpha1Outputs. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1Parameter (*default=None, global_name=None, name=None, value=None, value_from=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Parameter - a model defined in OpenAPI

openapi_types

attribute_map

property default (*self*)

Gets the default of this V1alpha1Parameter. # noqa: E501

Returns The default of this V1alpha1Parameter. # noqa: E501

Return type str

property global_name (*self*)

Gets the global_name of this V1alpha1Parameter. # noqa: E501

Returns The global_name of this V1alpha1Parameter. # noqa: E501

Return type str

property name (*self*)

Gets the name of this V1alpha1Parameter. # noqa: E501

Returns The name of this V1alpha1Parameter. # noqa: E501

Return type str

property value (*self*)

Gets the value of this V1alpha1Parameter. # noqa: E501

Returns The value of this V1alpha1Parameter. # noqa: E501

Return type str

property value_from (*self*)

Gets the value_from of this V1alpha1Parameter. # noqa: E501

Returns The value_from of this V1alpha1Parameter. # noqa: E501

Return type *V1alpha1ValueFrom*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1PodGC (*strategy=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1PodGC - a model defined in OpenAPI

openapi_types

attribute_map

property strategy (*self*)

Gets the strategy of this V1alpha1PodGC. # noqa: E501

Returns The strategy of this V1alpha1PodGC. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1Prometheus (counter=None, gauge=None, help=None, histogram=None, labels=None, name=None, when=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Prometheus - a model defined in OpenAPI

openapi_types

attribute_map

property counter (*self*)

Gets the counter of this V1alpha1Prometheus. # noqa: E501

Returns The counter of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Counter*

property gauge (*self*)

Gets the gauge of this V1alpha1Prometheus. # noqa: E501

Returns The gauge of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Gauge*

property help (*self*)

Gets the help of this V1alpha1Prometheus. # noqa: E501

Returns The help of this V1alpha1Prometheus. # noqa: E501

Return type str

property histogram (*self*)

Gets the histogram of this V1alpha1Prometheus. # noqa: E501

Returns The histogram of this V1alpha1Prometheus. # noqa: E501

Return type *V1alpha1Histogram*

property labels (*self*)

Gets the labels of this V1alpha1Prometheus. # noqa: E501

Returns The labels of this V1alpha1Prometheus. # noqa: E501

Return type list[*V1alpha1MetricLabel*]

property name (*self*)

Gets the name of this V1alpha1Prometheus. # noqa: E501

Returns The name of this V1alpha1Prometheus. # noqa: E501

Return type str

property when (*self*)

Gets the when of this V1alpha1Prometheus. # noqa: E501

Returns The when of this V1alpha1Prometheus. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

class argo.models.V1alpha1RawArtifact (*data=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1RawArtifact - a model defined in OpenAPI

openapi_types

attribute_map

property data (*self*)

Gets the data of this V1alpha1RawArtifact. # noqa: E501

Returns The data of this V1alpha1RawArtifact. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ResourceTemplate (*action=None, failure_condition=None, manifest=None, merge_strategy=None, set_owner_reference=None, success_condition=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ResourceTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property action (*self*)

Gets the action of this V1alpha1ResourceTemplate. # noqa: E501

Returns The action of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property failure_condition (*self*)

Gets the failure_condition of this V1alpha1ResourceTemplate. # noqa: E501

Returns The failure_condition of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property manifest (*self*)

Gets the manifest of this V1alpha1ResourceTemplate. # noqa: E501

Returns The manifest of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property merge_strategy (*self*)

Gets the merge_strategy of this V1alpha1ResourceTemplate. # noqa: E501

Returns The merge_strategy of this V1alpha1ResourceTemplate. # noqa: E501

Return type str

property `set_owner_reference` (*self*)

Gets the `set_owner_reference` of this `V1alpha1ResourceTemplate`. # noqa: E501

`SetOwnerReference` sets the reference to the workflow on the `OwnerReference` of generated resource. # noqa: E501

Returns The `set_owner_reference` of this `V1alpha1ResourceTemplate`. # noqa: E501

Return type `bool`

property `success_condition` (*self*)

Gets the `success_condition` of this `V1alpha1ResourceTemplate`. # noqa: E501

Returns The `success_condition` of this `V1alpha1ResourceTemplate`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1RetryStrategy` (*backoff=None, limit=None, retry_policy=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1RetryStrategy` - a model defined in OpenAPI

openapi_types

attribute_map

property `backoff` (*self*)

Gets the `backoff` of this `V1alpha1RetryStrategy`. # noqa: E501

Returns The `backoff` of this `V1alpha1RetryStrategy`. # noqa: E501

Return type `V1alpha1Backoff`

property `limit` (*self*)

Gets the `limit` of this `V1alpha1RetryStrategy`. # noqa: E501

Returns The `limit` of this `V1alpha1RetryStrategy`. # noqa: E501

Return type `int`

property `retry_policy` (*self*)

Gets the `retry_policy` of this `V1alpha1RetryStrategy`. # noqa: E501

Returns The `retry_policy` of this `V1alpha1RetryStrategy`. # noqa: E501

Return type `str`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1S3Artifact` (*key=None, s3_bucket=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1S3Artifact` - a model defined in OpenAPI

openapi_types

attribute_map

property key (*self*)

Gets the key of this V1alpha1S3Artifact. # noqa: E501

Returns The key of this V1alpha1S3Artifact. # noqa: E501

Return type str

property s3_bucket (*self*)

Gets the s3_bucket of this V1alpha1S3Artifact. # noqa: E501

Returns The s3_bucket of this V1alpha1S3Artifact. # noqa: E501

Return type *V1alpha1S3Bucket*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1S3Bucket (*access_key_secret=None, bucket=None, endpoint=None, insecure=None, region=None, role_arn=None, secret_key_secret=None, use_sdk_creds=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1S3Bucket - a model defined in OpenAPI

openapi_types

attribute_map

property access_key_secret (*self*)

Gets the access_key_secret of this V1alpha1S3Bucket. # noqa: E501

Returns The access_key_secret of this V1alpha1S3Bucket. # noqa: E501

Return type kubernetes.client.models.V1SecretKeySelector

property bucket (*self*)

Gets the bucket of this V1alpha1S3Bucket. # noqa: E501

Returns The bucket of this V1alpha1S3Bucket. # noqa: E501

Return type str

property endpoint (*self*)

Gets the endpoint of this V1alpha1S3Bucket. # noqa: E501

Returns The endpoint of this V1alpha1S3Bucket. # noqa: E501

Return type str

property insecure (*self*)

Gets the insecure of this V1alpha1S3Bucket. # noqa: E501

Returns The insecure of this V1alpha1S3Bucket. # noqa: E501

Return type bool

property region (*self*)

Gets the region of this V1alpha1S3Bucket. # noqa: E501

Returns The region of this V1alpha1S3Bucket. # noqa: E501

Return type str

property `role_arn` (*self*)

Gets the role_arn of this V1alpha1S3Bucket. # noqa: E501

RoleARN is the Amazon Resource Name (ARN) of the role to assume. # noqa: E501

Returns The role_arn of this V1alpha1S3Bucket. # noqa: E501

Return type str

property `secret_key_secret` (*self*)

Gets the secret_key_secret of this V1alpha1S3Bucket. # noqa: E501

Returns The secret_key_secret of this V1alpha1S3Bucket. # noqa: E501

Return type `kubernetes.client.models.V1SecretKeySelector`

property `use_sdk_creds` (*self*)

Gets the use_sdk_creds of this V1alpha1S3Bucket. # noqa: E501

UseSDKCreds tells the driver to figure out credentials based on sdk defaults. # noqa: E501

Returns The use_sdk_creds of this V1alpha1S3Bucket. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1ScriptTemplate` (*container=None, source=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ScriptTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property `container` (*self*)

Gets the container of this V1alpha1ScriptTemplate. # noqa: E501

Returns The container of this V1alpha1ScriptTemplate. # noqa: E501

Return type `kubernetes.client.models.V1Container`

property `source` (*self*)

Gets the source of this V1alpha1ScriptTemplate. # noqa: E501

Returns The source of this V1alpha1ScriptTemplate. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1Sequence (count=None, end=None, format=None, start=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Sequence - a model defined in OpenAPI

openapi_types

attribute_map

property count (*self*)

Gets the count of this V1alpha1Sequence. # noqa: E501

Returns The count of this V1alpha1Sequence. # noqa: E501

Return type str

property end (*self*)

Gets the end of this V1alpha1Sequence. # noqa: E501

Returns The end of this V1alpha1Sequence. # noqa: E501

Return type str

property format (*self*)

Gets the format of this V1alpha1Sequence. # noqa: E501

Returns The format of this V1alpha1Sequence. # noqa: E501

Return type str

property start (*self*)

Gets the start of this V1alpha1Sequence. # noqa: E501

Returns The start of this V1alpha1Sequence. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1SuspendTemplate (duration=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1SuspendTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property duration (*self*)

Gets the duration of this V1alpha1SuspendTemplate. # noqa: E501

Returns The duration of this V1alpha1SuspendTemplate. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1TTLStrategy(seconds_after_completion=None,  
                                     seconds_after_failure=None,          sec-  
                                     onds_after_success=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1TTLStrategy - a model defined in OpenAPI

openapi_types

attribute_map

property seconds_after_completion (*self*)

Gets the seconds_after_completion of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_completion of this V1alpha1TTLStrategy. # noqa: E501

Return type int

property seconds_after_failure (*self*)

Gets the seconds_after_failure of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_failure of this V1alpha1TTLStrategy. # noqa: E501

Return type int

property seconds_after_success (*self*)

Gets the seconds_after_success of this V1alpha1TTLStrategy. # noqa: E501

Returns The seconds_after_success of this V1alpha1TTLStrategy. # noqa: E501

Return type int

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1Template(active_deadline_seconds=None,          affinity=None,  
                                  archive_location=None,          arguments=None,          au-  
                                  tomount_service_account_token=None,          con-  
                                  tainer=None,          daemon=None,          dag=None,          execu-  
                                  tor=None,          host_aliases=None,          init_containers=None,  
                                  inputs=None,          metadata=None,          metrics=None,  
                                  name=None,          node_selector=None,          outputs=None,          par-  
                                  allelism=None,          pod_spec_patch=None,          priority=None,  
                                  priority_class_name=None,          resource=None,          resub-  
                                  mit_pending_pods=None,          retry_strategy=None,          sched-  
                                  uler_name=None,          script=None,          security_context=None,  
                                  service_account_name=None,          sidecars=None,  
                                  steps=None,          suspend=None,          template=None,          tem-  
                                  plate_ref=None,          tolerations=None,          volumes=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1Template - a model defined in OpenAPI

openapi_types

attribute_map

property active_deadline_seconds (*self*)

Gets the active_deadline_seconds of this V1alpha1Template. # noqa: E501

Optional duration in seconds relative to the StartTime that the pod may be active on a node before the system actively tries to terminate the pod; value must be positive integer This field is only applicable to container and script templates. # noqa: E501

Returns The active_deadline_seconds of this V1alpha1Template. # noqa: E501

Return type str

property affinity (*self*)

Gets the affinity of this V1alpha1Template. # noqa: E501

Returns The affinity of this V1alpha1Template. # noqa: E501

Return type kubernetes.client.models.V1Affinity

property archive_location (*self*)

Gets the archive_location of this V1alpha1Template. # noqa: E501

Returns The archive_location of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ArtifactLocation*

property arguments (*self*)

Gets the arguments of this V1alpha1Template. # noqa: E501

Returns The arguments of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Arguments*

property automount_service_account_token (*self*)

Gets the automount_service_account_token of this V1alpha1Template. # noqa: E501

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted in pods. ServiceAccountName of ExecutorConfig must be specified if this value is false. # noqa: E501

Returns The automount_service_account_token of this V1alpha1Template. # noqa: E501

Return type bool

property container (*self*)

Gets the container of this V1alpha1Template. # noqa: E501

Returns The container of this V1alpha1Template. # noqa: E501

Return type kubernetes.client.models.V1Container

property daemon (*self*)

Gets the daemon of this V1alpha1Template. # noqa: E501

Returns The daemon of this V1alpha1Template. # noqa: E501

Return type bool

property dag (*self*)

Gets the dag of this V1alpha1Template. # noqa: E501

Returns The dag of this V1alpha1Template. # noqa: E501

Return type *V1alpha1DAGTemplate*

property executor (*self*)

Gets the executor of this V1alpha1Template. # noqa: E501

Returns The executor of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ExecutorConfig*

property host_aliases (*self*)

Gets the host_aliases of this V1alpha1Template. # noqa: E501

Returns The host_aliases of this V1alpha1Template. # noqa: E501

Return type list[kubernetes.client.models.V1HostAlias]

property init_containers (*self*)

Gets the init_containers of this V1alpha1Template. # noqa: E501

Returns The init_containers of this V1alpha1Template. # noqa: E501

Return type list[*V1alpha1UserContainer*]

property inputs (*self*)

Gets the inputs of this V1alpha1Template. # noqa: E501

Returns The inputs of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Inputs*

property metadata (*self*)

Gets the metadata of this V1alpha1Template. # noqa: E501

Returns The metadata of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Metadata*

property metrics (*self*)

Gets the metrics of this V1alpha1Template. # noqa: E501

Returns The metrics of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Metrics*

property name (*self*)

Gets the name of this V1alpha1Template. # noqa: E501

Returns The name of this V1alpha1Template. # noqa: E501

Return type str

property node_selector (*self*)

Gets the node_selector of this V1alpha1Template. # noqa: E501

NodeSelector is a selector to schedule this step of the workflow to be run on the selected node(s). Overrides the selector set at the workflow level. # noqa: E501

Returns The node_selector of this V1alpha1Template. # noqa: E501

Return type dict(str, str)

property outputs (*self*)

Gets the outputs of this V1alpha1Template. # noqa: E501

Returns The outputs of this V1alpha1Template. # noqa: E501

Return type *V1alpha1Outputs*

property parallelism (*self*)

Gets the parallelism of this V1alpha1Template. # noqa: E501

Parallelism limits the max total parallel pods that can execute at the same time within the boundaries of this template invocation. If additional steps/dag templates are invoked, the pods created by those templates will not be counted towards this total. # noqa: E501

Returns The parallelism of this V1alpha1Template. # noqa: E501

Return type str

property pod_spec_patch (*self*)

Gets the pod_spec_patch of this V1alpha1Template. # noqa: E501

PodSpecPatch holds strategic merge patch to apply against the pod spec. Allows parameterization of container fields which are not strings (e.g. resource limits). # noqa: E501

Returns The pod_spec_patch of this V1alpha1Template. # noqa: E501

Return type str

property priority (*self*)

Gets the priority of this V1alpha1Template. # noqa: E501

Priority to apply to workflow pods. # noqa: E501

Returns The priority of this V1alpha1Template. # noqa: E501

Return type int

property priority_class_name (*self*)

Gets the priority_class_name of this V1alpha1Template. # noqa: E501

PriorityClassName to apply to workflow pods. # noqa: E501

Returns The priority_class_name of this V1alpha1Template. # noqa: E501

Return type str

property resource (*self*)

Gets the resource of this V1alpha1Template. # noqa: E501

Returns The resource of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ResourceTemplate*

property resubmit_pending_pods (*self*)

Gets the resubmit_pending_pods of this V1alpha1Template. # noqa: E501

Returns The resubmit_pending_pods of this V1alpha1Template. # noqa: E501

Return type bool

property retry_strategy (*self*)

Gets the retry_strategy of this V1alpha1Template. # noqa: E501

Returns The retry_strategy of this V1alpha1Template. # noqa: E501

Return type *V1alpha1RetryStrategy*

property scheduler_name (*self*)

Gets the scheduler_name of this V1alpha1Template. # noqa: E501

Returns The scheduler_name of this V1alpha1Template. # noqa: E501

Return type str

property script (*self*)

Gets the script of this V1alpha1Template. # noqa: E501

Returns The script of this V1alpha1Template. # noqa: E501

Return type *V1alpha1ScriptTemplate*

property security_context (*self*)

Gets the security_context of this V1alpha1Template. # noqa: E501

Returns The security_context of this V1alpha1Template. # noqa: E501

Return type `kubernetes.client.models.V1PodSecurityContext`

property service_account_name (*self*)

Gets the service_account_name of this V1alpha1Template. # noqa: E501

Returns The service_account_name of this V1alpha1Template. # noqa: E501

Return type `str`

property sidecars (*self*)

Gets the sidecars of this V1alpha1Template. # noqa: E501

Returns The sidecars of this V1alpha1Template. # noqa: E501

Return type `list[V1alpha1UserContainer]`

property steps (*self*)

Gets the steps of this V1alpha1Template. # noqa: E501

Returns The steps of this V1alpha1Template. # noqa: E501

Return type `list[list]`

property suspend (*self*)

Gets the suspend of this V1alpha1Template. # noqa: E501

Returns The suspend of this V1alpha1Template. # noqa: E501

Return type *V1alpha1SuspendTemplate*

property template (*self*)

Gets the template of this V1alpha1Template. # noqa: E501

Template is the name of the template which is used as the base of this template. DEPRECATED: This field is not used. # noqa: E501

Returns The template of this V1alpha1Template. # noqa: E501

Return type `str`

property template_ref (*self*)

Gets the template_ref of this V1alpha1Template. # noqa: E501

Returns The template_ref of this V1alpha1Template. # noqa: E501

Return type *V1alpha1TemplateRef*

property tolerations (*self*)

Gets the tolerations of this V1alpha1Template. # noqa: E501

Returns The tolerations of this V1alpha1Template. # noqa: E501

Return type `list[kubernetes.client.models.V1Toleration]`

property volumes (*self*)

Gets the volumes of this V1alpha1Template. # noqa: E501

Returns The volumes of this V1alpha1Template. # noqa: E501

Return type `list[kubernetes.client.models.V1Volume]`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1TemplateRef (*name=None, runtime_resolution=None, template=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1TemplateRef - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1TemplateRef. # noqa: E501

Name is the resource name of the template. # noqa: E501

Returns The name of this V1alpha1TemplateRef. # noqa: E501

Return type str

property runtime_resolution (*self*)

Gets the runtime_resolution of this V1alpha1TemplateRef. # noqa: E501

RuntimeResolution skips validation at creation time. By enabling this option, you can create the referred workflow template before the actual runtime. # noqa: E501

Returns The runtime_resolution of this V1alpha1TemplateRef. # noqa: E501

Return type bool

property template (*self*)

Gets the template of this V1alpha1TemplateRef. # noqa: E501

Template is the name of referred template in the resource. # noqa: E501

Returns The template of this V1alpha1TemplateRef. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1UserContainer (*container=None, mirror_volume_mounts=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1UserContainer - a model defined in OpenAPI

openapi_types

attribute_map

property container (*self*)

Gets the container of this V1alpha1UserContainer. # noqa: E501

Returns The container of this V1alpha1UserContainer. # noqa: E501

Return type kubernetes.client.models.V1Container

property mirror_volume_mounts (*self*)

Gets the mirror_volume_mounts of this V1alpha1UserContainer. # noqa: E501

Returns The mirror_volume_mounts of this V1alpha1UserContainer. # noqa: E501

Return type bool

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1ValueFrom (*default=None, jq_filter=None, json_path=None, parameter=None, path=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1ValueFrom - a model defined in OpenAPI

openapi_types

attribute_map

property default (*self*)

Gets the default of this V1alpha1ValueFrom. # noqa: E501

Returns The default of this V1alpha1ValueFrom. # noqa: E501

Return type str

property jq_filter (*self*)

Gets the jq_filter of this V1alpha1ValueFrom. # noqa: E501

Returns The jq_filter of this V1alpha1ValueFrom. # noqa: E501

Return type str

property json_path (*self*)

Gets the json_path of this V1alpha1ValueFrom. # noqa: E501

Returns The json_path of this V1alpha1ValueFrom. # noqa: E501

Return type str

property parameter (*self*)

Gets the parameter of this V1alpha1ValueFrom. # noqa: E501

Returns The parameter of this V1alpha1ValueFrom. # noqa: E501

Return type str

property path (*self*)

Gets the path of this V1alpha1ValueFrom. # noqa: E501

Returns The path of this V1alpha1ValueFrom. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```

class argo.models.V1alpha1Workflow (metadata=None, spec=None, status=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1Workflow - a model defined in OpenAPI

    openapi_types
    attribute_map

    property metadata (self)
        Gets the metadata of this V1alpha1Workflow. # noqa: E501

        Returns The metadata of this V1alpha1Workflow. # noqa: E501

        Return type kubernetes.client.models.V1ObjectMeta

    property spec (self)
        Gets the spec of this V1alpha1Workflow. # noqa: E501

        Returns The spec of this V1alpha1Workflow. # noqa: E501

        Return type V1alpha1WorkflowSpec

    property status (self)
        Gets the status of this V1alpha1Workflow. # noqa: E501

        Returns The status of this V1alpha1Workflow. # noqa: E501

        Return type V1alpha1WorkflowStatus

    to_dict (self)
        Returns the model properties as a dict

    to_str (self)
        Returns the string representation of the model

class argo.models.V1alpha1WorkflowCondition (message=None, status=None, type=None)
    NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech

    Do not edit the class manually.

    V1alpha1WorkflowCondition - a model defined in OpenAPI

    openapi_types
    attribute_map

    property message (self)
        Gets the message of this V1alpha1WorkflowCondition. # noqa: E501

        Returns The message of this V1alpha1WorkflowCondition. # noqa: E501

        Return type str

    property status (self)
        Gets the status of this V1alpha1WorkflowCondition. # noqa: E501

        Returns The status of this V1alpha1WorkflowCondition. # noqa: E501

        Return type str

    property type (self)
        Gets the type of this V1alpha1WorkflowCondition. # noqa: E501

        Returns The type of this V1alpha1WorkflowCondition. # noqa: E501

```

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1WorkflowCreateRequest (create_options=None, instance_id=None, namespace=None, server_dry_run=None, workflow=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowCreateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The create_options of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type kubernetes.client.models.V1CreateOptions

property instance_id (*self*)

Gets the instance_id of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The instance_id of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type str

property server_dry_run (*self*)

Gets the server_dry_run of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The server_dry_run of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type bool

property workflow (*self*)

Gets the workflow of this V1alpha1WorkflowCreateRequest. # noqa: E501

Returns The workflow of this V1alpha1WorkflowCreateRequest. # noqa: E501

Return type *V1alpha1Workflow*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1WorkflowLintRequest (namespace=None, workflow=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowLintRequest - a model defined in OpenAPI

openapi_types

attribute_map

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowLintRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowLintRequest. # noqa: E501

Return type str

property workflow (*self*)

Gets the workflow of this V1alpha1WorkflowLintRequest. # noqa: E501

Returns The workflow of this V1alpha1WorkflowLintRequest. # noqa: E501

Return type *V1alpha1Workflow*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowList (*items=None, metadata=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowList - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)

Gets the items of this V1alpha1WorkflowList. # noqa: E501

Returns The items of this V1alpha1WorkflowList. # noqa: E501

Return type list[*V1alpha1Workflow*]

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowList. # noqa: E501

Returns The metadata of this V1alpha1WorkflowList. # noqa: E501

Return type kubernetes.client.models.V1ListMeta

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowResubmitRequest (*memoized=None, name=None, namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowResubmitRequest - a model defined in OpenAPI

openapi_types

attribute_map

property `memoized(self)`

Gets the memoized of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The memoized of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type bool

property `name(self)`

Gets the name of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type str

property `namespace(self)`

Gets the namespace of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowResubmitRequest. # noqa: E501

Return type str

to_dict `(self)`

Returns the model properties as a dict

to_str `(self)`

Returns the string representation of the model

class `argo.models.V1alpha1WorkflowResumeRequest` (*name=None, namespace=None,*
node_field_selector=None)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowResumeRequest - a model defined in OpenAPI

openapi_types

attribute_map

property `name(self)`

Gets the name of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

property `namespace(self)`

Gets the namespace of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

property `node_field_selector(self)`

Gets the node_field_selector of this V1alpha1WorkflowResumeRequest. # noqa: E501

Returns The node_field_selector of this V1alpha1WorkflowResumeRequest. # noqa: E501

Return type str

to_dict `(self)`

Returns the model properties as a dict

to_str `(self)`

Returns the string representation of the model

class argo.models.V1alpha1WorkflowRetryRequest (*name=None, namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowRetryRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowRetryRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowRetryRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowRetryRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowRetryRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowSpec (*active_deadline_seconds=None, affinity=None, arguments=None, artifact_repository_ref=None, automount_service_account_token=None, dns_config=None, dns_policy=None, entry_point=None, executor=None, host_aliases=None, host_network=None, image_pull_secrets=None, metrics=None, node_selector=None, on_exit=None, parallelism=None, pod_disruption_budget=None, pod_gc=None, pod_priority=None, pod_priority_class_name=None, pod_spec_patch=None, priority=None, scheduler_name=None, security_context=None, service_account_name=None, shutdown=None, suspend=None, templates=None, tolerations=None, ttl_seconds_after_finished=None, ttl_strategy=None, volume_claim_templates=None, volumes=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowSpec - a model defined in OpenAPI

openapi_types

attribute_map

property active_deadline_seconds (*self*)

Gets the active_deadline_seconds of this V1alpha1WorkflowSpec. # noqa: E501

Returns The active_deadline_seconds of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property affinity (*self*)

Gets the affinity of this V1alpha1WorkflowSpec. # noqa: E501

Returns The affinity of this V1alpha1WorkflowSpec. # noqa: E501

Return type `kubernetes.client.models.V1Affinity`

property arguments (*self*)

Gets the arguments of this V1alpha1WorkflowSpec. # noqa: E501

Returns The arguments of this V1alpha1WorkflowSpec. # noqa: E501

Return type `V1alpha1Arguments`

property artifact_repository_ref (*self*)

Gets the artifact_repository_ref of this V1alpha1WorkflowSpec. # noqa: E501

Returns The artifact_repository_ref of this V1alpha1WorkflowSpec. # noqa: E501

Return type `V1alpha1ArtifactRepositoryRef`

property automount_service_account_token (*self*)

Gets the automount_service_account_token of this V1alpha1WorkflowSpec. # noqa: E501

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted in pods. ServiceAccountName of ExecutorConfig must be specified if this value is false. # noqa: E501

Returns The automount_service_account_token of this V1alpha1WorkflowSpec. # noqa: E501

Return type `bool`

property dns_config (*self*)

Gets the dns_config of this V1alpha1WorkflowSpec. # noqa: E501

Returns The dns_config of this V1alpha1WorkflowSpec. # noqa: E501

Return type `kubernetes.client.models.V1PodDNSConfig`

property dns_policy (*self*)

Gets the dns_policy of this V1alpha1WorkflowSpec. # noqa: E501

Set DNS policy for the pod. Defaults to "ClusterFirst". Valid values are 'ClusterFirstWithHostNet', 'ClusterFirst', 'Default' or 'None'. DNS parameters given in DNSConfig will be merged with the policy selected with DNSPolicy. To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'. # noqa: E501

Returns The dns_policy of this V1alpha1WorkflowSpec. # noqa: E501

Return type `str`

property entrypoint (*self*)

Gets the entrypoint of this V1alpha1WorkflowSpec. # noqa: E501

Entrypoint is a template reference to the starting point of the v1alpha1. # noqa: E501

Returns The entrypoint of this V1alpha1WorkflowSpec. # noqa: E501

Return type `str`

property executor (*self*)

Gets the executor of this V1alpha1WorkflowSpec. # noqa: E501

Returns The executor of this V1alpha1WorkflowSpec. # noqa: E501

Return type `V1alpha1ExecutorConfig`

property host_aliases (*self*)

Gets the host_aliases of this V1alpha1WorkflowSpec. # noqa: E501

Returns The host_aliases of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1HostAlias]

property host_network (*self*)

Gets the host_network of this V1alpha1WorkflowSpec. # noqa: E501

Host networking requested for this workflow pod. Default to false. # noqa: E501

Returns The host_network of this V1alpha1WorkflowSpec. # noqa: E501

Return type bool

property image_pull_secrets (*self*)

Gets the image_pull_secrets of this V1alpha1WorkflowSpec. # noqa: E501

Returns The image_pull_secrets of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1LocalObjectReference]

property metrics (*self*)

Gets the metrics of this V1alpha1WorkflowSpec. # noqa: E501

Returns The metrics of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1Metrics*

property node_selector (*self*)

Gets the node_selector of this V1alpha1WorkflowSpec. # noqa: E501

NodeSelector is a selector which will result in all pods of the workflow to be scheduled on the selected node(s). This is able to be overridden by a nodeSelector specified in the template. # noqa: E501

Returns The node_selector of this V1alpha1WorkflowSpec. # noqa: E501

Return type dict(str, str)

property on_exit (*self*)

Gets the on_exit of this V1alpha1WorkflowSpec. # noqa: E501

OnExit is a template reference which is invoked at the end of the workflow, irrespective of the success, failure, or error of the primary v1alpha1. # noqa: E501

Returns The on_exit of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property parallelism (*self*)

Gets the parallelism of this V1alpha1WorkflowSpec. # noqa: E501

Returns The parallelism of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property pod_disruption_budget (*self*)

Gets the pod_disruption_budget of this V1alpha1WorkflowSpec. # noqa: E501

Returns The pod_disruption_budget of this V1alpha1WorkflowSpec. # noqa: E501

Return type kubernetes.client.models.V1PodDisruptionBudgetSpec

property pod_gc (*self*)

Gets the pod_gc of this V1alpha1WorkflowSpec. # noqa: E501

Returns The pod_gc of this V1alpha1WorkflowSpec. # noqa: E501

Return type *V1alpha1PodGC*

property pod_priority (*self*)

Gets the pod_priority of this V1alpha1WorkflowSpec. # noqa: E501

Priority to apply to workflow pods. # noqa: E501

Returns The pod_priority of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property pod_priority_class_name (*self*)

Gets the pod_priority_class_name of this V1alpha1WorkflowSpec. # noqa: E501

PriorityClassName to apply to workflow pods. # noqa: E501

Returns The pod_priority_class_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property pod_spec_patch (*self*)

Gets the pod_spec_patch of this V1alpha1WorkflowSpec. # noqa: E501

PodSpecPatch holds strategic merge patch to apply against the pod spec. Allows parameterization of container fields which are not strings (e.g. resource limits). # noqa: E501

Returns The pod_spec_patch of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property priority (*self*)

Gets the priority of this V1alpha1WorkflowSpec. # noqa: E501

Priority is used if controller is configured to process limited number of workflows in parallel. Workflows with higher priority are processed first. # noqa: E501

Returns The priority of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property scheduler_name (*self*)

Gets the scheduler_name of this V1alpha1WorkflowSpec. # noqa: E501

Returns The scheduler_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property security_context (*self*)

Gets the security_context of this V1alpha1WorkflowSpec. # noqa: E501

Returns The security_context of this V1alpha1WorkflowSpec. # noqa: E501

Return type `kubernetes.client.models.V1PodSecurityContext`

property service_account_name (*self*)

Gets the service_account_name of this V1alpha1WorkflowSpec. # noqa: E501

ServiceAccountName is the name of the ServiceAccount to run all pods of the workflow as. # noqa: E501

Returns The service_account_name of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property shutdown (*self*)

Gets the shutdown of this V1alpha1WorkflowSpec. # noqa: E501

Returns The shutdown of this V1alpha1WorkflowSpec. # noqa: E501

Return type str

property suspend (*self*)

Gets the suspend of this V1alpha1WorkflowSpec. # noqa: E501

Returns The suspend of this V1alpha1WorkflowSpec. # noqa: E501

Return type bool

property templates (*self*)

Gets the templates of this V1alpha1WorkflowSpec. # noqa: E501

Returns The templates of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[V1alpha1Template]

property tolerations (*self*)

Gets the tolerations of this V1alpha1WorkflowSpec. # noqa: E501

Returns The tolerations of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1Toleration]

property ttl_seconds_after_finished (*self*)

Gets the ttl_seconds_after_finished of this V1alpha1WorkflowSpec. # noqa: E501

TTLSecondsAfterFinished limits the lifetime of a Workflow that has finished execution (Succeeded, Failed, Error). If this field is set, once the Workflow finishes, it will be deleted after ttlSecondsAfterFinished expires. If this field is unset, ttlSecondsAfterFinished will not expire. If this field is set to zero, ttlSecondsAfterFinished expires immediately after the Workflow finishes. DEPRECATED: Use TTLStrategy.SecondsAfterCompletion instead. # noqa: E501

Returns The ttl_seconds_after_finished of this V1alpha1WorkflowSpec. # noqa: E501

Return type int

property ttl_strategy (*self*)

Gets the ttl_strategy of this V1alpha1WorkflowSpec. # noqa: E501

Returns The ttl_strategy of this V1alpha1WorkflowSpec. # noqa: E501

Return type V1alpha1TTLStrategy

property volume_claim_templates (*self*)

Gets the volume_claim_templates of this V1alpha1WorkflowSpec. # noqa: E501

Returns The volume_claim_templates of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1PersistentVolumeClaim]

property volumes (*self*)

Gets the volumes of this V1alpha1WorkflowSpec. # noqa: E501

Returns The volumes of this V1alpha1WorkflowSpec. # noqa: E501

Return type list[kubernetes.client.models.V1Volume]

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1WorkflowStatus (compressed_nodes=None, conditions=None,  
finished_at=None, message=None, nodes=None,  
offload_node_status_version=None, outputs=None,  
persistent_volume_claims=None, phase=None,  
resources_duration=None, started_at=None, stored_templates=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStatus - a model defined in OpenAPI

openapi_types

attribute_map

property compressed_nodes (*self*)

Gets the compressed_nodes of this V1alpha1WorkflowStatus. # noqa: E501

Returns The compressed_nodes of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property conditions (*self*)

Gets the conditions of this V1alpha1WorkflowStatus. # noqa: E501

Returns The conditions of this V1alpha1WorkflowStatus. # noqa: E501

Return type list[V1alpha1WorkflowCondition]

property finished_at (*self*)

Gets the finished_at of this V1alpha1WorkflowStatus. # noqa: E501

Returns The finished_at of this V1alpha1WorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property message (*self*)

Gets the message of this V1alpha1WorkflowStatus. # noqa: E501

A human readable message indicating details about why the workflow is in this condition. # noqa: E501

Returns The message of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property nodes (*self*)

Gets the nodes of this V1alpha1WorkflowStatus. # noqa: E501

Nodes is a mapping between a node ID and the node's status. # noqa: E501

Returns The nodes of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, V1alpha1NodeStatus)

property offload_node_status_version (*self*)

Gets the offload_node_status_version of this V1alpha1WorkflowStatus. # noqa: E501

Whether on not node status has been offloaded to a database. If exists, then Nodes and CompressedNodes will be empty. This will actually be populated with a hash of the offloaded data. # noqa: E501

Returns The offload_node_status_version of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property outputs (*self*)

Gets the outputs of this V1alpha1WorkflowStatus. # noqa: E501

Returns The outputs of this V1alpha1WorkflowStatus. # noqa: E501

Return type *V1alpha1Outputs*

property persistent_volume_claims (*self*)

Gets the persistent_volume_claims of this V1alpha1WorkflowStatus. # noqa: E501

PersistentVolumeClaims tracks all PVCs that were created as part of the v1alpha1. The contents of this list are drained at the end of the workflow. # noqa: E501

Returns The persistent_volume_claims of this V1alpha1WorkflowStatus. # noqa: E501

Return type list[kubernetes.client.models.V1Volume]

property phase (*self*)

Gets the phase of this V1alpha1WorkflowStatus. # noqa: E501

Phase a simple, high-level summary of where the workflow is in its lifecycle. # noqa: E501

Returns The phase of this V1alpha1WorkflowStatus. # noqa: E501

Return type str

property resources_duration (*self*)

Gets the resources_duration of this V1alpha1WorkflowStatus. # noqa: E501

Returns The resources_duration of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, str)

property started_at (*self*)

Gets the started_at of this V1alpha1WorkflowStatus. # noqa: E501

Returns The started_at of this V1alpha1WorkflowStatus. # noqa: E501

Return type kubernetes.client.models.V1Time

property stored_templates (*self*)

Gets the stored_templates of this V1alpha1WorkflowStatus. # noqa: E501

StoredTemplates is a mapping between a template ref and the node's status. # noqa: E501

Returns The stored_templates of this V1alpha1WorkflowStatus. # noqa: E501

Return type dict(str, *V1alpha1Template*)

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

```
class argo.models.V1alpha1WorkflowStep (arguments=None, continue_on=None, name=None,
                                         on_exit=None, template=None, template_ref=None,
                                         when=None, with_items=None, with_param=None,
                                         with_sequence=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStep - a model defined in OpenAPI

openapi_types

attribute_map

property arguments (*self*)

Gets the arguments of this V1alpha1WorkflowStep. # noqa: E501

Returns The arguments of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1Arguments*

property continue_on (*self*)

Gets the continue_on of this V1alpha1WorkflowStep. # noqa: E501

Returns The continue_on of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1ContinueOn*

property name (*self*)

Gets the name of this V1alpha1WorkflowStep. # noqa: E501

Returns The name of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property on_exit (*self*)

Gets the on_exit of this V1alpha1WorkflowStep. # noqa: E501

OnExit is a template reference which is invoked at the end of the template, irrespective of the success, failure, or error of the primary template. # noqa: E501

Returns The on_exit of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property template (*self*)

Gets the template of this V1alpha1WorkflowStep. # noqa: E501

Returns The template of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property template_ref (*self*)

Gets the template_ref of this V1alpha1WorkflowStep. # noqa: E501

Returns The template_ref of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1TemplateRef*

property when (*self*)

Gets the when of this V1alpha1WorkflowStep. # noqa: E501

Returns The when of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property with_items (*self*)

Gets the with_items of this V1alpha1WorkflowStep. # noqa: E501

Returns The with_items of this V1alpha1WorkflowStep. # noqa: E501

Return type list[*V1alpha1Item*]

property with_param (*self*)

Gets the with_param of this V1alpha1WorkflowStep. # noqa: E501

WithParam expands a step into multiple parallel steps from the value in the parameter, which is expected to be a JSON list. # noqa: E501

Returns The with_param of this V1alpha1WorkflowStep. # noqa: E501

Return type str

property with_sequence (*self*)

Gets the with_sequence of this V1alpha1WorkflowStep. # noqa: E501

Returns The with_sequence of this V1alpha1WorkflowStep. # noqa: E501

Return type *V1alpha1Sequence*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowStopRequest (*message=None, name=None, namespace=None, node_field_selector=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowStopRequest - a model defined in OpenAPI

openapi_types

attribute_map

property message (*self*)

Gets the message of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The message of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property name (*self*)

Gets the name of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

property node_field_selector (*self*)

Gets the node_field_selector of this V1alpha1WorkflowStopRequest. # noqa: E501

Returns The node_field_selector of this V1alpha1WorkflowStopRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowSuspendRequest (*name=None, namespace=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowSuspendRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Return type str

property namespace (*self*)

Gets the namespace of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Returns The namespace of this V1alpha1WorkflowSuspendRequest. # noqa: E501

Return type str

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowTemplate (*metadata=None, spec=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplate - a model defined in OpenAPI

openapi_types

attribute_map

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowTemplate. # noqa: E501

Returns The metadata of this V1alpha1WorkflowTemplate. # noqa: E501

Return type kubernetes.client.models.V1ObjectMeta

property spec (*self*)

Gets the spec of this V1alpha1WorkflowTemplate. # noqa: E501

Returns The spec of this V1alpha1WorkflowTemplate. # noqa: E501

Return type *V1alpha1WorkflowTemplateSpec*

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowTemplateCreateRequest (*create_options=None, namespace=None, template=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateCreateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Returns The create_options of this V1alpha1WorkflowTemplateCreateRequest. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property namespace (*self*)

Gets the namespace of this `V1alpha1WorkflowTemplateCreateRequest`. # noqa: E501

Returns The namespace of this `V1alpha1WorkflowTemplateCreateRequest`. # noqa: E501

Return type `str`

property template (*self*)

Gets the template of this `V1alpha1WorkflowTemplateCreateRequest`. # noqa: E501

Returns The template of this `V1alpha1WorkflowTemplateCreateRequest`. # noqa: E501

Return type `V1alpha1WorkflowTemplate`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1WorkflowTemplateLintRequest` (*create_options=None, namespace=None, template=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1WorkflowTemplateLintRequest` - a model defined in OpenAPI

openapi_types

attribute_map

property create_options (*self*)

Gets the create_options of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Returns The create_options of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Return type `kubernetes.client.models.V1CreateOptions`

property namespace (*self*)

Gets the namespace of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Returns The namespace of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Return type `str`

property template (*self*)

Gets the template of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Returns The template of this `V1alpha1WorkflowTemplateLintRequest`. # noqa: E501

Return type `V1alpha1WorkflowTemplate`

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class `argo.models.V1alpha1WorkflowTemplateList` (*items=None, metadata=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

`V1alpha1WorkflowTemplateList` - a model defined in OpenAPI

openapi_types

attribute_map

property items (*self*)

Gets the items of this V1alpha1WorkflowTemplateList. # noqa: E501

Returns The items of this V1alpha1WorkflowTemplateList. # noqa: E501

Return type list[V1alpha1WorkflowTemplate]

property metadata (*self*)

Gets the metadata of this V1alpha1WorkflowTemplateList. # noqa: E501

Returns The metadata of this V1alpha1WorkflowTemplateList. # noqa: E501

Return type kubernetes.client.models.V1ListMeta

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowTemplateSpec (*workflow_spec=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateSpec - a model defined in OpenAPI

openapi_types

attribute_map

property workflow_spec (*self*)

Gets the workflow_spec of this V1alpha1WorkflowTemplateSpec. # noqa: E501

Returns The workflow_spec of this V1alpha1WorkflowTemplateSpec. # noqa: E501

Return type V1alpha1WorkflowSpec

to_dict (*self*)

Returns the model properties as a dict

to_str (*self*)

Returns the string representation of the model

class argo.models.V1alpha1WorkflowTemplateUpdateRequest (*name=None, names-pace=None, tem-plate=None*)

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

V1alpha1WorkflowTemplateUpdateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)

Gets the name of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Returns The name of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501

Return type str

property namespace (*self*)
 Gets the namespace of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501
Returns The namespace of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501
Return type str

property template (*self*)
 Gets the template of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501
Returns The template of this V1alpha1WorkflowTemplateUpdateRequest. # noqa: E501
Return type *V1alpha1WorkflowTemplate*

to_dict (*self*)
 Returns the model properties as a dict

to_str (*self*)
 Returns the string representation of the model

class argo.models.V1alpha1WorkflowTerminateRequest (*name=None, namespace=None*)
 NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>
 Do not edit the class manually.
 V1alpha1WorkflowTerminateRequest - a model defined in OpenAPI

openapi_types

attribute_map

property name (*self*)
 Gets the name of this V1alpha1WorkflowTerminateRequest. # noqa: E501
Returns The name of this V1alpha1WorkflowTerminateRequest. # noqa: E501
Return type str

property namespace (*self*)
 Gets the namespace of this V1alpha1WorkflowTerminateRequest. # noqa: E501
Returns The namespace of this V1alpha1WorkflowTerminateRequest. # noqa: E501
Return type str

to_dict (*self*)
 Returns the model properties as a dict

to_str (*self*)
 Returns the string representation of the model

class argo.models.V1alpha1WorkflowWatchEvent (*object=None, type=None*)
 NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>
 Do not edit the class manually.
 V1alpha1WorkflowWatchEvent - a model defined in OpenAPI

openapi_types

attribute_map

property type (*self*)
 Gets the type of this V1alpha1WorkflowWatchEvent. # noqa: E501
Returns The type of this V1alpha1WorkflowWatchEvent. # noqa: E501
Return type str

to_dict (*self*)
Returns the model properties as a dict

to_str (*self*)
Returns the string representation of the model

1.1.2 Submodules

1.1.2.1 argo.configuration

Argo

Argo # noqa: E501

The version of the OpenAPI document: v2.7.5 Generated by: <https://openapi-generator.tech>

1.1.2.1.1 Module Contents

class `argo.configuration.TypeWithDefault` (*cls, name, bases, dct*)

Create and return a new object. See help(type) for accurate signature.

set_default (*cls, default*)

class `argo.configuration.Configuration` (*host='http://localhost:2746', api_key={},
api_key_prefix={}, username="", password=""*)

NOTE: This class is auto generated by OpenAPI Generator

Ref: <https://openapi-generator.tech> Do not edit the class manually.

Parameters

- **host** – Base url
- **api_key** – Dict to store API key(s)
- **api_key_prefix** – Dict to store API prefix (e.g. Bearer)
- **username** – Username for HTTP basic authentication
- **password** – Password for HTTP basic authentication

Constructor

host

Default Base url

temp_folder_path

Temp file folder for downloading files

api_key

dict to store API key(s)

api_key_prefix

dict to store API prefix (e.g. Bearer)

refresh_api_key_hook

function hook to refresh API key if expired

username

Username for HTTP basic authentication

password
Password for HTTP basic authentication

logger
Logging Settings

logger_format = %(asctime)s %(levelname)s %(message)s
Log format

logger_stream_handler
Log stream handler

logger_file_handler
Log file handler

logger_file
Debug file location

debug = False
Debug switch

verify_ssl = True
SSL/TLS verification Set this to false to skip verifying SSL certificate when calling API from https server.

ssl_ca_cert
Set this to customize the certificate file to verify the peer.

cert_file
client certificate file

key_file
client key file

assert_hostname
Set this to True/False to enable/disable SSL hostname verification.

connection_pool_maxsize
urllib3 connection pool's maximum number of connections saved per pool. urllib3 uses 1 connection as default value, but this is not the best value when you are making a lot of possibly parallel requests to the same host, which is often the case here. `cpu_count * 5` is used as default value to increase performance.

proxy
Proxy URL

proxy_headers
Proxy headers

safe_chars_for_path_param =
Safe chars for path_param

retries
Adding retries to override urllib3 default value 3

property logger_file (self)
The logger file.

If the `logger_file` is None, then add stream handler and remove file handler. Otherwise, add file handler and remove stream handler.

Parameters value – The `logger_file` path.

Type str

property debug (*self*)

Debug status

Parameters value – The debug status, True or False.

Type bool

property logger_format (*self*)

The logger format.

The logger_formatter will be updated when sets logger_format.

Parameters value – The format string.

Type str

get_api_key_with_prefix (*self, identifier*)

Gets API key (with prefix if set).

Parameters identifier – The identifier of apiKey.

Returns The token for api key authentication.

get_basic_auth_token (*self*)

Gets HTTP basic authentication header (string).

Returns The token for basic HTTP authentication.

auth_settings (*self*)

Gets Auth Settings dict for api client.

Returns The Auth Settings information dict.

to_debug_report (*self*)

Gets the essential information for debugging.

Returns The report for debugging.

get_host_settings (*self*)

Gets an array of host settings

Returns An array of host settings

get_host_from_settings (*self, index, variables={}*)

Gets host URL based on the index and variables :param index: array index of the host settings :param variables: hash of variable and the corresponding value :return: URL based on host settings

ARGO-MODELS

argo-models is a argo namespaced package with the `argo.models` subpackage which contains the generated OpenAPI models from [Argo](#).

Documentations can be found at <https://argo-models.readthedocs.io/en/latest/>

```
pip install argo-models
```

```
from argo.models import V1alpha1ArtifactLocation, V1alpha1S3Artifact
from kubernetes.client.models import V1SecretKeySelector

# create aws cred
access_key_secret = V1SecretKeySelector(name="s3_secret", key="accesskey")
secret_key_secret = V1SecretKeySelector(name="s3_secret", key="secretkey")

# create artifact config for s3
s3_artifact = V1alpha1S3Artifact(
    bucket="foobar",
    endpoint="s3.amazonaws.com"
    insecure=False,
    access_key_secret=access_key_secret,
    secret_key_secret=secret_key_secret,
    key=""
)

# create artifact location
artifact_location = V1alpha1ArtifactLocation(s3=s3_artifact)
```

2.1 Developer notes

To generate the latest models, update `version.txt` with the desired argo release (e.g. `2.3.0-rc3`) and then run `./generate-api.sh`.

To release new version to pypi, create a release with the corresponding version tag (e.g. `v2.2.1`). Travis will automatically publish the package.

NOTE:

`version.txt` should hold the current/latest argo version to be generated, as it is also used by `setup.py` as the `argo-models` package version.

Please install [@openapitools/openapi-generator-cli](#) to generate the openapi specs.

2.2 License

This package is licensed under [Apache-2.0](#) and is a derivative of the [Argo project](#) using [OpenAPI generator](#).

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

a

argo, 1
argo.configuration, 148
argo.models, 1
argo.models.cronvlalphal_create_cron_workflow_request, 1
argo.models.cronvlalphal_lint_cron_workflow_request, 2
argo.models.cronvlalphal_update_cron_workflow_request, 3
argo.models.google_protobuf_any, 4
argo.models.grpc_gateway_runtime_stream_error, 4
argo.models.vlalphal_archive_strategy, 6
argo.models.vlalphal_arguments, 6
argo.models.vlalphal_artifact, 7
argo.models.vlalphal_artifact_location, 8
argo.models.vlalphal_artifact_repository_ref, 10
argo.models.vlalphal_artifactory_artifact, 11
argo.models.vlalphal_artifactory_auth, 11
argo.models.vlalphal_backoff, 12
argo.models.vlalphal_continue_on, 13
argo.models.vlalphal_counter, 14
argo.models.vlalphal_cron_workflow, 14
argo.models.vlalphal_cron_workflow_list, 15
argo.models.vlalphal_cron_workflow_spec, 16
argo.models.vlalphal_cron_workflow_status, 18
argo.models.vlalphal_dag_task, 18
argo.models.vlalphal_dag_template, 20
argo.models.vlalphal_executor_config, 21
argo.models.vlalphal_gauge, 22
argo.models.vlalphal_gcs_artifact, 23
argo.models.vlalphal_gcs_bucket, 23
argo.models.vlalphal_git_artifact, 24
argo.models.vlalphal_hdfs_artifact, 26
argo.models.vlalphal_hdfs_config, 26
argo.models.vlalphal_hdfs_krb_config, 27
argo.models.vlalphal_histogram, 29
argo.models.vlalphal_http_artifact, 30
argo.models.vlalphal_info_response, 30
argo.models.vlalphal_inputs, 31
argo.models.vlalphal_item, 32
argo.models.vlalphal_item_value, 33
argo.models.vlalphal_link, 34
argo.models.vlalphal_log_entry, 35
argo.models.vlalphal_metadata, 35
argo.models.vlalphal_metric_label, 36
argo.models.vlalphal_metrics, 37
argo.models.vlalphal_node_status, 37
argo.models.vlalphal_oss_artifact, 41
argo.models.vlalphal_oss_bucket, 42
argo.models.vlalphal_outputs, 43
argo.models.vlalphal_parameter, 43
argo.models.vlalphal_pod_gc, 45
argo.models.vlalphal_prometheus, 45
argo.models.vlalphal_raw_artifact, 47
argo.models.vlalphal_resource_template, 47
argo.models.vlalphal_retry_strategy, 49
argo.models.vlalphal_s3_artifact, 49
argo.models.vlalphal_s3_bucket, 50
argo.models.vlalphal_script_template, 52
argo.models.vlalphal_sequence, 52
argo.models.vlalphal_suspend_template, 53
argo.models.vlalphal_template, 54
argo.models.vlalphal_template_ref, 59
argo.models.vlalphal_ttl_strategy, 60
argo.models.vlalphal_user_container, 61
argo.models.vlalphal_value_from, 62
argo.models.vlalphal_workflow, 63
argo.models.vlalphal_workflow_condition, 64

`argo.models.v1alpha1_workflow_create_request,`
65
`argo.models.v1alpha1_workflow_lint_request,`
66
`argo.models.v1alpha1_workflow_list,` 67
`argo.models.v1alpha1_workflow_resubmit_request,`
67
`argo.models.v1alpha1_workflow_resume_request,`
68
`argo.models.v1alpha1_workflow_retry_request,`
69
`argo.models.v1alpha1_workflow_spec,` 70
`argo.models.v1alpha1_workflow_status,`
76
`argo.models.v1alpha1_workflow_step,` 78
`argo.models.v1alpha1_workflow_stop_request,`
80
`argo.models.v1alpha1_workflow_suspend_request,`
81
`argo.models.v1alpha1_workflow_template,`
81
`argo.models.v1alpha1_workflow_template_create_request,`
82
`argo.models.v1alpha1_workflow_template_lint_request,`
83
`argo.models.v1alpha1_workflow_template_list,`
84
`argo.models.v1alpha1_workflow_template_spec,`
85
`argo.models.v1alpha1_workflow_template_update_request,`
85
`argo.models.v1alpha1_workflow_terminate_request,`
86
`argo.models.v1alpha1_workflow_watch_event,`
87

INDEX

A

access_key_secret ()
 (*argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket* property), 42
 access_key_secret ()
 (*argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket* property), 50
 access_key_secret ()
 (*argo.models.V1alpha1OSSBucket* property), 115
 access_key_secret ()
 (*argo.models.V1alpha1S3Bucket* property), 121
 action () (*argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate* property), 48
 action () (*argo.models.V1alpha1ResourceTemplate* property), 119
 active () (*argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus* property), 18
 active () (*argo.models.V1alpha1CronWorkflowStatus* property), 98
 active_deadline_seconds ()
 (*argo.models.v1alpha1_template.V1alpha1Template* property), 55
 active_deadline_seconds ()
 (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 71
 active_deadline_seconds ()
 (*argo.models.V1alpha1Template* property), 124
 active_deadline_seconds ()
 (*argo.models.V1alpha1WorkflowSpec* property), 135
 addresses () (*argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig* property), 27
 addresses () (*argo.models.V1alpha1HDFSConfig* property), 104
 affinity () (*argo.models.v1alpha1_template.V1alpha1Template* property), 55
 affinity () (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 72
 affinity () (*argo.models.V1alpha1Template* property), 125
 affinity () (*argo.models.V1alpha1WorkflowSpec* property), 135
 annotations () (*argo.models.v1alpha1_metadata.V1alpha1Metadata* property), 36
 annotations () (*argo.models.V1alpha1Metadata* property), 111
 api_key (*argo.configuration.Configuration* attribute), 148
 api_key_prefix (*argo.configuration.Configuration* attribute), 148
 archive () (*argo.models.v1alpha1_artifact.V1alpha1Artifact* property), 7
 archive () (*argo.models.V1alpha1Artifact* property), 91
 archive_location ()
 (*argo.models.v1alpha1_template.V1alpha1Template* property), 55
 archive_location ()
 (*argo.models.V1alpha1Template* property), 125
 archive_logs () (*argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation* property), 9
 archive_logs () (*argo.models.V1alpha1ArtifactLocation* property), 92
 argo (module), 1
 argo.configuration (module), 148
 argo.models (module), 1
 argo.models.cronv1alpha1_create_cron_workflow_request (module), 1
 argo.models.cronv1alpha1_lint_cron_workflow_request (module), 2
 argo.models.cronv1alpha1_update_cron_workflow_request (module), 3
 argo.models.google_protobuf_any (module), 4
 argo.models.grpc_gateway_runtime_stream_error (module), 4
 argo.models.v1alpha1_archive_strategy (module), 6
 argo.models.v1alpha1_arguments (module), 6
 argo.models.v1alpha1_artifact (module), 7

`argo.models.v1alpha1_artifact_location (module)`, 8
`argo.models.v1alpha1_artifact_repository_ref (module)`, 10
`argo.models.v1alpha1_artifactory_artifact (module)`, 11
`argo.models.v1alpha1_artifactory_auth (module)`, 11
`argo.models.v1alpha1_backoff (module)`, 12
`argo.models.v1alpha1_continue_on (module)`, 13
`argo.models.v1alpha1_counter (module)`, 14
`argo.models.v1alpha1_cron_workflow (module)`, 14
`argo.models.v1alpha1_cron_workflow_list (module)`, 15
`argo.models.v1alpha1_cron_workflow_spec (module)`, 16
`argo.models.v1alpha1_cron_workflow_status (module)`, 18
`argo.models.v1alpha1_dag_task (module)`, 18
`argo.models.v1alpha1_dag_template (module)`, 20
`argo.models.v1alpha1_executor_config (module)`, 21
`argo.models.v1alpha1_gauge (module)`, 22
`argo.models.v1alpha1_gcs_artifact (module)`, 23
`argo.models.v1alpha1_gcs_bucket (module)`, 23
`argo.models.v1alpha1_git_artifact (module)`, 24
`argo.models.v1alpha1_hdfs_artifact (module)`, 26
`argo.models.v1alpha1_hdfs_config (module)`, 26
`argo.models.v1alpha1_hdfs_krb_config (module)`, 27
`argo.models.v1alpha1_histogram (module)`, 29
`argo.models.v1alpha1_http_artifact (module)`, 30
`argo.models.v1alpha1_info_response (module)`, 30
`argo.models.v1alpha1_inputs (module)`, 31
`argo.models.v1alpha1_item (module)`, 32
`argo.models.v1alpha1_item_value (module)`, 33
`argo.models.v1alpha1_link (module)`, 34
`argo.models.v1alpha1_log_entry (module)`, 35
`argo.models.v1alpha1_metadata (module)`, 35
`argo.models.v1alpha1_metric_label (module)`, 36
`argo.models.v1alpha1_metrics (module)`, 37
`argo.models.v1alpha1_node_status (module)`, 37
`argo.models.v1alpha1_oss_artifact (module)`, 41
`argo.models.v1alpha1_oss_bucket (module)`, 42
`argo.models.v1alpha1_outputs (module)`, 43
`argo.models.v1alpha1_parameter (module)`, 43
`argo.models.v1alpha1_pod_gc (module)`, 45
`argo.models.v1alpha1_prometheus (module)`, 45
`argo.models.v1alpha1_raw_artifact (module)`, 47
`argo.models.v1alpha1_resource_template (module)`, 47
`argo.models.v1alpha1_retry_strategy (module)`, 49
`argo.models.v1alpha1_s3_artifact (module)`, 49
`argo.models.v1alpha1_s3_bucket (module)`, 50
`argo.models.v1alpha1_script_template (module)`, 52
`argo.models.v1alpha1_sequence (module)`, 52
`argo.models.v1alpha1_suspend_template (module)`, 53
`argo.models.v1alpha1_template (module)`, 54
`argo.models.v1alpha1_template_ref (module)`, 59
`argo.models.v1alpha1_ttl_strategy (module)`, 60
`argo.models.v1alpha1_user_container (module)`, 61
`argo.models.v1alpha1_value_from (module)`, 62
`argo.models.v1alpha1_workflow (module)`, 63
`argo.models.v1alpha1_workflow_condition (module)`, 64
`argo.models.v1alpha1_workflow_create_request (module)`, 65
`argo.models.v1alpha1_workflow_lint_request (module)`, 66
`argo.models.v1alpha1_workflow_list (module)`, 67
`argo.models.v1alpha1_workflow_resubmit_request (module)`, 67
`argo.models.v1alpha1_workflow_resume_request (module)`, 68
`argo.models.v1alpha1_workflow_retry_request (module)`, 69
`argo.models.v1alpha1_workflow_spec (module)`, 70

argo.models.v1alpha1_workflow_status (module), 76	artifactory() (argo.models.V1alpha1ArtifactLocation property), 92
argo.models.v1alpha1_workflow_step (mod- ule), 78	artifactory_auth() (argo.models.v1alpha1_artifactory_artifact.V1alpha1Artifactory property), 11
argo.models.v1alpha1_workflow_stop_request (module), 80	artifactory_auth() (argo.models.V1alpha1ArtifactoryArtifact property), 94
argo.models.v1alpha1_workflow_suspend_request (module), 81	artifacts() (argo.models.v1alpha1_arguments.V1alpha1Arguments property), 6
argo.models.v1alpha1_workflow_template (module), 81	create_cron_request() (argo.models.v1alpha1_inputs.V1alpha1Inputs property), 31
argo.models.v1alpha1_workflow_template_create_request (module), 82	delete_request() (argo.models.v1alpha1_outputs.V1alpha1Outputs property), 43
argo.models.v1alpha1_workflow_template_lint_request (module), 83	list_artifacts() (argo.models.V1alpha1Arguments prop- erty), 91
argo.models.v1alpha1_workflow_template_list_artifacts (module), 84	list_artifacts() (argo.models.V1alpha1Inputs property), 107
argo.models.v1alpha1_workflow_template_spec (module), 85	update_request() (argo.models.V1alpha1Outputs prop- erty), 116
argo.models.v1alpha1_workflow_template_update_request (module), 85	hostname (argo.configuration.Configuration attribute), 149
argo.models.v1alpha1_workflow_terminate_request (module), 86	attribute_map (argo.models.cronv1alpha1_create_cron_workflow_req attribute), 2
argo.models.v1alpha1_workflow_watch_event (module), 87	attribute_map (argo.models.cronv1alpha1_lint_cron_workflow_reques attribute), 2
arguments() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask property), 19	attribute_map (argo.models.cronv1alpha1_update_cron_workflow_req attribute), 3
arguments() (argo.models.v1alpha1_template.V1alpha1Template property), 56	attribute_map (argo.models.Cronv1alpha1CreateCronWorkflowReque attribute), 87
arguments() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 72	attribute_map (argo.models.Cronv1alpha1LintCronWorkflowRequest attribute), 88
arguments() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep property), 78	attribute_map (argo.models.Cronv1alpha1UpdateCronWorkflowReque attribute), 88
arguments() (argo.models.V1alpha1DAGTask prop- erty), 99	attribute_map (argo.models.google_protobuf_any.GoogleProtobufAny attribute), 4
arguments() (argo.models.V1alpha1Template prop- erty), 125	attribute_map (argo.models.GoogleProtobufAny at- tribute), 89
arguments() (argo.models.V1alpha1WorkflowSpec property), 136	attribute_map (argo.models.grpc_gateway_runtime_stream_error.Grp attribute), 5
arguments() (argo.models.V1alpha1WorkflowStep property), 141	attribute_map (argo.models.GrpcGatewayRuntimeStreamError attribute), 90
artifact_location() (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 7	attribute_map (argo.models.v1alpha1_archive_strategy.V1alpha1Arch attribute), 6
artifact_location() (argo.models.V1alpha1Artifact property), 91	attribute_map (argo.models.v1alpha1_arguments.V1alpha1Arguments attribute), 6
artifact_repository_ref() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 72	attribute_map (argo.models.v1alpha1_artifact.V1alpha1Artifact attribute), 7
artifact_repository_ref() (argo.models.V1alpha1WorkflowSpec prop- erty), 136	attribute_map (argo.models.v1alpha1_artifact_location.V1alpha1Arti attribute), 9
artifactory() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9	attribute_map (argo.models.v1alpha1_artifact_repository_ref.V1alpha attribute), 10
	attribute_map (argo.models.v1alpha1_artifactory_artifact.V1alpha1A attribute), 11

attribute_map(argo.models.v1alpha1_artifactory_auth.V1alpha1ArtifactoryAuth(artifactory_auth attribute), 12
 attribute_map(argo.models.v1alpha1_artifact.V1alpha1Artifact(artifact attribute), 36
 attribute_map(argo.models.v1alpha1_backoff.V1alpha1Backoff(artifactory_auth attribute), 12
 attribute_map(argo.models.v1alpha1_backoff.V1alpha1Backoff(artifactory_auth attribute), 37
 attribute_map(argo.models.v1alpha1_continue_on.V1alpha1ContinueOn(artifactory_auth attribute), 13
 attribute_map(argo.models.v1alpha1_continue_on.V1alpha1ContinueOn(artifactory_auth attribute), 38
 attribute_map(argo.models.v1alpha1_counter.V1alpha1Counter(artifactory_auth attribute), 14
 attribute_map(argo.models.v1alpha1_counter.V1alpha1Counter(artifactory_auth attribute), 41
 attribute_map(argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow(artifactory_auth attribute), 14
 attribute_map(argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow(artifactory_auth attribute), 42
 attribute_map(argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList(artifactory_auth attribute), 15
 attribute_map(argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList(artifactory_auth attribute), 43
 attribute_map(argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec(artifactory_auth attribute), 16
 attribute_map(argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec(artifactory_auth attribute), 44
 attribute_map(argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus(artifactory_auth attribute), 18
 attribute_map(argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus(artifactory_auth attribute), 45
 attribute_map(argo.models.v1alpha1_dag_task.V1alpha1DAGTask(artifactory_auth attribute), 19
 attribute_map(argo.models.v1alpha1_dag_task.V1alpha1DAGTask(artifactory_auth attribute), 45
 attribute_map(argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate(artifactory_auth attribute), 21
 attribute_map(argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate(artifactory_auth attribute), 47
 attribute_map(argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig(artifactory_auth attribute), 21
 attribute_map(argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig(artifactory_auth attribute), 48
 attribute_map(argo.models.v1alpha1_gauge.V1alpha1Gauge(artifactory_auth attribute), 22
 attribute_map(argo.models.v1alpha1_gauge.V1alpha1Gauge(artifactory_auth attribute), 49
 attribute_map(argo.models.v1alpha1_gcs_artifact.V1alpha1GCSArtifact(artifactory_auth attribute), 23
 attribute_map(argo.models.v1alpha1_gcs_artifact.V1alpha1GCSArtifact(artifactory_auth attribute), 50
 attribute_map(argo.models.v1alpha1_gcs_bucket.V1alpha1GCSBucket(artifactory_auth attribute), 24
 attribute_map(argo.models.v1alpha1_gcs_bucket.V1alpha1GCSBucket(artifactory_auth attribute), 50
 attribute_map(argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact(artifactory_auth attribute), 25
 attribute_map(argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact(artifactory_auth attribute), 52
 attribute_map(argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact(artifactory_auth attribute), 26
 attribute_map(argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact(artifactory_auth attribute), 53
 attribute_map(argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig(artifactory_auth attribute), 27
 attribute_map(argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig(artifactory_auth attribute), 54
 attribute_map(argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSKrbConfig(artifactory_auth attribute), 28
 attribute_map(argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSKrbConfig(artifactory_auth attribute), 55
 attribute_map(argo.models.v1alpha1_histogram.V1alpha1Histogram(artifactory_auth attribute), 29
 attribute_map(argo.models.v1alpha1_histogram.V1alpha1Histogram(artifactory_auth attribute), 60
 attribute_map(argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact(artifactory_auth attribute), 30
 attribute_map(argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact(artifactory_auth attribute), 61
 attribute_map(argo.models.v1alpha1_info_response.V1alpha1InfoResponse(artifactory_auth attribute), 30
 attribute_map(argo.models.v1alpha1_info_response.V1alpha1InfoResponse(artifactory_auth attribute), 62
 attribute_map(argo.models.v1alpha1_inputs.V1alpha1Inputs(artifactory_auth attribute), 31
 attribute_map(argo.models.v1alpha1_inputs.V1alpha1Inputs(artifactory_auth attribute), 62
 attribute_map(argo.models.v1alpha1_item.V1alpha1Item(artifactory_auth attribute), 32
 attribute_map(argo.models.v1alpha1_item.V1alpha1Item(artifactory_auth attribute), 63
 attribute_map(argo.models.v1alpha1_item_value.V1alpha1ItemValue(artifactory_auth attribute), 33
 attribute_map(argo.models.v1alpha1_item_value.V1alpha1ItemValue(artifactory_auth attribute), 64
 attribute_map(argo.models.v1alpha1_link.V1alpha1Link(artifactory_auth attribute), 34
 attribute_map(argo.models.v1alpha1_link.V1alpha1Link(artifactory_auth attribute), 65
 attribute_map(argo.models.v1alpha1_log_entry.V1alpha1LogEntry(artifactory_auth attribute), 35
 attribute_map(argo.models.v1alpha1_log_entry.V1alpha1LogEntry(artifactory_auth attribute), 66
 attribute_map(argo.models.v1alpha1_metadata.V1alpha1Metadata(artifactory_auth attribute), 36
 attribute_map(argo.models.v1alpha1_metadata.V1alpha1Metadata(artifactory_auth attribute), 67

`attribute_map (argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest attribute), 68`
`attribute_map (argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest attribute), 69`
`attribute_map (argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest attribute), 70`
`attribute_map (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec attribute), 71`
`attribute_map (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus attribute), 76`
`attribute_map (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep attribute), 78`
`attribute_map (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest attribute), 80`
`attribute_map (argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest attribute), 81`
`attribute_map (argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate attribute), 82`
`attribute_map (argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest attribute), 82`
`attribute_map (argo.models.v1alpha1_workflow_template_link_request.V1alpha1WorkflowTemplateLinkRequest attribute), 83`
`attribute_map (argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList attribute), 84`
`attribute_map (argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec attribute), 85`
`attribute_map (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest attribute), 85`
`attribute_map (argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest attribute), 86`
`attribute_map (argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent attribute), 87`
`attribute_map (argo.models.V1alpha1ArchiveStrategy attribute), 90`
`attribute_map (argo.models.V1alpha1Arguments attribute), 91`
`attribute_map (argo.models.V1alpha1Artifact attribute), 91`
`attribute_map (argo.models.V1alpha1ArtifactLocation attribute), 92`
`attribute_map (argo.models.V1alpha1ArtifactoryArtifact attribute), 94`
`attribute_map (argo.models.V1alpha1ArtifactoryAuth attribute), 94`
`attribute_map (argo.models.V1alpha1ArtifactRepositoryRef attribute), 93`
`attribute_map (argo.models.V1alpha1Backoff attribute), 95`
`attribute_map (argo.models.V1alpha1ContinueOn attribute), 95`
`attribute_map (argo.models.V1alpha1Counter attribute), 96`
`attribute_map (argo.models.V1alpha1CronWorkflow attribute), 96`
`attribute_map (argo.models.V1alpha1WorkflowRevision attribute), 97`
`attribute_map (argo.models.V1alpha1WorkflowResourceRequirements attribute), 97`
`attribute_map (argo.models.V1alpha1WorkflowStatus attribute), 98`
`attribute_map (argo.models.V1alpha1WorkflowSpec attribute), 99`
`attribute_map (argo.models.V1alpha1WorkflowStatus attribute), 100`
`attribute_map (argo.models.V1alpha1WorkflowStep attribute), 101`
`attribute_map (argo.models.V1alpha1WorkflowStopRequest attribute), 102`
`attribute_map (argo.models.V1alpha1WorkflowSuspendRequest attribute), 101`
`attribute_map (argo.models.V1alpha1WorkflowTemplate attribute), 102`
`attribute_map (argo.models.V1alpha1WorkflowTemplateCreateRequest attribute), 103`
`attribute_map (argo.models.V1alpha1WorkflowTemplateLinkRequest attribute), 104`
`attribute_map (argo.models.V1alpha1WorkflowTemplateList attribute), 104`
`attribute_map (argo.models.V1alpha1WorkflowTemplateSpec attribute), 105`
`attribute_map (argo.models.V1alpha1WorkflowTemplateUpdateRequest attribute), 106`
`attribute_map (argo.models.V1alpha1WorkflowTerminateRequest attribute), 106`
`attribute_map (argo.models.V1alpha1WorkflowWatchEvent attribute), 107`
`attribute_map (argo.models.V1alpha1ArchiveStrategy attribute), 107`
`attribute_map (argo.models.V1alpha1Inputs attribute), 107`
`attribute_map (argo.models.V1alpha1Arguments attribute), 108`
`attribute_map (argo.models.V1alpha1Item attribute), 108`
`attribute_map (argo.models.V1alpha1ItemValue attribute), 109`
`attribute_map (argo.models.V1alpha1Link attribute), 110`
`attribute_map (argo.models.V1alpha1LogEntry attribute), 110`
`attribute_map (argo.models.V1alpha1Metadata attribute), 111`
`attribute_map (argo.models.V1alpha1MetricLabel attribute), 111`
`attribute_map (argo.models.V1alpha1Metrics attribute), 112`
`attribute_map (argo.models.V1alpha1NodeStatus attribute), 112`
`attribute_map (argo.models.V1alpha1OSSArtifact attribute), 115`
`attribute_map (argo.models.V1alpha1OSSBucket attribute), 115`

`attribute_map (argo.models.V1alpha1Outputs attribute), 116`
`attribute_map (argo.models.V1alpha1Parameter attribute), 117`
`attribute_map (argo.models.V1alpha1PodGC attribute), 117`
`attribute_map (argo.models.V1alpha1Prometheus attribute), 118`
`attribute_map (argo.models.V1alpha1RawArtifact attribute), 119`
`attribute_map (argo.models.V1alpha1ResourceTemplate attribute), 119`
`attribute_map (argo.models.V1alpha1RetryStrategy attribute), 120`
`attribute_map (argo.models.V1alpha1S3Artifact attribute), 121`
`attribute_map (argo.models.V1alpha1S3Bucket attribute), 121`
`attribute_map (argo.models.V1alpha1ScriptTemplate attribute), 122`
`attribute_map (argo.models.V1alpha1Sequence attribute), 123`
`attribute_map (argo.models.V1alpha1SuspendTemplate attribute), 123`
`attribute_map (argo.models.V1alpha1Template attribute), 124`
`attribute_map (argo.models.V1alpha1TemplateRef attribute), 129`
`attribute_map (argo.models.V1alpha1TTLStrategy attribute), 124`
`attribute_map (argo.models.V1alpha1UserContainer attribute), 129`
`attribute_map (argo.models.V1alpha1ValueFrom attribute), 130`
`attribute_map (argo.models.V1alpha1Workflow attribute), 131`
`attribute_map (argo.models.V1alpha1WorkflowCondition attribute), 131`
`attribute_map (argo.models.V1alpha1WorkflowCreateRequest attribute), 132`
`attribute_map (argo.models.V1alpha1WorkflowLintRequest attribute), 133`
`attribute_map (argo.models.V1alpha1WorkflowList attribute), 133`
`attribute_map (argo.models.V1alpha1WorkflowResubmitRequest attribute), 133`
`attribute_map (argo.models.V1alpha1WorkflowResumeRequest attribute), 134`
`attribute_map (argo.models.V1alpha1WorkflowRetryRequest attribute), 135`
`attribute_map (argo.models.V1alpha1WorkflowSpec attribute), 135`
`attribute_map (argo.models.V1alpha1WorkflowStatus attribute), 140`
`attribute_map (argo.models.V1alpha1WorkflowStep attribute), 141`
`attribute_map (argo.models.V1alpha1WorkflowStopRequest attribute), 143`
`attribute_map (argo.models.V1alpha1WorkflowSuspendRequest attribute), 143`
`attribute_map (argo.models.V1alpha1WorkflowTemplate attribute), 144`
`attribute_map (argo.models.V1alpha1WorkflowTemplateCreateRequest attribute), 144`
`attribute_map (argo.models.V1alpha1WorkflowTemplateLintRequest attribute), 145`
`attribute_map (argo.models.V1alpha1WorkflowTemplateList attribute), 146`
`attribute_map (argo.models.V1alpha1WorkflowTemplateSpec attribute), 146`
`attribute_map (argo.models.V1alpha1WorkflowTemplateUpdateRequest attribute), 146`
`attribute_map (argo.models.V1alpha1WorkflowTerminateRequest attribute), 147`
`attribute_map (argo.models.V1alpha1WorkflowWatchEvent attribute), 147`
`auth_settings () (argo.configuration.Configuration method), 150`
`automount_service_account_token () (argo.models.v1alpha1_template.V1alpha1Template property), 56`
`automount_service_account_token () (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 72`
`automount_service_account_token () (argo.models.V1alpha1Template property), 125`
`automount_service_account_token () (argo.models.V1alpha1WorkflowSpec property), 136`
B
`backoff () (argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy property), 49`
`backoff () (argo.models.V1alpha1RetryStrategy property), 120`
`bool_val () (argo.models.v1alpha1_item.V1alpha1Item property), 32`
`bool_val () (argo.models.v1alpha1_item_value.V1alpha1ItemValue property), 33`
`bool_val () (argo.models.V1alpha1Item property), 108`
`bool_val () (argo.models.V1alpha1ItemValue property), 109`
`boundary_id () (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 38`
`boundary_id () (argo.models.V1alpha1NodeStatus property), 112`

[bucket\(\) \(argo.models.v1alpha1_gcs_bucket.V1alpha1GCSBucket property\), 24](#)
[bucket\(\) \(argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket property\), 42](#)
[bucket\(\) \(argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket property\), 51](#)
[bucket\(\) \(argo.models.V1alpha1GCSBucket property\), 102](#)
[bucket\(\) \(argo.models.V1alpha1OSSBucket property\), 115](#)
[bucket\(\) \(argo.models.V1alpha1S3Bucket property\), 121](#)
[buckets\(\) \(argo.models.v1alpha1_histogram.V1alpha1Histogram property\), 29](#)
[buckets\(\) \(argo.models.V1alpha1Histogram property\), 106](#)

C

[cert_file \(argo.configuration.Configuration attribute\), 149](#)
[children\(\) \(argo.models.v1alpha1_node_status.V1alpha1NodeStatus property\), 38](#)
[children\(\) \(argo.models.V1alpha1NodeStatus property\), 112](#)
[compressed_nodes\(\) \(argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property\), 76](#)
[compressed_nodes\(\) \(argo.models.V1alpha1WorkflowStatus property\), 140](#)
[concurrency_policy\(\) \(argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property\), 16](#)
[concurrency_policy\(\) \(argo.models.V1alpha1CronWorkflowSpec property\), 97](#)
[conditions\(\) \(argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property\), 76](#)
[conditions\(\) \(argo.models.V1alpha1WorkflowStatus property\), 140](#)
[config_map\(\) \(argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef property\), 10](#)
[config_map\(\) \(argo.models.V1alpha1ArtifactRepositoryRef property\), 93](#)
[Configuration \(class in argo.configuration\), 148](#)
[connection_pool_maxsize \(argo.configuration.Configuration attribute\), 149](#)
[container\(\) \(argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate property\), 52](#)
[container\(\) \(argo.models.v1alpha1_template.V1alpha1Template property\), 56](#)
[container\(\) \(argo.models.v1alpha1_user_container.V1alpha1UserContainer property\), 62](#)

[container\(\) \(argo.models.V1alpha1ScriptTemplate property\), 122](#)
[container\(\) \(argo.models.V1alpha1Template property\), 125](#)
[container\(\) \(argo.models.V1alpha1UserContainer property\), 129](#)
[content\(\) \(argo.models.v1alpha1_log_entry.V1alpha1LogEntry property\), 35](#)
[content\(\) \(argo.models.V1alpha1LogEntry property\), 110](#)
[continue_on\(\) \(argo.models.v1alpha1_dag_task.V1alpha1DAGTask property\), 19](#)
[continue_on\(\) \(argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep property\), 78](#)
[continue_on\(\) \(argo.models.V1alpha1DAGTask property\), 99](#)
[continue_on\(\) \(argo.models.V1alpha1WorkflowStep property\), 142](#)
[count\(\) \(argo.models.v1alpha1_sequence.V1alpha1Sequence property\), 53](#)
[count\(\) \(argo.models.V1alpha1Sequence property\), 123](#)
[counter\(\) \(argo.models.v1alpha1_prometheus.V1alpha1Prometheus property\), 45](#)
[counter\(\) \(argo.models.V1alpha1Prometheus property\), 118](#)
[create_options\(\) \(argo.models.cronv1alpha1_create_cron_workflow.V1alpha1CreateCronWorkflow property\), 2](#)
[create_options\(\) \(argo.models.Cronv1alpha1CreateCronWorkflowRequest property\), 87](#)
[create_options\(\) \(argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest property\), 65](#)
[create_options\(\) \(argo.models.v1alpha1_workflow_template_create.V1alpha1WorkflowTemplateCreateRequest property\), 82](#)
[create_options\(\) \(argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest property\), 83](#)
[create_options\(\) \(argo.models.V1alpha1WorkflowCreateRequest property\), 132](#)
[create_options\(\) \(argo.models.V1alpha1WorkflowTemplateCreateRequest property\), 144](#)
[create_options\(\) \(argo.models.V1alpha1WorkflowTemplateLintRequest property\), 145](#)
[cron_workflow\(\) \(argo.models.cronv1alpha1_create_cron_workflow.V1alpha1CreateCronWorkflow property\), 2](#)
[cron_workflow\(\) \(argo.models.cronv1alpha1_lint_cron_workflow_request.V1alpha1LintCronWorkflowRequest property\), 2](#)
[cron_workflow\(\) \(argo.models.cronv1alpha1_update_cron_workflow_request.V1alpha1UpdateCronWorkflowRequest property\), 3](#)
[cron_workflow\(\) \(argo.models.Cronv1alpha1CreateCronWorkflowRequest property\), 88](#)
[cron_workflow\(\) \(argo.models.Cronv1alpha1LintCronWorkflowRequest property\), 88](#)
[cron_workflow\(\) \(argo.models.Cronv1alpha1UpdateCronWorkflowRequest property\), 88](#)

Cronv1alpha1CreateCronWorkflowRequest
 (class in *argo.models*), 87
 Cronv1alpha1CreateCronWorkflowRequest
 (class in *argo.models.cronv1alpha1_create_cron_workflow_request*), 38
 1
 Cronv1alpha1LintCronWorkflowRequest
 (class in *argo.models*), 88
 Cronv1alpha1LintCronWorkflowRequest
 (class in *argo.models.cronv1alpha1_lint_cron_workflow_request*), 2
 2
 Cronv1alpha1UpdateCronWorkflowRequest
 (class in *argo.models*), 88
 Cronv1alpha1UpdateCronWorkflowRequest
 (class in *argo.models.cronv1alpha1_update_cron_workflow_request*), 3
 3

D

daemon() (*argo.models.v1alpha1_template.V1alpha1Template* property), 56
 daemon() (*argo.models.V1alpha1Template* property), 125
 daemon() (*argo.models.v1alpha1_node_status.V1alpha1NodeStatus* property), 38
 daemon() (*argo.models.V1alpha1NodeStatus* property), 112
 dag() (*argo.models.v1alpha1_template.V1alpha1Template* property), 56
 dag() (*argo.models.V1alpha1Template* property), 125
 data() (*argo.models.v1alpha1_raw_artifact.V1alpha1RawArtifact* property), 47
 data() (*argo.models.V1alpha1RawArtifact* property), 119
 debug (*argo.configuration.Configuration* attribute), 149
 debug() (*argo.configuration.Configuration* property), 149
 default() (*argo.models.v1alpha1_parameter.V1alpha1Parameter* property), 44
 default() (*argo.models.v1alpha1_value_from.V1alpha1ValueFrom* property), 62
 default() (*argo.models.V1alpha1Parameter* property), 117
 default() (*argo.models.V1alpha1ValueFrom* property), 130
 dependencies() (*argo.models.v1alpha1_dag_task.V1alpha1DAGTask* property), 19
 dependencies() (*argo.models.V1alpha1DAGTask* property), 99
 depth() (*argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact* property), 25
 depth() (*argo.models.V1alpha1GitArtifact* property), 103
 details() (*argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError* property), 5

details() (*argo.models.GrpcGatewayRuntimeStreamError* property), 90
 display_name() (*argo.models.v1alpha1_node_status.V1alpha1NodeStatus* property), 112
 display_name() (*argo.models.V1alpha1NodeStatus* property), 112
 dns_config() (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 72
 dns_config() (*argo.models.V1alpha1WorkflowSpec* property), 136
 dns_policy() (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 72
 dns_policy() (*argo.models.V1alpha1WorkflowSpec* property), 136
 duration() (*argo.models.v1alpha1_backoff.V1alpha1Backoff* property), 12
 duration() (*argo.models.v1alpha1_suspend_template.V1alpha1SuspendTemplate* property), 54
 duration() (*argo.models.V1alpha1Backoff* property), 95
 duration() (*argo.models.V1alpha1SuspendTemplate* property), 123

E

end() (*argo.models.v1alpha1_sequence.V1alpha1Sequence* property), 53
 end() (*argo.models.V1alpha1Sequence* property), 123
 endpoint() (*argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket* property), 42
 endpoint() (*argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket* property), 51
 endpoint() (*argo.models.V1alpha1OSSBucket* property), 116
 endpoint() (*argo.models.V1alpha1S3Bucket* property), 121
 endpoint() (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 72
 endpoint() (*argo.models.V1alpha1WorkflowSpec* property), 136
 error() (*argo.models.v1alpha1_continue_on.V1alpha1ContinueOn* property), 13
 error() (*argo.models.V1alpha1ContinueOn* property), 95
 executor() (*argo.models.v1alpha1_template.V1alpha1Template* property), 56
 executor() (*argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec* property), 72
 executor() (*argo.models.V1alpha1Template* property), 125
 executor() (*argo.models.V1alpha1WorkflowSpec* property), 136

F

factor() (*argo.models.v1alpha1_backoff.V1alpha1Backoff*

property), 13

factor() (argo.models.V1alpha1Backoff property), 95

fail_fast() (argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate property), 21

fail_fast() (argo.models.V1alpha1DAGTemplate property), 100

failed() (argo.models.v1alpha1_continue_on.V1alpha1ContinueOn property), 13

failed() (argo.models.V1alpha1ContinueOn property), 95

failed_jobs_history_limit() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 16

failed_jobs_history_limit() (argo.models.V1alpha1CronWorkflowSpec property), 97

failure_condition() (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate property), 48

failure_condition() (argo.models.V1alpha1ResourceTemplate property), 119

fetch() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25

fetch() (argo.models.V1alpha1GitArtifact property), 103

finished_at() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 38

finished_at() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 76

finished_at() (argo.models.V1alpha1NodeStatus property), 112

finished_at() (argo.models.V1alpha1WorkflowStatus property), 140

force() (argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact property), 26

force() (argo.models.V1alpha1HDFSArtifact property), 104

format() (argo.models.v1alpha1_sequence.V1alpha1Sequence property), 53

format() (argo.models.V1alpha1Sequence property), 123

G

g_cs_bucket() (argo.models.v1alpha1_gcs_artifact.V1alpha1GCSArtifact property), 23

g_cs_bucket() (argo.models.V1alpha1GCSArtifact property), 101

gauge() (argo.models.v1alpha1_prometheus.V1alpha1Prometheus property), 46

gauge() (argo.models.V1alpha1Prometheus property), 118

gcs() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9

gcs() (argo.models.V1alpha1ArtifactLocation property), 92

get_with_prefix() (argo.configuration.Configuration method), 150

get_basic_auth_token() (argo.configuration.Configuration method), 150

get_host_from_settings() (argo.configuration.Configuration method), 150

get_workflow_spec() (argo.configuration.Configuration method), 150

git() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9

git() (argo.models.V1alpha1ArtifactLocation property), 93

global_name() (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 7

global_name() (argo.models.v1alpha1_parameter.V1alpha1Parameter property), 44

global_name() (argo.models.V1alpha1Artifact property), 91

global_name() (argo.models.V1alpha1Parameter property), 117

GoogleProtobufAny (class in argo.models), 89

GoogleProtobufAny (class in argo.models.google_protobuf_any), 4

grpc_code() (argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError property), 5

grpc_code() (argo.models.GrpcGatewayRuntimeStreamError property), 90

GrpcGatewayRuntimeStreamError (class in argo.models), 89

GrpcGatewayRuntimeStreamError (class in argo.models.grpc_gateway_runtime_stream_error), 5

H

hdfs_config() (argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact property), 26

hdfs_config() (argo.models.V1alpha1HDFSArtifact property), 104

hdfs_config() (argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig property), 27

hdfs_krb_config() (argo.models.V1alpha1HDFSConfig property), 105

hdfs() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9

hdfs() (argo.models.V1alpha1ArtifactLocation property), 93

`hdfs_user()` (`argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig` property), 27
`hdfs_user()` (`argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig` property), 27
`hdfs_user()` (`argo.models.V1alpha1HDFSConfig` property), 105
`help()` (`argo.models.v1alpha1_prometheus.V1alpha1Prometheus` property), 46
`help()` (`argo.models.V1alpha1Prometheus` property), 118
`help()` (`argo.models.v1alpha1_prometheus.V1alpha1Prometheus` property), 118
`help()` (`argo.models.V1alpha1Prometheus` property), 118
`histogram()` (`argo.models.v1alpha1_prometheus.V1alpha1Prometheus` property), 46
`histogram()` (`argo.models.V1alpha1Prometheus` property), 118
`host` (`argo.configuration.Configuration` attribute), 148
`host_aliases()` (`argo.models.v1alpha1_template.V1alpha1Template` property), 56
`host_aliases()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` property), 73
`host_aliases()` (`argo.models.V1alpha1Template` property), 126
`host_aliases()` (`argo.models.V1alpha1WorkflowSpec` property), 136
`host_network()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` property), 73
`host_network()` (`argo.models.V1alpha1WorkflowSpec` property), 137
`http()` (`argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation` property), 9
`http()` (`argo.models.V1alpha1ArtifactLocation` property), 93
`http_code()` (`argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError` property), 5
`http_code()` (`argo.models.GrpcGatewayRuntimeStreamError` property), 90
`http_status()` (`argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError` property), 5
`http_status()` (`argo.models.GrpcGatewayRuntimeStreamError` property), 90
`id()` (`argo.models.v1alpha1_node_status.V1alpha1NodeStatus` property), 39
`id()` (`argo.models.V1alpha1NodeStatus` property), 113
`image_pull_secrets()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` property), 73
`image_pull_secrets()` (`argo.models.V1alpha1WorkflowSpec` property), 137
`init_containers()` (`argo.models.v1alpha1_template.V1alpha1Template` property), 56
`init_containers()` (`argo.models.V1alpha1Template` property), 126
`jq_filter()` (`argo.models.v1alpha1_value_from.V1alpha1ValueFrom` property), 63
`jq_filter()` (`argo.models.V1alpha1ValueFrom` property), 130
`json_path()` (`argo.models.v1alpha1_value_from.V1alpha1ValueFrom` property), 63
`json_path()` (`argo.models.V1alpha1ValueFrom` property), 130

K

`key()` (`argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef` property), 10
`key()` (`argo.models.v1alpha1_gcs_artifact.V1alpha1GCSArtifact` property), 23
`key()` (`argo.models.v1alpha1_metric_label.V1alpha1MetricLabel` property), 36
`key()` (`argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact` property), 41

key () (argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact property), 50
 key () (argo.models.V1alpha1ArtifactRepositoryRef property), 94
 key () (argo.models.V1alpha1GCSArtifact property), 101
 key () (argo.models.V1alpha1MetricLabel property), 111
 key () (argo.models.V1alpha1OSSArtifact property), 115
 key () (argo.models.V1alpha1S3Artifact property), 121
 key_file (argo.configuration.Configuration attribute), 149
 krb_c_cache_secret () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_c_cache_secret () (argo.models.V1alpha1HDFSkrbConfig property), 105
 krb_config_config_map () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_config_config_map () (argo.models.V1alpha1HDFSkrbConfig property), 105
 krb_keytab_secret () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_keytab_secret () (argo.models.V1alpha1HDFSkrbConfig property), 105
 krb_realm () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_realm () (argo.models.V1alpha1HDFSkrbConfig property), 105
 krb_service_principal_name () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_service_principal_name () (argo.models.V1alpha1HDFSkrbConfig property), 106
 krb_username () (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig property), 28
 krb_username () (argo.models.V1alpha1HDFSkrbConfig property), 106
 labels () (argo.models.v1alpha1_metadata.V1alpha1Metadata property), 36
 labels () (argo.models.v1alpha1_prometheus.V1alpha1Prometheus property), 46
 labels () (argo.models.V1alpha1Metadata property), 111
 labels () (argo.models.V1alpha1Prometheus property), 118
 last_scheduled_time () (argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus property), 18
 last_scheduled_time () (argo.models.V1alpha1CronWorkflowStatus property), 99
 limit () (argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy property), 49
 limit () (argo.models.V1alpha1RetryStrategy property), 120
 links () (argo.models.v1alpha1_info_response.V1alpha1InfoResponse property), 30
 links () (argo.models.V1alpha1InfoResponse property), 107
 list_val () (argo.models.v1alpha1_item.V1alpha1Item property), 32
 list_val () (argo.models.v1alpha1_item_value.V1alpha1ItemValue property), 33
 list_val () (argo.models.V1alpha1Item property), 108
 list_val () (argo.models.V1alpha1ItemValue property), 109
 logger (argo.configuration.Configuration attribute), 149
 logger (argo.configuration.Configuration attribute), 149
 logger_file () (argo.configuration.Configuration property), 149
 logger_file_handler (argo.configuration.Configuration attribute), 149
 logger_format (argo.configuration.Configuration attribute), 149
 logger_format () (argo.configuration.Configuration property), 150
 logger_stream_handler (argo.configuration.Configuration attribute), 149
 managed_namespace () (argo.models.v1alpha1_info_response.V1alpha1InfoResponse property), 31
 managed_namespace () (argo.models.V1alpha1InfoResponse property), 107
 manifest () (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate property), 48
 manifest () (argo.models.V1alpha1ResourceTemplate property), 119
 map_val () (argo.models.v1alpha1_item.V1alpha1Item property), 32

map_val() (argo.models.v1alpha1_item_value.V1alpha1ItemValue property), 97
 property), 33
 map_val() (argo.models.V1alpha1Item property), 108
 map_val() (argo.models.V1alpha1ItemValue property), 109
 max_duration() (argo.models.v1alpha1_backoff.V1alpha1Backoff property), 13
 max_duration() (argo.models.V1alpha1Backoff property), 95
 memoized() (argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest property), 68
 memoized() (argo.models.V1alpha1WorkflowResubmitRequest property), 133
 merge_strategy() (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate property), 48
 merge_strategy() (argo.models.V1alpha1ResourceTemplate property), 119
 message() (argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError property), 5
 message() (argo.models.GrpcGatewayRuntimeStreamError property), 90
 message() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 39
 message() (argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition property), 64
 message() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 76
 message() (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest property), 80
 message() (argo.models.V1alpha1NodeStatus property), 113
 message() (argo.models.V1alpha1WorkflowCondition property), 131
 message() (argo.models.V1alpha1WorkflowStatus property), 140
 message() (argo.models.V1alpha1WorkflowStopRequest property), 143
 metadata() (argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow property), 14
 metadata() (argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList property), 15
 metadata() (argo.models.v1alpha1_template.V1alpha1Template property), 57
 metadata() (argo.models.v1alpha1_workflow.V1alpha1Workflow property), 63
 metadata() (argo.models.v1alpha1_workflow_list.V1alpha1WorkflowList property), 67
 metadata() (argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate property), 82
 metadata() (argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList property), 84
 metadata() (argo.models.V1alpha1CronWorkflow property), 96
 metadata() (argo.models.V1alpha1CronWorkflowList property), 97
 metadata() (argo.models.V1alpha1Template property), 126
 metadata() (argo.models.V1alpha1Workflow property), 131
 metadata() (argo.models.V1alpha1WorkflowList property), 133
 metadata() (argo.models.V1alpha1WorkflowTemplate property), 144
 metadata() (argo.models.V1alpha1WorkflowTemplateList property), 146
 metadata() (argo.models.v1alpha1_template.V1alpha1Template property), 57
 metadata() (argo.models.V1alpha1Template property), 126
 message() (argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError property), 137
 message() (argo.models.GrpcGatewayRuntimeStreamError property), 137
 message() (argo.models.v1alpha1_user_container.V1alpha1UserContainer property), 62
 message() (argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition property), 130
 message() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 7
 message() (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest property), 91

N

name() (argo.models.cron.v1alpha1_update_cron_workflow_request.CronV1alpha1UpdateCronWorkflowRequest property), 3
 name() (argo.models.CronV1alpha1UpdateCronWorkflowRequest property), 89
 name() (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 8
 name() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask property), 19
 name() (argo.models.v1alpha1_link.V1alpha1Link property), 19
 name() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 39
 name() (argo.models.v1alpha1_parameter.V1alpha1Parameter property), 44
 name() (argo.models.v1alpha1_prometheus.V1alpha1Prometheus property), 46
 name() (argo.models.v1alpha1_template.V1alpha1Template property), 57
 name() (argo.models.v1alpha1_template_ref.V1alpha1TemplateRef property), 60
 name() (argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest property), 68
 name() (argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest property), 69

name () (argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest property), 70
 name () (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep property), 78
 name () (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest property), 80
 name () (argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest property), 81
 name () (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest property), 85
 name () (argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest property), 86
 name () (argo.models.V1alpha1Artifact property), 92
 name () (argo.models.V1alpha1DAGTask property), 99
 name () (argo.models.V1alpha1Link property), 110
 name () (argo.models.V1alpha1NodeStatus property), 113
 name () (argo.models.V1alpha1Parameter property), 117
 name () (argo.models.V1alpha1Prometheus property), 118
 name () (argo.models.V1alpha1Template property), 126
 name () (argo.models.V1alpha1TemplateRef property), 129
 name () (argo.models.V1alpha1WorkflowResubmitRequest property), 134
 name () (argo.models.V1alpha1WorkflowResumeRequest property), 134
 name () (argo.models.V1alpha1WorkflowRetryRequest property), 135
 name () (argo.models.V1alpha1WorkflowStep property), 142
 name () (argo.models.V1alpha1WorkflowStopRequest property), 143
 name () (argo.models.V1alpha1WorkflowSuspendRequest property), 143
 name () (argo.models.V1alpha1WorkflowTemplateUpdateRequest property), 146
 name () (argo.models.V1alpha1WorkflowTerminateRequest property), 147
 namespace () (argo.models.cronv1alpha1_create_cron_workflow_request.CronV1alpha1CreateCronWorkflowRequest property), 2
 namespace () (argo.models.cronv1alpha1_lint_cron_workflow_request.CronV1alpha1LintCronWorkflowRequest property), 2
 namespace () (argo.models.cronv1alpha1_update_cron_workflow_request.CronV1alpha1UpdateCronWorkflowRequest property), 3
 namespace () (argo.models.CronV1alpha1CreateCronWorkflowRequest property), 88
 namespace () (argo.models.CronV1alpha1LintCronWorkflowRequest property), 88
 namespace () (argo.models.CronV1alpha1UpdateCronWorkflowRequest property), 89
 namespace () (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest property), 65
 namespace () (argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest property), 66
 namespace () (argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest property), 68
 namespace () (argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest property), 69
 namespace () (argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest property), 70
 namespace () (argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest property), 80
 namespace () (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest property), 80
 namespace () (argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest property), 81
 namespace () (argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest property), 83
 namespace () (argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest property), 83
 namespace () (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest property), 86
 namespace () (argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest property), 86
 namespace () (argo.models.V1alpha1WorkflowCreateRequest property), 132
 namespace () (argo.models.V1alpha1WorkflowLintRequest property), 133
 namespace () (argo.models.V1alpha1WorkflowResubmitRequest property), 134
 namespace () (argo.models.V1alpha1WorkflowResumeRequest property), 134
 namespace () (argo.models.V1alpha1WorkflowRetryRequest property), 135
 namespace () (argo.models.V1alpha1WorkflowStopRequest property), 143
 namespace () (argo.models.V1alpha1WorkflowSuspendRequest property), 144
 namespace () (argo.models.V1alpha1WorkflowTemplateCreateRequest property), 145
 namespace () (argo.models.V1alpha1WorkflowTemplateLintRequest property), 145
 namespace () (argo.models.V1alpha1WorkflowTemplateUpdateRequest property), 146
 namespace () (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest property), 147
 node_field_selector () (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest property), 65
 node_field_selector () (argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest property), 134
 node_field_selector () (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest property), 143

`node_selector()` (`argo.models.v1alpha1_template.V1alpha1Template` `property`), 57
`node_selector()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` `property`), 73
`node_selector()` (`argo.models.V1alpha1Template` `property`), 126
`node_selector()` (`argo.models.V1alpha1WorkflowSpec` `property`), 137
`nodes()` (`argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus` `property`), 77
`nodes()` (`argo.models.V1alpha1WorkflowStatus` `property`), 140
`num_val()` (`argo.models.v1alpha1_item.V1alpha1Item` `property`), 32
`num_val()` (`argo.models.v1alpha1_item_value.V1alpha1ItemValue` `property`), 33
`num_val()` (`argo.models.V1alpha1Item` `property`), 108
`num_val()` (`argo.models.V1alpha1ItemValue` `property`), 109

O

`o_ss_bucket()` (`argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact` `property`), 41
`o_ss_bucket()` (`argo.models.V1alpha1OSSArtifact` `property`), 115
`offload_node_status_version()` (`argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus` `property`), 77
`offload_node_status_version()` (`argo.models.V1alpha1WorkflowStatus` `property`), 140
`on_exit()` (`argo.models.v1alpha1_dag_task.V1alpha1DAGTask` `property`), 19
`on_exit()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` `property`), 73
`on_exit()` (`argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep` `property`), 79
`on_exit()` (`argo.models.V1alpha1DAGTask` `property`), 99
`on_exit()` (`argo.models.V1alpha1WorkflowSpec` `property`), 137
`on_exit()` (`argo.models.V1alpha1WorkflowStep` `property`), 142
`openapi_types` (`argo.models.cronv1alpha1_create_cron_workflow_request.Cronv1alpha1CreateCronWorkflowRequest` `attribute`), 1
`openapi_types` (`argo.models.cronv1alpha1_lint_cron_workflow_request.Cronv1alpha1LintCronWorkflowRequest` `attribute`), 2
`openapi_types` (`argo.models.cronv1alpha1_update_cron_workflow_request.Cronv1alpha1UpdateCronWorkflowRequest` `attribute`), 3
`openapi_types` (`argo.models.Cronv1alpha1CreateCronWorkflowRequest` `attribute`), 24
`openapi_types` (`argo.models.Cronv1alpha1LintCronWorkflowRequest` `attribute`), 24
`openapi_types` (`argo.models.v1alpha1_archive_strategy.V1alpha1ArchiveStrategy` `attribute`), 6
`openapi_types` (`argo.models.v1alpha1_arguments.V1alpha1Arguments` `attribute`), 6
`openapi_types` (`argo.models.v1alpha1_artifact.V1alpha1Artifact` `attribute`), 7
`openapi_types` (`argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation` `attribute`), 9
`openapi_types` (`argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef` `attribute`), 10
`openapi_types` (`argo.models.v1alpha1_artifactory_artifact.V1alpha1ArtifactoryArtifact` `attribute`), 11
`openapi_types` (`argo.models.v1alpha1_artifactory_auth.V1alpha1ArtifactoryAuth` `attribute`), 12
`openapi_types` (`argo.models.v1alpha1_backoff.V1alpha1Backoff` `attribute`), 12
`openapi_types` (`argo.models.v1alpha1_continue_on.V1alpha1ContinueOn` `attribute`), 13
`openapi_types` (`argo.models.v1alpha1_counter.V1alpha1Counter` `attribute`), 14
`openapi_types` (`argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow` `attribute`), 14
`openapi_types` (`argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList` `attribute`), 15
`openapi_types` (`argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec` `attribute`), 16
`openapi_types` (`argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus` `attribute`), 18
`openapi_types` (`argo.models.v1alpha1_dag_task.V1alpha1DAGTask` `attribute`), 19
`openapi_types` (`argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate` `attribute`), 21
`openapi_types` (`argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig` `attribute`), 21
`openapi_types` (`argo.models.v1alpha1_gauge.V1alpha1Gauge` `attribute`), 22
`openapi_types` (`argo.models.v1alpha1_gcs_artifact.V1alpha1GCSEArtifact` `attribute`), 23
`openapi_types` (`argo.models.v1alpha1_gcs_bucket.V1alpha1GCSEBucket` `attribute`), 24
`openapi_types` (`argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact` `attribute`), 24
`openapi_types` (`argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact` `attribute`), 26

openapi_types (argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig (argo.models.v1alpha1_suspend_template.V1alpha1SuspendTemplate (attribute), 27
 openapi_types (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFS_KRB_Config (argo.models.v1alpha1_template.V1alpha1Template (attribute), 28
 openapi_types (argo.models.v1alpha1_histogram.V1alpha1Histogram (argo.models.v1alpha1_template_ref.V1alpha1TemplateRef (attribute), 29
 openapi_types (argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact (argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy (attribute), 30
 openapi_types (argo.models.v1alpha1_info_response.V1alpha1InfoResponse (argo.models.v1alpha1_user_container.V1alpha1UserContainer (attribute), 30
 openapi_types (argo.models.v1alpha1_inputs.V1alpha1Inputs (argo.models.v1alpha1_value_from.V1alpha1ValueFrom (attribute), 31
 openapi_types (argo.models.v1alpha1_item.V1alpha1Item (argo.models.v1alpha1_workflow.V1alpha1Workflow (attribute), 32
 openapi_types (argo.models.v1alpha1_item_value.V1alpha1ItemValue (argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition (attribute), 33
 openapi_types (argo.models.v1alpha1_link.V1alpha1Link (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest (attribute), 34
 openapi_types (argo.models.v1alpha1_log_entry.V1alpha1LogEntry (argo.models.v1alpha1_workflow_lint_request.V1alpha1WorkflowLintRequest (attribute), 35
 openapi_types (argo.models.v1alpha1_metadata.V1alpha1Metadata (argo.models.v1alpha1_workflow_list.V1alpha1WorkflowList (attribute), 36
 openapi_types (argo.models.v1alpha1_metric_label.V1alpha1MetricLabel (argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest (attribute), 36
 openapi_types (argo.models.v1alpha1_metrics.V1alpha1Metrics (argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest (attribute), 37
 openapi_types (argo.models.v1alpha1_node_status.V1alpha1NodeStatus (argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest (attribute), 38
 openapi_types (argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec (attribute), 41
 openapi_types (argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus (attribute), 42
 openapi_types (argo.models.v1alpha1_outputs.V1alpha1Outputs (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep (attribute), 43
 openapi_types (argo.models.v1alpha1_parameter.V1alpha1Parameter (argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest (attribute), 44
 openapi_types (argo.models.v1alpha1_pod_gc.V1alpha1PodGC (argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest (attribute), 45
 openapi_types (argo.models.v1alpha1_prometheus.V1alpha1Prometheus (argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate (attribute), 45
 openapi_types (argo.models.v1alpha1_raw_artifact.V1alpha1RawArtifact (argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest (attribute), 47
 openapi_types (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate (argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest (attribute), 47
 openapi_types (argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy (argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList (attribute), 49
 openapi_types (argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact (argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec (attribute), 50
 openapi_types (argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest (attribute), 50
 openapi_types (argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate (argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest (attribute), 52
 openapi_types (argo.models.v1alpha1_sequence.V1alpha1Sequence (argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent (attribute), 53

[openapi_types \(argo.models.V1alpha1ArchiveStrategy attribute\), 90](#)
[openapi_types \(argo.models.V1alpha1Arguments attribute\), 91](#)
[openapi_types \(argo.models.V1alpha1Artifact attribute\), 91](#)
[openapi_types \(argo.models.V1alpha1ArtifactLocation attribute\), 92](#)
[openapi_types \(argo.models.V1alpha1ArtifactoryArtifact attribute\), 94](#)
[openapi_types \(argo.models.V1alpha1ArtifactoryAuth attribute\), 94](#)
[openapi_types \(argo.models.V1alpha1ArtifactRepositoryRef attribute\), 93](#)
[openapi_types \(argo.models.V1alpha1Backoff attribute\), 95](#)
[openapi_types \(argo.models.V1alpha1ContinueOn attribute\), 95](#)
[openapi_types \(argo.models.V1alpha1Counter attribute\), 96](#)
[openapi_types \(argo.models.V1alpha1CronWorkflow attribute\), 96](#)
[openapi_types \(argo.models.V1alpha1CronWorkflowList attribute\), 97](#)
[openapi_types \(argo.models.V1alpha1CronWorkflowSpec attribute\), 97](#)
[openapi_types \(argo.models.V1alpha1CronWorkflowStatus attribute\), 98](#)
[openapi_types \(argo.models.V1alpha1DAGTask attribute\), 99](#)
[openapi_types \(argo.models.V1alpha1DAGTemplate attribute\), 100](#)
[openapi_types \(argo.models.V1alpha1ExecutorConfig attribute\), 101](#)
[openapi_types \(argo.models.V1alpha1Gauge attribute\), 102](#)
[openapi_types \(argo.models.V1alpha1GCSEArtifact attribute\), 101](#)
[openapi_types \(argo.models.V1alpha1GCSBucket attribute\), 102](#)
[openapi_types \(argo.models.V1alpha1GitArtifact attribute\), 103](#)
[openapi_types \(argo.models.V1alpha1HDFSArtifact attribute\), 104](#)
[openapi_types \(argo.models.V1alpha1HDFSConfig attribute\), 104](#)
[openapi_types \(argo.models.V1alpha1HDFSKrbConfig attribute\), 105](#)
[openapi_types \(argo.models.V1alpha1Histogram attribute\), 106](#)
[openapi_types \(argo.models.V1alpha1HTTPArtifact attribute\), 106](#)
[openapi_types \(argo.models.V1alpha1InfoResponse attribute\), 107](#)
[openapi_types \(argo.models.V1alpha1Inputs attribute\), 107](#)
[openapi_types \(argo.models.V1alpha1Item attribute\), 108](#)
[openapi_types \(argo.models.V1alpha1ItemValue attribute\), 109](#)
[openapi_types \(argo.models.V1alpha1Link attribute\), 110](#)
[openapi_types \(argo.models.V1alpha1LogEntry attribute\), 110](#)
[openapi_types \(argo.models.V1alpha1Metadata attribute\), 111](#)
[openapi_types \(argo.models.V1alpha1MetricLabel attribute\), 111](#)
[openapi_types \(argo.models.V1alpha1Metrics attribute\), 111](#)
[openapi_types \(argo.models.V1alpha1NodeStatus attribute\), 112](#)
[openapi_types \(argo.models.V1alpha1OSSArtifact attribute\), 115](#)
[openapi_types \(argo.models.V1alpha1OSSBucket attribute\), 115](#)
[openapi_types \(argo.models.V1alpha1Outputs attribute\), 116](#)
[openapi_types \(argo.models.V1alpha1Parameter attribute\), 117](#)
[openapi_types \(argo.models.V1alpha1PodGC attribute\), 117](#)
[openapi_types \(argo.models.V1alpha1Prometheus attribute\), 118](#)
[openapi_types \(argo.models.V1alpha1RawArtifact attribute\), 119](#)
[openapi_types \(argo.models.V1alpha1ResourceTemplate attribute\), 119](#)
[openapi_types \(argo.models.V1alpha1RetryStrategy attribute\), 120](#)
[openapi_types \(argo.models.V1alpha1S3Artifact attribute\), 120](#)
[openapi_types \(argo.models.V1alpha1S3Bucket attribute\), 121](#)
[openapi_types \(argo.models.V1alpha1ScriptTemplate attribute\), 122](#)
[openapi_types \(argo.models.V1alpha1Sequence attribute\), 123](#)
[openapi_types \(argo.models.V1alpha1SuspendTemplate attribute\), 123](#)
[openapi_types \(argo.models.V1alpha1Template attribute\), 124](#)
[openapi_types \(argo.models.V1alpha1TemplateRef attribute\), 129](#)
[openapi_types \(argo.models.V1alpha1TTLStrategy attribute\), 124](#)
[openapi_types \(argo.models.V1alpha1UserContainer attribute\), 129](#)

openapi_types (argo.models.V1alpha1ValueFrom attribute), 130
 openapi_types (argo.models.V1alpha1Workflow attribute), 131
 openapi_types (argo.models.V1alpha1WorkflowCondition attribute), 131
 openapi_types (argo.models.V1alpha1WorkflowCreateRequest attribute), 132
 openapi_types (argo.models.V1alpha1WorkflowLintRequest attribute), 133
 openapi_types (argo.models.V1alpha1WorkflowList attribute), 133
 openapi_types (argo.models.V1alpha1WorkflowResubmitRequest attribute), 133
 openapi_types (argo.models.V1alpha1WorkflowResumeRequest attribute), 134
 openapi_types (argo.models.V1alpha1WorkflowRetryRequest attribute), 135
 openapi_types (argo.models.V1alpha1WorkflowSpec attribute), 135
 openapi_types (argo.models.V1alpha1WorkflowStatus attribute), 140
 openapi_types (argo.models.V1alpha1WorkflowStep attribute), 141
 openapi_types (argo.models.V1alpha1WorkflowStopRequest attribute), 143
 openapi_types (argo.models.V1alpha1WorkflowSuspendRequest attribute), 143
 openapi_types (argo.models.V1alpha1WorkflowTemplate attribute), 144
 openapi_types (argo.models.V1alpha1WorkflowTemplateCreateRequest attribute), 144
 openapi_types (argo.models.V1alpha1WorkflowTemplateLintRequest attribute), 145
 openapi_types (argo.models.V1alpha1WorkflowTemplateList attribute), 145
 openapi_types (argo.models.V1alpha1WorkflowTemplateSpec attribute), 146
 openapi_types (argo.models.V1alpha1WorkflowTemplateUpdateRequest attribute), 146
 openapi_types (argo.models.V1alpha1WorkflowTerminateRequest attribute), 147
 openapi_types (argo.models.V1alpha1WorkflowWatchEvent attribute), 147
 optional () (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 8
 optional () (argo.models.V1alpha1Artifact property), 92
 oss () (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9
 oss () (argo.models.V1alpha1ArtifactLocation property), 93
 outbound_nodes () (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 39
 outbound_nodes () (argo.models.V1alpha1NodeStatus property), 113
 outputs () (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 39
 outputs () (argo.models.v1alpha1_template.V1alpha1Template property), 57
 outputs () (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77
 outputs () (argo.models.V1alpha1NodeStatus property), 113
 outputs () (argo.models.V1alpha1Template property), 126
 outputs () (argo.models.V1alpha1WorkflowStatus property), 140
 parallelism () (argo.models.v1alpha1_template.V1alpha1Template property), 57
 parallelism () (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 73
 parallelism () (argo.models.V1alpha1Template property), 126
 parallelism () (argo.models.V1alpha1WorkflowSpec property), 137
 parameter () (argo.models.v1alpha1_value_from.V1alpha1ValueFrom property), 63
 parameter () (argo.models.V1alpha1ValueFrom property), 130
 parameters () (argo.models.v1alpha1_arguments.V1alpha1Arguments property), 7
 parameters () (argo.models.v1alpha1_inputs.V1alpha1Inputs property), 31
 parameters () (argo.models.v1alpha1_outputs.V1alpha1Outputs property), 43
 parameters () (argo.models.V1alpha1Arguments property), 91
 parameters () (argo.models.V1alpha1Inputs property), 107
 parameters () (argo.models.V1alpha1Outputs property), 116
 password () (argo.configuration.Configuration attribute), 148
 password_secret () (argo.models.v1alpha1_artifact_auth.V1alpha1ArtifactAuth property), 12
 password_secret () (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25
 password_secret () (argo.models.V1alpha1ArtifactAuth property), 94
 password_secret () (argo.models.V1alpha1GitArtifact property), 103

path() (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 57
 path() (argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact property), 74
 path() (argo.models.v1alpha1_value_from.V1alpha1ValueFrom property), 127
 path() (argo.models.V1alpha1Artifact property), 92
 path() (argo.models.V1alpha1HDFSArtifact property), 104
 path() (argo.models.V1alpha1ValueFrom property), 130
 persistent_volume_claims() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77
 persistent_volume_claims() (argo.models.V1alpha1WorkflowStatus property), 141
 phase() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 39
 phase() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77
 phase() (argo.models.V1alpha1NodeStatus property), 113
 phase() (argo.models.V1alpha1WorkflowStatus property), 141
 pod_disruption_budget() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 73
 pod_disruption_budget() (argo.models.V1alpha1WorkflowSpec property), 137
 pod_gc() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 73
 pod_gc() (argo.models.V1alpha1WorkflowSpec property), 137
 pod_ip() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40
 pod_ip() (argo.models.V1alpha1NodeStatus property), 114
 pod_name() (argo.models.v1alpha1_log_entry.V1alpha1LogEntry property), 35
 pod_name() (argo.models.V1alpha1LogEntry property), 110
 pod_priority() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
 pod_priority() (argo.models.V1alpha1WorkflowSpec property), 138
 pod_priority_class_name() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
 pod_priority_class_name() (argo.models.V1alpha1WorkflowSpec property), 138
 pod_spec_patch() (argo.models.v1alpha1_template.V1alpha1Template property), 57
 pod_spec_patch() (argo.models.V1alpha1Template property), 127
 pod_spec_patch() (argo.models.V1alpha1WorkflowSpec property), 138
 priority() (argo.models.v1alpha1_template.V1alpha1Template property), 57
 priority() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
 priority() (argo.models.V1alpha1Template property), 127
 priority() (argo.models.V1alpha1WorkflowSpec property), 138
 priority_class_name() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 priority_class_name() (argo.models.V1alpha1Template property), 127
 prometheus() (argo.models.v1alpha1_metrics.V1alpha1Metrics property), 37
 prometheus() (argo.models.V1alpha1Metrics property), 112
 proxy (argo.configuration.Configuration attribute), 149
 providers (argo.configuration.Configuration attribute), 149

R

raw() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9
 raw() (argo.models.V1alpha1ArtifactLocation property), 93
 realtime() (argo.models.v1alpha1_gauge.V1alpha1Gauge property), 22
 realtime() (argo.models.V1alpha1Gauge property), 102
 refresh_api_key_hook (argo.configuration.Configuration attribute), 148
 region() (argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket property), 51
 region() (argo.models.V1alpha1S3Bucket property), 121
 repo() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25
 repo() (argo.models.V1alpha1GitArtifact property), 127
 resource() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 resource() (argo.models.V1alpha1Template property), 127
 resources_duration()

(argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40
 resources_duration() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77
 resources_duration() (argo.models.V1alpha1NodeStatus property), 114
 resources_duration() (argo.models.V1alpha1WorkflowStatus property), 141
 resubmit_pending_pods() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 resubmit_pending_pods() (argo.models.V1alpha1Template property), 127
 result() (argo.models.v1alpha1_outputs.V1alpha1Outputs property), 43
 result() (argo.models.V1alpha1Outputs property), 116
 retries (argo.configuration.Configuration attribute), 149
 retry_policy() (argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy property), 49
 retry_policy() (argo.models.V1alpha1RetryStrategy property), 120
 retry_strategy() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 retry_strategy() (argo.models.V1alpha1Template property), 127
 revision() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25
 revision() (argo.models.V1alpha1GitArtifact property), 103
 role_arn() (argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket property), 51
 role_arn() (argo.models.V1alpha1S3Bucket property), 122
 runtime_resolution() (argo.models.v1alpha1_template_ref.V1alpha1TemplateRef property), 60
 runtime_resolution() (argo.models.V1alpha1TemplateRef property), 129
 s3() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation property), 9
 s3() (argo.models.V1alpha1ArtifactLocation property), 93
 s3_bucket() (argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact property), 50
 s3_bucket() (argo.models.V1alpha1S3Artifact property), 121
 safe_chars_for_path_param (argo.configuration.Configuration attribute), 149
 schedule() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 16
 schedule() (argo.models.V1alpha1CronWorkflowSpec property), 97
 scheduler_name() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 scheduler_name() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
 scheduler_name() (argo.models.V1alpha1Template property), 127
 scheduler_name() (argo.models.V1alpha1WorkflowSpec property), 138
 scope() (argo.models.v1alpha1_link.V1alpha1Link property), 34
 scope() (argo.models.V1alpha1Link property), 110
 script() (argo.models.v1alpha1_template.V1alpha1Template property), 58
 script() (argo.models.V1alpha1Template property), 127
 seconds_after_completion() (argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy property), 61
 seconds_after_completion() (argo.models.V1alpha1TTLStrategy property), 124
 seconds_after_failure() (argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy property), 61
 seconds_after_failure() (argo.models.V1alpha1TTLStrategy property), 124
 seconds_after_success() (argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy property), 61
 seconds_after_success() (argo.models.V1alpha1TTLStrategy property), 124
 secret_key_secret() (argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket property), 42
 secret_key_secret() (argo.models.V1alpha1OSSBucket property), 116
 secret_key_secret() (argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket property), 51
 secret_key_secret() (argo.models.V1alpha1S3Bucket property), 122

S

```

security_context() (argo.models.v1alpha1_template.V1alpha1Template property), 58
security_context() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
security_context() (argo.models.V1alpha1Template property), 128
security_context() (argo.models.V1alpha1WorkflowSpec property), 138
server_dry_run() (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest property), 65
server_dry_run() (argo.models.V1alpha1WorkflowCreateRequest property), 132
service_account_key_secret() (argo.models.v1alpha1_gcs_bucket.V1alpha1GCSBucket property), 24
service_account_key_secret() (argo.models.V1alpha1GCSBucket property), 102
service_account_name() (argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig property), 21
service_account_name() (argo.models.v1alpha1_template.V1alpha1Template property), 58
service_account_name() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
service_account_name() (argo.models.V1alpha1ExecutorConfig property), 101
service_account_name() (argo.models.V1alpha1Template property), 128
service_account_name() (argo.models.V1alpha1WorkflowSpec property), 138
set_default() (argo.configuration.TypeWithDefault method), 148
set_owner_reference() (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate property), 48
set_owner_reference() (argo.models.V1alpha1ResourceTemplate property), 120
shutdown() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 74
shutdown() (argo.models.V1alpha1WorkflowSpec property), 138
sidecars() (argo.models.v1alpha1_template.V1alpha1Template property), 58
sidecars() (argo.models.V1alpha1Template property), 128
source() (argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate property), 52
spec() (argo.models.V1alpha1ScriptTemplate property), 122
spec() (argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow property), 15
spec() (argo.models.v1alpha1_workflow.V1alpha1Workflow property), 64
spec() (argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate property), 82
spec() (argo.models.V1alpha1WorkflowTemplate property), 144
ssh_private_key_secret() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25
ssh_private_key_secret() (argo.models.V1alpha1GitArtifact property), 103
start() (argo.configuration.Configuration attribute), 149
start() (argo.models.v1alpha1_sequence.V1alpha1Sequence property), 53
start() (argo.models.V1alpha1Sequence property), 123
start() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40
started_at() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77
started_at() (argo.models.V1alpha1NodeStatus property), 114
started_at() (argo.models.V1alpha1WorkflowStatus property), 141
starting_deadline_seconds() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 17
starting_deadline_seconds() (argo.models.V1alpha1CronWorkflowSpec property), 98
starting_deadline_seconds() (argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow property), 15
status() (argo.models.v1alpha1_workflow.V1alpha1Workflow property), 64
status() (argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition property), 64
status() (argo.models.V1alpha1CronWorkflow property), 96
status() (argo.models.V1alpha1Workflow property), 131
status() (argo.models.V1alpha1WorkflowCondition property), 131

```

property), 131

steps() (argo.models.v1alpha1_template.V1alpha1Template property), 58

steps() (argo.models.V1alpha1Template property), 128

stored_template_id() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40

stored_template_id() (argo.models.V1alpha1NodeStatus property), 114

stored_templates() (argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus property), 77

stored_templates() (argo.models.V1alpha1WorkflowStatus property), 141

str_val() (argo.models.v1alpha1_item.V1alpha1Item property), 32

str_val() (argo.models.v1alpha1_item_value.V1alpha1ItemValue property), 33

str_val() (argo.models.V1alpha1Item property), 108

str_val() (argo.models.V1alpha1ItemValue property), 109

strategy() (argo.models.v1alpha1_pod_gc.V1alpha1PodGC property), 45

strategy() (argo.models.V1alpha1PodGC property), 117

success_condition() (argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate property), 48

success_condition() (argo.models.V1alpha1ResourceTemplate property), 120

successful_jobs_history_limit() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 17

successful_jobs_history_limit() (argo.models.V1alpha1CronWorkflowSpec property), 98

suspend() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 17

suspend() (argo.models.v1alpha1_template.V1alpha1Template property), 59

suspend() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 75

suspend() (argo.models.V1alpha1CronWorkflowSpec property), 98

suspend() (argo.models.V1alpha1Template property), 128

suspend() (argo.models.V1alpha1WorkflowSpec property), 139

T

tar() (argo.models.v1alpha1_archive_strategy.V1alpha1ArchiveStrategy property), 6

tar() (argo.models.V1alpha1ArchiveStrategy property), 90

target() (argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate property), 21

target() (argo.models.V1alpha1DAGTemplate property), 101

tasks() (argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate property), 21

tasks() (argo.models.V1alpha1DAGTemplate property), 101

temp_folder_path (argo.configuration.Configuration attribute), 148

template() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask property), 19

template() (argo.models.v1alpha1_template.V1alpha1Template property), 59

template() (argo.models.v1alpha1_template_ref.V1alpha1TemplateRef property), 60

template() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep property), 79

template() (argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest property), 83

template() (argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest property), 83

template() (argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest property), 86

template() (argo.models.V1alpha1DAGTask property), 100

template() (argo.models.V1alpha1Template property), 128

template() (argo.models.V1alpha1TemplateRef property), 129

template() (argo.models.V1alpha1WorkflowStep property), 142

template() (argo.models.V1alpha1WorkflowTemplateCreateRequest property), 145

template() (argo.models.V1alpha1WorkflowTemplateLintRequest property), 145

template() (argo.models.V1alpha1WorkflowTemplateUpdateRequest property), 147

template_name() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40

template_name() (argo.models.V1alpha1NodeStatus property), 114

template_ref() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask property), 19

template_ref() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40

template_ref() (argo.models.v1alpha1_template.V1alpha1Template property), 59

template_ref() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep property), 79

property), 79
 template_ref() (argo.models.V1alpha1DAGTask property), 100
 template_ref() (argo.models.V1alpha1NodeStatus property), 114
 template_ref() (argo.models.V1alpha1Template property), 128
 template_ref() (argo.models.V1alpha1WorkflowStep property), 142
 template_scope() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40
 template_scope() (argo.models.V1alpha1NodeStatus property), 114
 templates() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 75
 templates() (argo.models.V1alpha1WorkflowSpec property), 139
 timezone() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec property), 17
 timezone() (argo.models.V1alpha1CronWorkflowSpec property), 98
 to_debug_report() (argo.configuration.Configuration method), 150
 to_dict() (argo.models.cronv1alpha1_create_cron_workflow_request.Cronv1alpha1CreateCronWorkflowRequest method), 2
 to_dict() (argo.models.cronv1alpha1_lint_cron_workflow_request.Cronv1alpha1LintCronWorkflowRequest method), 3
 to_dict() (argo.models.cronv1alpha1_update_cron_workflow_request.Cronv1alpha1UpdateCronWorkflowRequest method), 3
 to_dict() (argo.models.Cronv1alpha1CreateCronWorkflowRequest method), 88
 to_dict() (argo.models.Cronv1alpha1LintCronWorkflowRequest method), 88
 to_dict() (argo.models.Cronv1alpha1UpdateCronWorkflowRequest method), 89
 to_dict() (argo.models.google_protobuf_any.GoogleProtobufAny method), 4
 to_dict() (argo.models.GoogleProtobufAny method), 89
 to_dict() (argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError method), 5
 to_dict() (argo.models.GrpcGatewayRuntimeStreamError method), 90
 to_dict() (argo.models.v1alpha1_archive_strategy.V1alpha1ArchiveStrategy method), 6
 to_dict() (argo.models.v1alpha1_arguments.V1alpha1Arguments method), 7
 to_dict() (argo.models.v1alpha1_artifact.V1alpha1Artifact method), 8
 to_dict() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation method), 10
 to_dict() (argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef method), 10
 to_dict() (argo.models.v1alpha1_artifact.V1alpha1Artifact method), 11
 to_dict() (argo.models.v1alpha1_artifact_auth.V1alpha1ArtifactAuth method), 12
 to_dict() (argo.models.v1alpha1_backoff.V1alpha1Backoff method), 13
 to_dict() (argo.models.v1alpha1_continue_on.V1alpha1ContinueOn method), 13
 to_dict() (argo.models.v1alpha1_counter.V1alpha1Counter method), 13
 to_dict() (argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow method), 15
 to_dict() (argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList method), 15
 to_dict() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec method), 17
 to_dict() (argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus method), 17
 to_dict() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask method), 20
 to_dict() (argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate method), 21
 to_dict() (argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig method), 22
 to_dict() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact method), 25
 to_dict() (argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact method), 26
 to_dict() (argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig method), 27
 to_dict() (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig method), 29
 to_dict() (argo.models.v1alpha1_histogram.V1alpha1Histogram method), 29
 to_dict() (argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact method), 30
 to_dict() (argo.models.v1alpha1_info_response.V1alpha1InfoResponse method), 31
 to_dict() (argo.models.v1alpha1_inputs.V1alpha1Inputs method), 31
 to_dict() (argo.models.v1alpha1_item.V1alpha1Item method), 32
 to_dict() (argo.models.v1alpha1_item_value.V1alpha1ItemValue method), 34
 to_dict() (argo.models.v1alpha1_link.V1alpha1Link method), 34
 to_dict() (argo.models.v1alpha1_log_entry.V1alpha1LogEntry method), 35

`to_dict()` (`argo.models.v1alpha1_metadata.V1alpha1Metadata` method), 36
`to_dict()` (`argo.models.v1alpha1_metric_label.V1alpha1MetricLabel` method), 37
`to_dict()` (`argo.models.v1alpha1_metrics.V1alpha1Metrics` method), 37
`to_dict()` (`argo.models.v1alpha1_node_status.V1alpha1NodeStatus` method), 41
`to_dict()` (`argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact` method), 41
`to_dict()` (`argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket` method), 42
`to_dict()` (`argo.models.v1alpha1_outputs.V1alpha1Outputs` method), 43
`to_dict()` (`argo.models.v1alpha1_parameter.V1alpha1Parameter` method), 44
`to_dict()` (`argo.models.v1alpha1_pod_gc.V1alpha1PodGC` method), 45
`to_dict()` (`argo.models.v1alpha1_prometheus.V1alpha1Prometheus` method), 46
`to_dict()` (`argo.models.v1alpha1_raw_artifact.V1alpha1RawArtifact` method), 47
`to_dict()` (`argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate` method), 48
`to_dict()` (`argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy` method), 49
`to_dict()` (`argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact` method), 50
`to_dict()` (`argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket` method), 51
`to_dict()` (`argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate` method), 52
`to_dict()` (`argo.models.v1alpha1_sequence.V1alpha1Sequence` method), 53
`to_dict()` (`argo.models.v1alpha1_suspend_template.V1alpha1SuspendTemplate` method), 54
`to_dict()` (`argo.models.v1alpha1_template.V1alpha1Template` method), 59
`to_dict()` (`argo.models.v1alpha1_template_ref.V1alpha1TemplateRef` method), 60
`to_dict()` (`argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy` method), 61
`to_dict()` (`argo.models.v1alpha1_user_container.V1alpha1UserContainer` method), 62
`to_dict()` (`argo.models.v1alpha1_value_from.V1alpha1ValueFrom` method), 63
`to_dict()` (`argo.models.v1alpha1_workflow.V1alpha1Workflow` method), 64
`to_dict()` (`argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition` method), 65
`to_dict()` (`argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest` method), 66
`to_dict()` (`argo.models.v1alpha1_workflow_lint_request.V1alpha1WorkflowLintRequest` method), 66
`to_dict()` (`argo.models.v1alpha1_workflow_list.V1alpha1WorkflowList` method), 67
`to_dict()` (`argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest` method), 68
`to_dict()` (`argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest` method), 69
`to_dict()` (`argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest` method), 70
`to_dict()` (`argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec` method), 75
`to_dict()` (`argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus` method), 78
`to_dict()` (`argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep` method), 79
`to_dict()` (`argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest` method), 80
`to_dict()` (`argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest` method), 81
`to_dict()` (`argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate` method), 82
`to_dict()` (`argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest` method), 83
`to_dict()` (`argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList` method), 84
`to_dict()` (`argo.models.v1alpha1_workflow_template_lint_request.V1alpha1WorkflowTemplateLintRequest` method), 84
`to_dict()` (`argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec` method), 85
`to_dict()` (`argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest` method), 86
`to_dict()` (`argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest` method), 86
`to_dict()` (`argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent` method), 87
`to_dict()` (`argo.models.V1alpha1ArchiveStrategy` method), 90
`to_dict()` (`argo.models.V1alpha1Arguments` method), 91
`to_dict()` (`argo.models.V1alpha1Artifact` method), 92
`to_dict()` (`argo.models.V1alpha1ArtifactLocation` method), 93
`to_dict()` (`argo.models.V1alpha1ArtifactRepositoryRef` method), 94
`to_dict()` (`argo.models.V1alpha1ArtifactRepositoryAuth` method), 95
`to_dict()` (`argo.models.V1alpha1Backoff` method), 95
`to_dict()` (`argo.models.V1alpha1ContinueOnFailure` method), 96
`to_dict()` (`argo.models.V1alpha1Counter` method), 96
`to_dict()` (`argo.models.V1alpha1CronWorkflow` method), 96

`method`), 96
`to_dict()` (`argo.models.V1alpha1CronWorkflowList` `method`), 97
`to_dict()` (`argo.models.V1alpha1CronWorkflowSpec` `method`), 98
`to_dict()` (`argo.models.V1alpha1CronWorkflowStatus` `method`), 99
`to_dict()` (`argo.models.V1alpha1DAGTask` `method`), 100
`to_dict()` (`argo.models.V1alpha1DAGTemplate` `method`), 101
`to_dict()` (`argo.models.V1alpha1ExecutorConfig` `method`), 101
`to_dict()` (`argo.models.V1alpha1Gauge` `method`), 102
`to_dict()` (`argo.models.V1alpha1GCSArtifact` `method`), 102
`to_dict()` (`argo.models.V1alpha1GCSBucket` `method`), 102
`to_dict()` (`argo.models.V1alpha1GitArtifact` `method`), 104
`to_dict()` (`argo.models.V1alpha1HDFSArtifact` `method`), 104
`to_dict()` (`argo.models.V1alpha1HDFSConfig` `method`), 105
`to_dict()` (`argo.models.V1alpha1HDFSKrbConfig` `method`), 106
`to_dict()` (`argo.models.V1alpha1Histogram` `method`), 107
`to_dict()` (`argo.models.V1alpha1HTTPArtifact` `method`), 106
`to_dict()` (`argo.models.V1alpha1InfoResponse` `method`), 107
`to_dict()` (`argo.models.V1alpha1Inputs` `method`), 108
`to_dict()` (`argo.models.V1alpha1Item` `method`), 108
`to_dict()` (`argo.models.V1alpha1ItemValue` `method`), 109
`to_dict()` (`argo.models.V1alpha1Link` `method`), 110
`to_dict()` (`argo.models.V1alpha1LogEntry` `method`), 110
`to_dict()` (`argo.models.V1alpha1Metadata` `method`), 111
`to_dict()` (`argo.models.V1alpha1MetricLabel` `method`), 111
`to_dict()` (`argo.models.V1alpha1Metrics` `method`), 112
`to_dict()` (`argo.models.V1alpha1NodeStatus` `method`), 115
`to_dict()` (`argo.models.V1alpha1OSSArtifact` `method`), 115
`to_dict()` (`argo.models.V1alpha1OSSBucket` `method`), 116
`to_dict()` (`argo.models.V1alpha1Outputs` `method`), 116
`to_dict()` (`argo.models.V1alpha1Parameter` `method`), 117
`to_dict()` (`argo.models.V1alpha1PodGC` `method`), 117
`to_dict()` (`argo.models.V1alpha1Prometheus` `method`), 118
`to_dict()` (`argo.models.V1alpha1RawArtifact` `method`), 119
`to_dict()` (`argo.models.V1alpha1ResourceTemplate` `method`), 120
`to_dict()` (`argo.models.V1alpha1RetryStrategy` `method`), 120
`to_dict()` (`argo.models.V1alpha1S3Artifact` `method`), 121
`to_dict()` (`argo.models.V1alpha1S3Bucket` `method`), 122
`to_dict()` (`argo.models.V1alpha1ScriptTemplate` `method`), 122
`to_dict()` (`argo.models.V1alpha1Sequence` `method`), 123
`to_dict()` (`argo.models.V1alpha1SuspendTemplate` `method`), 123
`to_dict()` (`argo.models.V1alpha1Template` `method`), 128
`to_dict()` (`argo.models.V1alpha1TemplateRef` `method`), 129
`to_dict()` (`argo.models.V1alpha1TTLStrategy` `method`), 124
`to_dict()` (`argo.models.V1alpha1UserContainer` `method`), 130
`to_dict()` (`argo.models.V1alpha1ValueFrom` `method`), 130
`to_dict()` (`argo.models.V1alpha1Workflow` `method`), 131
`to_dict()` (`argo.models.V1alpha1WorkflowCondition` `method`), 132
`to_dict()` (`argo.models.V1alpha1WorkflowCreateRequest` `method`), 132
`to_dict()` (`argo.models.V1alpha1WorkflowLintRequest` `method`), 133
`to_dict()` (`argo.models.V1alpha1WorkflowList` `method`), 133
`to_dict()` (`argo.models.V1alpha1WorkflowResubmitRequest` `method`), 134
`to_dict()` (`argo.models.V1alpha1WorkflowResumeRequest` `method`), 134
`to_dict()` (`argo.models.V1alpha1WorkflowRetryRequest` `method`), 135
`to_dict()` (`argo.models.V1alpha1WorkflowSpec` `method`), 139
`to_dict()` (`argo.models.V1alpha1WorkflowStatus` `method`), 141
`to_dict()` (`argo.models.V1alpha1WorkflowStep` `method`), 143

```

to_dict() (argo.models.V1alpha1WorkflowStopRequest to_str() (argo.models.v1alpha1_backoff.V1alpha1Backoff
    method), 143                                method), 13
to_dict() (argo.models.V1alpha1WorkflowSuspendRequest to_str() (argo.models.v1alpha1_continue_on.V1alpha1ContinueOn
    method), 144                                method), 13
to_dict() (argo.models.V1alpha1WorkflowTemplate to_str() (argo.models.v1alpha1_counter.V1alpha1Counter
    method), 144                                method), 14
to_dict() (argo.models.V1alpha1WorkflowTemplateCreateRequest to_str() (argo.models.v1alpha1_cron_workflow.V1alpha1CronWorkflow
    method), 145                                method), 15
to_dict() (argo.models.V1alpha1WorkflowTemplateLintRequest to_str() (argo.models.v1alpha1_cron_workflow_list.V1alpha1CronWorkflowList
    method), 145                                method), 15
to_dict() (argo.models.V1alpha1WorkflowTemplateList to_str() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec
    method), 146                                method), 17
to_dict() (argo.models.V1alpha1WorkflowTemplateSpec to_str() (argo.models.v1alpha1_cron_workflow_status.V1alpha1CronWorkflowStatus
    method), 146                                method), 18
to_dict() (argo.models.V1alpha1WorkflowTemplateUpdateRequest to_str() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask
    method), 147                                method), 20
to_dict() (argo.models.V1alpha1WorkflowTerminateRequest to_str() (argo.models.v1alpha1_dag_template.V1alpha1DAGTemplate
    method), 147                                method), 21
to_dict() (argo.models.V1alpha1WorkflowWatchEvent to_str() (argo.models.v1alpha1_executor_config.V1alpha1ExecutorConfig
    method), 147                                method), 22
to_str() (argo.models.cronv1alpha1_create_cron_workflow_request.CronV1alpha1CreateCronWorkflowRequest, V1alpha1GCSArtifact
    method), 2                                method), 22
to_str() (argo.models.cronv1alpha1_lint_cron_workflow_request.CronV1alpha1LintCronWorkflowRequest, V1alpha1GCSArtifact
    method), 3                                method), 23
to_str() (argo.models.cronv1alpha1_update_cron_workflow_request.CronV1alpha1UpdateCronWorkflowRequest, V1alpha1GCSBucket
    method), 3                                method), 24
to_str() (argo.models.CronV1alpha1CreateCronWorkflowRequest to_str() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact
    method), 88                                method), 25
to_str() (argo.models.CronV1alpha1LintCronWorkflowRequest to_str() (argo.models.v1alpha1_hdfs_artifact.V1alpha1HDFSArtifact
    method), 88                                method), 26
to_str() (argo.models.CronV1alpha1UpdateCronWorkflowRequest to_str() (argo.models.v1alpha1_hdfs_config.V1alpha1HDFSConfig
    method), 89                                method), 27
to_str() (argo.models.google_protobuf_any.GoogleProtobufAny to_str() (argo.models.v1alpha1_hdfs_krb_config.V1alpha1HDFSkrbConfig
    method), 4                                method), 29
to_str() (argo.models.GoogleProtobufAny method), to_str() (argo.models.v1alpha1_histogram.V1alpha1Histogram
    89                                method), 29
to_str() (argo.models.grpc_gateway_runtime_stream_error.GrpcGatewayRuntimeStreamError to_str() (argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact
    method), 5                                method), 30
to_str() (argo.models.GrpcGatewayRuntimeStreamError to_str() (argo.models.v1alpha1_info_response.V1alpha1InfoResponse
    method), 90                                method), 31
to_str() (argo.models.v1alpha1_archive_strategy.V1alpha1ArchiveStrategy to_str() (argo.models.v1alpha1_inputs.V1alpha1Inputs
    method), 6                                method), 31
to_str() (argo.models.v1alpha1_arguments.V1alpha1Arguments to_str() (argo.models.v1alpha1_item.V1alpha1Item
    method), 7                                method), 33
to_str() (argo.models.v1alpha1_artifact.V1alpha1Artifact to_str() (argo.models.v1alpha1_item_value.V1alpha1ItemValue
    method), 8                                method), 34
to_str() (argo.models.v1alpha1_artifact_location.V1alpha1ArtifactLocation to_str() (argo.models.v1alpha1_link.V1alpha1Link
    method), 10                                method), 34
to_str() (argo.models.v1alpha1_artifact_repository_ref.V1alpha1ArtifactRepositoryRef to_str() (argo.models.v1alpha1_log_entry.V1alpha1LogEntry
    method), 10                                method), 35
to_str() (argo.models.v1alpha1_artifactory_artifact.V1alpha1ArtifactoryArtifact to_str() (argo.models.v1alpha1_metadata.V1alpha1Metadata
    method), 11                                method), 36
to_str() (argo.models.v1alpha1_artifactory_auth.V1alpha1ArtifactoryAuth to_str() (argo.models.v1alpha1_metric_label.V1alpha1MetricLabel
    method), 12                                method), 37

```

<code>to_str()</code> (<code>argo.models.v1alpha1_metrics.V1alpha1Metric</code> method), 37	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_resume_request.V1alpha1WorkflowResumeRequest</code> method), 69
<code>to_str()</code> (<code>argo.models.v1alpha1_node_status.V1alpha1NodeStatus</code> method), 41	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_retry_request.V1alpha1WorkflowRetryRequest</code> method), 70
<code>to_str()</code> (<code>argo.models.v1alpha1_oss_artifact.V1alpha1OSSArtifact</code> method), 41	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec</code> method), 75
<code>to_str()</code> (<code>argo.models.v1alpha1_oss_bucket.V1alpha1OSSBucket</code> method), 42	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_status.V1alpha1WorkflowStatus</code> method), 78
<code>to_str()</code> (<code>argo.models.v1alpha1_outputs.V1alpha1Outputs</code> method), 43	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep</code> method), 79
<code>to_str()</code> (<code>argo.models.v1alpha1_parameter.V1alpha1Parameter</code> method), 44	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_stop_request.V1alpha1WorkflowStopRequest</code> method), 80
<code>to_str()</code> (<code>argo.models.v1alpha1_pod_gc.V1alpha1PodGC</code> method), 45	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_suspend_request.V1alpha1WorkflowSuspendRequest</code> method), 81
<code>to_str()</code> (<code>argo.models.v1alpha1_prometheus.V1alpha1Prometheus</code> method), 46	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_template.V1alpha1WorkflowTemplate</code> method), 82
<code>to_str()</code> (<code>argo.models.v1alpha1_raw_artifact.V1alpha1RawArtifact</code> method), 47	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_template_create_request.V1alpha1WorkflowTemplateCreateRequest</code> method), 83
<code>to_str()</code> (<code>argo.models.v1alpha1_resource_template.V1alpha1ResourceTemplate</code> method), 48	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_template_list.V1alpha1WorkflowTemplateList</code> method), 84
<code>to_str()</code> (<code>argo.models.v1alpha1_retry_strategy.V1alpha1RetryStrategy</code> method), 49	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec</code> method), 85
<code>to_str()</code> (<code>argo.models.v1alpha1_s3_artifact.V1alpha1S3Artifact</code> method), 50	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_template_update_request.V1alpha1WorkflowTemplateUpdateRequest</code> method), 86
<code>to_str()</code> (<code>argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket</code> method), 51	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_terminate_request.V1alpha1WorkflowTerminateRequest</code> method), 87
<code>to_str()</code> (<code>argo.models.v1alpha1_script_template.V1alpha1ScriptTemplate</code> method), 52	<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent</code> method), 87
<code>to_str()</code> (<code>argo.models.v1alpha1_sequence.V1alpha1Sequence</code> method), 53	<code>to_str()</code> (<code>argo.models.V1alpha1ArchiveStrategy</code> method), 90
<code>to_str()</code> (<code>argo.models.v1alpha1_suspend_template.V1alpha1SuspendTemplate</code> method), 54	<code>to_str()</code> (<code>argo.models.V1alpha1Arguments</code> method), 91
<code>to_str()</code> (<code>argo.models.v1alpha1_template.V1alpha1Template</code> method), 59	<code>to_str()</code> (<code>argo.models.V1alpha1Artifact</code> method), 92
<code>to_str()</code> (<code>argo.models.v1alpha1_template_ref.V1alpha1TemplateRef</code> method), 60	<code>to_str()</code> (<code>argo.models.V1alpha1ArtifactLocation</code> method), 93
<code>to_str()</code> (<code>argo.models.v1alpha1_ttl_strategy.V1alpha1TTLStrategy</code> method), 61	<code>to_str()</code> (<code>argo.models.V1alpha1ArtifactoryArtifact</code> method), 94
<code>to_str()</code> (<code>argo.models.v1alpha1_user_container.V1alpha1UserContainer</code> method), 62	<code>to_str()</code> (<code>argo.models.V1alpha1ArtifactoryAuth</code> method), 95
<code>to_str()</code> (<code>argo.models.v1alpha1_value_from.V1alpha1ValueFrom</code> method), 63	<code>to_str()</code> (<code>argo.models.V1alpha1ArtifactRepositoryRef</code> method), 96
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow.V1alpha1Workflow</code> method), 64	<code>to_str()</code> (<code>argo.models.V1alpha1Backoff</code> method), 95
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition</code> method), 65	<code>to_str()</code> (<code>argo.models.V1alpha1ContinueOnFailure</code> method), 96
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest</code> method), 66	<code>to_str()</code> (<code>argo.models.V1alpha1CronWorkflow</code> method), 97
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_lint_request.V1alpha1WorkflowLintRequest</code> method), 66	<code>to_str()</code> (<code>argo.models.V1alpha1CronWorkflowList</code> method), 97
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_list.V1alpha1WorkflowList</code> method), 67	<code>to_str()</code> (<code>argo.models.V1alpha1CronWorkflowSpec</code> method), 98
<code>to_str()</code> (<code>argo.models.v1alpha1_workflow_resubmit_request.V1alpha1WorkflowResubmitRequest</code> method), 68	<code>to_str()</code> (<code>argo.models.V1alpha1CronWorkflowStatus</code> method), 99

`method)`, 99
`to_str()` (*argo.models.V1alpha1DAGTask method*), 100
`to_str()` (*argo.models.V1alpha1DAGTemplate method*), 101
`to_str()` (*argo.models.V1alpha1ExecutorConfig method*), 101
`to_str()` (*argo.models.V1alpha1Gauge method*), 103
`to_str()` (*argo.models.V1alpha1GCSArtifact method*), 102
`to_str()` (*argo.models.V1alpha1GCSBucket method*), 102
`to_str()` (*argo.models.V1alpha1GitArtifact method*), 104
`to_str()` (*argo.models.V1alpha1HDFSArtifact method*), 104
`to_str()` (*argo.models.V1alpha1HDFSConfig method*), 105
`to_str()` (*argo.models.V1alpha1HDFSKrbConfig method*), 106
`to_str()` (*argo.models.V1alpha1Histogram method*), 107
`to_str()` (*argo.models.V1alpha1HTTPArtifact method*), 106
`to_str()` (*argo.models.V1alpha1InfoResponse method*), 107
`to_str()` (*argo.models.V1alpha1Inputs method*), 108
`to_str()` (*argo.models.V1alpha1Item method*), 108
`to_str()` (*argo.models.V1alpha1ItemValue method*), 109
`to_str()` (*argo.models.V1alpha1Link method*), 110
`to_str()` (*argo.models.V1alpha1LogEntry method*), 110
`to_str()` (*argo.models.V1alpha1Metadata method*), 111
`to_str()` (*argo.models.V1alpha1MetricLabel method*), 111
`to_str()` (*argo.models.V1alpha1Metrics method*), 112
`to_str()` (*argo.models.V1alpha1NodeStatus method*), 115
`to_str()` (*argo.models.V1alpha1OSSArtifact method*), 115
`to_str()` (*argo.models.V1alpha1OSSBucket method*), 116
`to_str()` (*argo.models.V1alpha1Outputs method*), 116
`to_str()` (*argo.models.V1alpha1Parameter method*), 117
`to_str()` (*argo.models.V1alpha1PodGC method*), 117
`to_str()` (*argo.models.V1alpha1Prometheus method*), 118
`to_str()` (*argo.models.V1alpha1RawArtifact method*), 119
`to_str()` (*argo.models.V1alpha1ResourceTemplate method*), 120
`to_str()` (*argo.models.V1alpha1RetryStrategy method*), 120
`to_str()` (*argo.models.V1alpha1S3Artifact method*), 121
`to_str()` (*argo.models.V1alpha1S3Bucket method*), 122
`to_str()` (*argo.models.V1alpha1ScriptTemplate method*), 122
`to_str()` (*argo.models.V1alpha1Sequence method*), 123
`to_str()` (*argo.models.V1alpha1SuspendTemplate method*), 123
`to_str()` (*argo.models.V1alpha1Template method*), 129
`to_str()` (*argo.models.V1alpha1TemplateRef method*), 129
`to_str()` (*argo.models.V1alpha1TTLStrategy method*), 124
`to_str()` (*argo.models.V1alpha1UserContainer method*), 130
`to_str()` (*argo.models.V1alpha1ValueFrom method*), 130
`to_str()` (*argo.models.V1alpha1Workflow method*), 131
`to_str()` (*argo.models.V1alpha1WorkflowCondition method*), 132
`to_str()` (*argo.models.V1alpha1WorkflowCreateRequest method*), 132
`to_str()` (*argo.models.V1alpha1WorkflowLintRequest method*), 133
`to_str()` (*argo.models.V1alpha1WorkflowList method*), 133
`to_str()` (*argo.models.V1alpha1WorkflowResubmitRequest method*), 134
`to_str()` (*argo.models.V1alpha1WorkflowResumeRequest method*), 134
`to_str()` (*argo.models.V1alpha1WorkflowRetryRequest method*), 135
`to_str()` (*argo.models.V1alpha1WorkflowSpec method*), 139
`to_str()` (*argo.models.V1alpha1WorkflowStatus method*), 141
`to_str()` (*argo.models.V1alpha1WorkflowStep method*), 143
`to_str()` (*argo.models.V1alpha1WorkflowStopRequest method*), 143
`to_str()` (*argo.models.V1alpha1WorkflowSuspendRequest method*), 144
`to_str()` (*argo.models.V1alpha1WorkflowTemplate method*), 144
`to_str()` (*argo.models.V1alpha1WorkflowTemplateCreateRequest method*), 145
`to_str()` (*argo.models.V1alpha1WorkflowTemplateLintRequest*

method), 145

to_str() (argo.models.V1alpha1WorkflowTemplateList method), 146

to_str() (argo.models.V1alpha1WorkflowTemplateSpec method), 146

to_str() (argo.models.V1alpha1WorkflowTemplateUpdateRequest method), 147

to_str() (argo.models.V1alpha1WorkflowTerminateRequest method), 147

to_str() (argo.models.V1alpha1WorkflowWatchEvent method), 148

tolerations() (argo.models.v1alpha1_template.V1alpha1Template property), 59

tolerations() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 75

tolerations() (argo.models.V1alpha1Template property), 128

tolerations() (argo.models.V1alpha1WorkflowSpec property), 139

ttl_seconds_after_finished() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 75

ttl_seconds_after_finished() (argo.models.V1alpha1WorkflowSpec property), 139

ttl_strategy() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec property), 75

ttl_strategy() (argo.models.V1alpha1WorkflowSpec property), 139

type() (argo.models.v1alpha1_item.V1alpha1Item property), 32

type() (argo.models.v1alpha1_item_value.V1alpha1ItemValue property), 34

type() (argo.models.v1alpha1_node_status.V1alpha1NodeStatus property), 40

type() (argo.models.v1alpha1_workflow_condition.V1alpha1WorkflowCondition property), 64

type() (argo.models.v1alpha1_workflow_watch_event.V1alpha1WorkflowWatchEvent property), 87

type() (argo.models.V1alpha1Item property), 108

type() (argo.models.V1alpha1ItemValue property), 109

type() (argo.models.V1alpha1NodeStatus property), 114

type() (argo.models.V1alpha1WorkflowCondition property), 131

type() (argo.models.V1alpha1WorkflowWatchEvent property), 147

type_url() (argo.models.google_protobuf_any.GoogleProtobufAny property), 4

type_url() (argo.models.GoogleProtobufAny property), 89

TypeWithDefault (class in argo.configuration), 148

U

url() (argo.models.v1alpha1_artifact.V1alpha1Artifact property), 11

url() (argo.models.v1alpha1_http_artifact.V1alpha1HTTPArtifact property), 30

url() (argo.models.v1alpha1_link.V1alpha1Link property), 34

url() (argo.models.V1alpha1Artifact property), 94

url() (argo.models.V1alpha1HTTPArtifact property), 106

url() (argo.models.V1alpha1Link property), 110

use_sdk_creds() (argo.models.v1alpha1_s3_bucket.V1alpha1S3Bucket property), 31

use_sdk_creds() (argo.models.V1alpha1S3Bucket property), 122

username (argo.configuration.Configuration attribute), 148

username_secret() (argo.models.v1alpha1_artifact_auth.V1alpha1ArtifactAuth property), 12

username_secret() (argo.models.v1alpha1_git_artifact.V1alpha1GitArtifact property), 25

username_secret() (argo.models.V1alpha1ArtifactAuth property), 94

username_secret() (argo.models.V1alpha1GitArtifact property), 104

V1alpha1ArchiveStrategy (class in argo.models), 90

V1alpha1ArchiveStrategy (class in argo.models.v1alpha1_archive_strategy), 6

V1alpha1Arguments (class in argo.models), 90

V1alpha1Arguments (class in argo.models.v1alpha1_arguments), 6

V1alpha1Artifact (class in argo.models), 91

V1alpha1Artifact (class in argo.models.v1alpha1_artifact), 7

V1alpha1ArtifactLocation (class in argo.models), 92

V1alpha1ArtifactLocation (class in argo.models.v1alpha1_artifact_location), 8

V1alpha1ArtifactFactoryArtifact (class in argo.models), 94

V1alpha1ArtifactFactoryArtifact (class in argo.models.v1alpha1_artifact_factory_artifact), 11

V1alpha1ArtifactFactoryAuth (class in argo.models), 94

Vlalpha1ArtifactoryAuth (class in <i>argo.models.vlalpha1_artifactory_auth</i>), 12	in	Vlalpha1GitArtifact (class in <i>argo.models</i>), 103
Vlalpha1ArtifactRepositoryRef (class in <i>argo.models</i>), 93	in	Vlalpha1GitArtifact (class in <i>argo.models.vlalpha1_git_artifact</i>), 24
Vlalpha1ArtifactRepositoryRef (class in <i>argo.models.vlalpha1_artifact_repository_ref</i>), 10	in	Vlalpha1HDFSArtifact (class in <i>argo.models</i>), 104
Vlalpha1Backoff (class in <i>argo.models</i>), 95	in	Vlalpha1HDFSArtifact (class in <i>argo.models.vlalpha1_hdfs_artifact</i>), 26
Vlalpha1Backoff (class in <i>argo.models.vlalpha1_backoff</i>), 12	in	Vlalpha1HDFSConfig (class in <i>argo.models</i>), 104
Vlalpha1ContinueOn (class in <i>argo.models</i>), 95	in	Vlalpha1HDFSConfig (class in <i>argo.models.vlalpha1_hdfs_config</i>), 27
Vlalpha1ContinueOn (class in <i>argo.models.vlalpha1_continue_on</i>), 13	in	Vlalpha1HDFSConfig (class in <i>argo.models.vlalpha1_hdfs_krb_config</i>), 105
Vlalpha1Counter (class in <i>argo.models</i>), 96	in	Vlalpha1HDFSConfig (class in <i>argo.models.vlalpha1_hdfs_krb_config</i>), 28
Vlalpha1Counter (class in <i>argo.models.vlalpha1_counter</i>), 14	in	Vlalpha1Histogram (class in <i>argo.models</i>), 106
Vlalpha1CronWorkflow (class in <i>argo.models</i>), 96	in	Vlalpha1Histogram (class in <i>argo.models.vlalpha1_histogram</i>), 29
Vlalpha1CronWorkflow (class in <i>argo.models.vlalpha1_cron_workflow</i>), 14	in	Vlalpha1HTTPArtifact (class in <i>argo.models</i>), 106
Vlalpha1CronWorkflowList (class in <i>argo.models</i>), 97	in	Vlalpha1HTTPArtifact (class in <i>argo.models.vlalpha1_http_artifact</i>), 30
Vlalpha1CronWorkflowList (class in <i>argo.models.vlalpha1_cron_workflow_list</i>), 15	in	Vlalpha1InfoResponse (class in <i>argo.models</i>), 107
Vlalpha1CronWorkflowSpec (class in <i>argo.models</i>), 97	in	Vlalpha1InfoResponse (class in <i>argo.models.vlalpha1_info_response</i>), 30
Vlalpha1CronWorkflowSpec (class in <i>argo.models.vlalpha1_cron_workflow_spec</i>), 16	in	Vlalpha1Inputs (class in <i>argo.models</i>), 107
Vlalpha1CronWorkflowStatus (class in <i>argo.models</i>), 98	in	Vlalpha1Inputs (class in <i>argo.models.vlalpha1_inputs</i>), 31
Vlalpha1CronWorkflowStatus (class in <i>argo.models.vlalpha1_cron_workflow_status</i>), 18	in	Vlalpha1Item (class in <i>argo.models</i>), 108
Vlalpha1DAGTask (class in <i>argo.models</i>), 99	in	Vlalpha1Item (class in <i>argo.models.vlalpha1_item</i>), 32
Vlalpha1DAGTask (class in <i>argo.models.vlalpha1_dag_task</i>), 19	in	Vlalpha1ItemValue (class in <i>argo.models</i>), 109
Vlalpha1DAGTemplate (class in <i>argo.models</i>), 100	in	Vlalpha1ItemValue (class in <i>argo.models.vlalpha1_item_value</i>), 33
Vlalpha1DAGTemplate (class in <i>argo.models.vlalpha1_dag_template</i>), 21	in	Vlalpha1Link (class in <i>argo.models</i>), 109
Vlalpha1ExecutorConfig (class in <i>argo.models</i>), 101	in	Vlalpha1Link (class in <i>argo.models.vlalpha1_link</i>), 34
Vlalpha1ExecutorConfig (class in <i>argo.models.vlalpha1_executor_config</i>), 21	in	Vlalpha1LogEntry (class in <i>argo.models</i>), 110
Vlalpha1Gauge (class in <i>argo.models</i>), 102	in	Vlalpha1LogEntry (class in <i>argo.models.vlalpha1_log_entry</i>), 35
Vlalpha1Gauge (class in <i>argo.models.vlalpha1_gauge</i>), 22	in	Vlalpha1Metadata (class in <i>argo.models</i>), 110
Vlalpha1GCSArtifact (class in <i>argo.models</i>), 101	in	Vlalpha1Metadata (class in <i>argo.models.vlalpha1_metadata</i>), 36
Vlalpha1GCSArtifact (class in <i>argo.models.vlalpha1_gcs_artifact</i>), 23	in	Vlalpha1MetricLabel (class in <i>argo.models</i>), 111
Vlalpha1GCSBucket (class in <i>argo.models</i>), 102	in	Vlalpha1MetricLabel (class in <i>argo.models.vlalpha1_metric_label</i>), 36
Vlalpha1GCSBucket (class in <i>argo.models.vlalpha1_gcs_bucket</i>), 24	in	Vlalpha1Metrics (class in <i>argo.models</i>), 111
		Vlalpha1Metrics (class in <i>argo.models.vlalpha1_metrics</i>), 37
		Vlalpha1NodeStatus (class in <i>argo.models</i>), 112
		Vlalpha1NodeStatus (class in <i>argo.models.vlalpha1_node_status</i>), 38
		Vlalpha1OSSArtifact (class in <i>argo.models</i>), 115
		Vlalpha1OSSArtifact (class in <i>argo.models.vlalpha1_oss_artifact</i>), 41
		Vlalpha1OSSBucket (class in <i>argo.models</i>), 115

V1alpha1OSSBucket	(class	in	V1alpha1UserContainer	(class in argo.models),
	argo.models.v1alpha1_oss_bucket), 42		129	
V1alpha1Outputs	(class in argo.models), 116		V1alpha1UserContainer	(class in
V1alpha1Outputs	(class	in	argo.models.v1alpha1_user_container), 62	
	argo.models.v1alpha1_outputs), 43		V1alpha1ValueFrom	(class in argo.models), 130
V1alpha1Parameter	(class in argo.models), 116		V1alpha1ValueFrom	(class in
V1alpha1Parameter	(class	in	argo.models.v1alpha1_value_from), 62	
	argo.models.v1alpha1_parameter), 44		V1alpha1Workflow	(class in argo.models), 130
V1alpha1PodGC	(class in argo.models), 117		V1alpha1Workflow	(class in
V1alpha1PodGC	(class	in	argo.models.v1alpha1_workflow), 63	
	argo.models.v1alpha1_pod_gc), 45		V1alpha1WorkflowCondition	(class in
V1alpha1Prometheus	(class in argo.models), 118		argo.models), 131	
V1alpha1Prometheus	(class	in	V1alpha1WorkflowCondition	(class in
	argo.models.v1alpha1_prometheus), 45		argo.models.v1alpha1_workflow_condition),	
V1alpha1RawArtifact	(class in argo.models), 119		64	
V1alpha1RawArtifact	(class	in	V1alpha1WorkflowCreateRequest	(class in
	argo.models.v1alpha1_raw_artifact), 47		argo.models), 132	
V1alpha1ResourceTemplate	(class	in	V1alpha1WorkflowCreateRequest	(class in
	argo.models), 119		argo.models.v1alpha1_workflow_create_request),	
V1alpha1ResourceTemplate	(class	in	65	
	argo.models.v1alpha1_resource_template),		V1alpha1WorkflowLintRequest	(class in
	47		argo.models), 132	
V1alpha1RetryStrategy	(class in argo.models),		V1alpha1WorkflowLintRequest	(class in
	120		argo.models.v1alpha1_workflow_lint_request),	
V1alpha1RetryStrategy	(class	in	66	
	argo.models.v1alpha1_retry_strategy), 49		V1alpha1WorkflowList	(class in argo.models), 133
V1alpha1S3Artifact	(class in argo.models), 120		V1alpha1WorkflowList	(class in
V1alpha1S3Artifact	(class	in	argo.models.v1alpha1_workflow_list), 67	
	argo.models.v1alpha1_s3_artifact), 50		V1alpha1WorkflowResubmitRequest	(class in
V1alpha1S3Bucket	(class in argo.models), 121		argo.models), 133	
V1alpha1S3Bucket	(class	in	V1alpha1WorkflowResubmitRequest	(class in
	argo.models.v1alpha1_s3_bucket), 50		argo.models.v1alpha1_workflow_resubmit_request),	
V1alpha1ScriptTemplate	(class in argo.models),		68	
	122		V1alpha1WorkflowResumeRequest	(class in
V1alpha1ScriptTemplate	(class	in	argo.models), 134	
	argo.models.v1alpha1_script_template),		V1alpha1WorkflowResumeRequest	(class in
	52		argo.models.v1alpha1_workflow_resume_request),	
V1alpha1Sequence	(class in argo.models), 122		69	
V1alpha1Sequence	(class	in	V1alpha1WorkflowRetryRequest	(class in
	argo.models.v1alpha1_sequence), 53		argo.models), 134	
V1alpha1SuspendTemplate	(class	in	V1alpha1WorkflowRetryRequest	(class in
	argo.models), 123		argo.models.v1alpha1_workflow_retry_request),	
V1alpha1SuspendTemplate	(class	in	70	
	argo.models.v1alpha1_suspend_template),		V1alpha1WorkflowSpec	(class in argo.models), 135
	54		V1alpha1WorkflowSpec	(class in
V1alpha1Template	(class in argo.models), 124		argo.models.v1alpha1_workflow_spec), 71	
V1alpha1Template	(class	in	V1alpha1WorkflowStatus	(class in argo.models),
	argo.models.v1alpha1_template), 55		139	
V1alpha1TemplateRef	(class in argo.models), 129		V1alpha1WorkflowStatus	(class in
V1alpha1TemplateRef	(class	in	argo.models.v1alpha1_workflow_status),	
	argo.models.v1alpha1_template_ref), 60		76	
V1alpha1TTLStrategy	(class in argo.models), 123		V1alpha1WorkflowStep	(class in argo.models), 141
V1alpha1TTLStrategy	(class	in	V1alpha1WorkflowStep	(class in
	argo.models.v1alpha1_ttl_strategy), 61		argo.models.v1alpha1_workflow_step), 78	

V1alpha1WorkflowStopRequest	(class in	property), 14
argo.models), 143		value() (argo.models.v1alpha1_gauge.V1alpha1Gauge
V1alpha1WorkflowStopRequest	(class in	property), 22
argo.models.v1alpha1_workflow_stop_request),	value()	(argo.models.v1alpha1_histogram.V1alpha1Histogram
80		property), 29
V1alpha1WorkflowSuspendRequest	(class in	value() (argo.models.v1alpha1_metric_label.V1alpha1MetricLabel
argo.models), 143		property), 36
V1alpha1WorkflowSuspendRequest	(class in	value() (argo.models.v1alpha1_parameter.V1alpha1Parameter
argo.models.v1alpha1_workflow_suspend_request),	property), 44	
81		value() (argo.models.V1alpha1Counter property), 96
V1alpha1WorkflowTemplate	(class in	value() (argo.models.V1alpha1Gauge property), 102
argo.models), 144		value() (argo.models.V1alpha1Histogram property),
V1alpha1WorkflowTemplate	(class in	107
argo.models.v1alpha1_workflow_template), 82	value()	(argo.models.V1alpha1MetricLabel property),
V1alpha1WorkflowTemplateCreateRequest		111
(class in argo.models), 144	value()	(argo.models.V1alpha1Parameter property),
V1alpha1WorkflowTemplateCreateRequest		117
(class in argo.models.v1alpha1_workflow_template_create_request),	value_from()	(argo.models.v1alpha1_parameter.V1alpha1Parameter
82		property), 44
V1alpha1WorkflowTemplateLintRequest		value_from() (argo.models.V1alpha1Parameter
(class in argo.models), 145		property), 117
V1alpha1WorkflowTemplateLintRequest		verify_ssl (argo.configuration.Configuration at-
(class in argo.models.v1alpha1_workflow_template_lint_request),	149	
83		volume_claim_templates()
V1alpha1WorkflowTemplateList	(class in	(argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec
argo.models), 145		property), 75
V1alpha1WorkflowTemplateList	(class in	volume_claim_templates()
argo.models.v1alpha1_workflow_template_list),		(argo.models.V1alpha1WorkflowSpec prop-
84		erty), 139
V1alpha1WorkflowTemplateSpec	(class in	volumes() (argo.models.v1alpha1_template.V1alpha1Template
argo.models), 146		property), 59
V1alpha1WorkflowTemplateSpec	(class in	volumes() (argo.models.v1alpha1_workflow_spec.V1alpha1WorkflowSpec
argo.models.v1alpha1_workflow_template_spec),	property), 75	
85		volumes() (argo.models.V1alpha1Template property),
V1alpha1WorkflowTemplateUpdateRequest		128
(class in argo.models), 146		volumes() (argo.models.V1alpha1WorkflowSpec
V1alpha1WorkflowTemplateUpdateRequest		property), 139
(class in argo.models.v1alpha1_workflow_template_update_request),		
85		
W		
V1alpha1WorkflowTerminateRequest	(class in	when() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask
argo.models), 147		property), 20
V1alpha1WorkflowTerminateRequest	(class in	when() (argo.models.v1alpha1_prometheus.V1alpha1Prometheus
argo.models.v1alpha1_workflow_terminate_request),	property), 46	
86		when() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep
V1alpha1WorkflowWatchEvent	(class in	property), 79
argo.models), 147		when() (argo.models.V1alpha1DAGTask property), 100
V1alpha1WorkflowWatchEvent	(class in	when() (argo.models.V1alpha1Prometheus property),
argo.models.v1alpha1_workflow_watch_event),		118
87		when() (argo.models.V1alpha1WorkflowStep property),
value() (argo.models.google_protobuf_any.GoogleProtobufAny		142
property), 4		with_items() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask
value() (argo.models.GoogleProtobufAny property),		property), 20
89		with_items() (argo.models.v1alpha1_workflow_step.V1alpha1Workflow
value() (argo.models.v1alpha1_counter.V1alpha1Counter		property), 79

```
with_items() (argo.models.V1alpha1DAGTask prop-
    erty), 100
with_items() (argo.models.V1alpha1WorkflowStep
    property), 142
with_param() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask
    property), 20
with_param() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep
    property), 79
with_param() (argo.models.V1alpha1DAGTask prop-
    erty), 100
with_param() (argo.models.V1alpha1WorkflowStep
    property), 142
with_sequence() (argo.models.v1alpha1_dag_task.V1alpha1DAGTask
    property), 20
with_sequence() (argo.models.v1alpha1_workflow_step.V1alpha1WorkflowStep
    property), 79
with_sequence() (argo.models.V1alpha1DAGTask
    property), 100
with_sequence() (argo.models.V1alpha1WorkflowStep
    property), 142
workflow() (argo.models.v1alpha1_workflow_create_request.V1alpha1WorkflowCreateRequest
    property), 66
workflow() (argo.models.v1alpha1_workflow_lint_request.V1alpha1WorkflowLintRequest
    property), 66
workflow() (argo.models.V1alpha1WorkflowCreateRequest
    property), 132
workflow() (argo.models.V1alpha1WorkflowLintRequest
    property), 133
workflow_meta() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec
    property), 17
workflow_meta() (argo.models.V1alpha1CronWorkflowSpec
    property), 98
workflow_spec() (argo.models.v1alpha1_cron_workflow_spec.V1alpha1CronWorkflowSpec
    property), 17
workflow_spec() (argo.models.v1alpha1_workflow_template_spec.V1alpha1WorkflowTemplateSpec
    property), 85
workflow_spec() (argo.models.V1alpha1CronWorkflowSpec
    property), 98
workflow_spec() (argo.models.V1alpha1WorkflowTemplateSpec
    property), 146
workflow_template_name()
    (argo.models.v1alpha1_node_status.V1alpha1NodeStatus
    property), 40
workflow_template_name()
    (argo.models.V1alpha1NodeStatus property),
    114
```